Commissioning of the ATLAS reconstruction software with first data

Christian Schmitt
CERN

On behalf of the ATLAS collaboration

IPRD08 Sienna
3rd of October 2008

Overview

- Introduction
 - The ATLAS detector
 - Simulation of cosmic events
- ATLAS offline reconstruction
 - Overview and commissioning
 - Cosmic reconstruction
 - Data quality monitoring
 - Event displays
 - Calibration and alignment
 - Detector performance
 - Software robustness
- Summary

The ATLAS Detector

The ATLAS Muon system

Stand-alone
momentum resolution
 $\Delta p_T/p_T < 10\%$
up to 1 TeV

2-6 Tm $|\eta| < 1.3$
4-8 Tm $1.6 < |\eta| < 2.7$

The ATLAS Calorimeters

LAr hadronic
end-cap (HEC)

LAr electromagnetic
end-cap (EMEC)

EM calorimeter:
180k channels
 $\sim 10\%/\sqrt{E}$ energy
res. for e/γ

Had. calorimeter: 20k channels
 $\sigma/E \sim 50\%/\sqrt{E} \oplus 0.03 (10\lambda)$

The ATLAS Inner Detector

Transition Radiation Tracker (TRT)
(350k channels) with e/π separation

SemiConductor Tracker (SCT)
~6M silicon strips

Pixels: 80M channels

2 Tesla Solenoid
 $\sigma/pT \sim 5 \times 10^{-4} \text{ pT} \oplus 0.01$

Simulation of cosmics in the Pit

- Cosmic muons generated across large area on surface
 - Production vertex within $\pm 300\text{m}$
 - Energy range 10 GeV - 5 TeV
- Muons extrapolated through rock using GEANT
- Apply filter to increase efficiency:
 - Keep only generated tracks pointing into sphere around detector
 - Keep only events that have simulated hit in detector

Samples with different detector geometry and with or without magnetic field

ATLAS Commissioning and impact on software

- **Commissioning of the ATLAS detector in the pit has started more than 2 years ago** with the first cosmic events recorded
- **Periodic dedicated cosmic runs** have taken place with more and more of the individual subdetectors in place
 - Detector geometry changed between periods (open detector) and reconstruction software needed to be adapted
 - Non standard configuration of subdetectors during early commissioning phase (e.g. different active gas in the TRT)
- **Cosmic events require special treatment in several parts of the detectors**
 - Random arrival time of the cosmic muons with respect to LHC clock
 - Dedicated algorithms for reconstruction of muons in the calorimeters
- **Reconstruction software needed to be able to cope with these non-standard situation before corresponding data taking started**

Data flow overview

Offline reconstruction chain

- Simplified overview over reconstruction chain
- Data decoders/simulation provides raw data objects
- Use of conditions information (cabling, calibration, alignment, DCS, ...)
- Detector description
- Standard as well as dedicated cosmics/single beam reconstruction algorithms
- Postprocessing & Analysis
 - DQ Monitoring, Event display

Reconstruction of cosmic muons

- As already mentioned, cosmic muons need a special treatment in the reconstruction
- Cosmic muons are non-pointing** to the center of ATLAS, pattern recognition needs to avoid pointing constraint
- Cosmic muons cross both halves of the detector**; information from both halves needs to be combined for optimal precision
- Calorimeter reconstruction uses modified clustering algorithm for an **enhanced muon detection**
- Cosmic muons are mostly clean events that can be used to **study and optimize the combined muon performance algorithm**
- Improvements to combined tracking (ID+Muon) algorithms and tools
- Muon identification based on calorimeter information

Data quality monitoring

- **Data quality checks** are performed **online** on the output from the event filter as well as **offline** during the reconstruction at the Tier-0
- Dedicated monitoring algorithms histogram different **subdetector quantities** and **correlations between subdetectors**

Event displays

- Event displays are a very important **fast feedback** on what's currently happening in the detector
- E.g. synchronization between detectors, noise, ...
- Also very **helpful for developers** of reconstruction algorithms
- Commissioned using cosmic and first beam events

Beam halo event in the ATLAS Detector

Calibration and alignment loop

- Calibration and alignment algorithms and procedures have been successfully applied to cosmic and first beam events
- Calibration loop tested in addition during several MC based exercises (“Full Dress Rehearsal”)

TRT calibration (cosmics)

Detector performance studies

- Offline performance studies provide **direct feedback to detector commissioning** as well as **important input for simulation verification**
- Example: comparison of measured pT in Muon spectrometer and Inner Detector for both cosmic data and simulation
 - Energy loss in calorimeters for cosmic muons in the top halve (left plot) and bottom halve (right plot) agrees

Software robustness

- Reconstruction software needs not only to be able to **deal with all kind of events** but also be **robust** against beam background and detector effects
 - Beam splash events (bottom right)
 - Noise in the detectors, e.g. HV trip

Months of cosmic data (incl. showers)
has helped to make core offline software
very robust

No crash on high occupancy events

Summary & Conclusions

- **ATLAS offline reconstruction software is being commissioned with first data**
 - Cosmic ray events
 - First single beam events
- **Full offline reconstruction chain is in place**
 - Core reconstruction algorithms including dedicated cosmic algorithms
 - **Data quality monitoring** and **event display**
 - **Calibration** and **alignment** algorithms and procedures
- **Software needs to be robust** against high occupancy events as well as noise in the subdetectors
 - No crash on e.g. beam splash events
- **Important feedback to hardware commissioning** from detector performance studies