Commissioning of the ATLAS Reconstruction Software with First Data

Adam Gibson

University of Toronto

For the ATLAS Offline Commissioning Group and the
ATLAS Collaboration

IEEE NSS 2008: Dresden

October 22, 2008

ATLAS Collaboration

(Status July 2008)

37 Countries
169 Institutions
2500 Scientific Authors total
(1800 with a PhD)

Albany, Alberta, NIKHEF Amsterdam, Ankara, LAPP Annecy, Argonne NL, Arizona, UT Arlington, Athens, NTU Athens, Baku, IFAE Barcelona, Belgrade, Bergen, Berkeley LBL and UC, HU Berlin, Bern, Birmingham, UAN Bogota, Bologna, Bonn, Boston, Brandeis, Bratislava/SAS Kosice, Brookhaven NL, Buenos Aires, Bucharest, Cambridge, Carleton, Casablanca/Rabat, CERN, Chinese Cluster, Chicago, Chile, Clermont-Ferrand, Columbia, NBI Copenhagen, Cosenza, AGH UST Cracow, IFJ PAN Cracow, UT Dallas, DESY, Dortmund, TU Dresden, JINR Dubna, Duke, Frascati, Freiburg, Geneva, Genoa, Giessen, Glasgow, Göttingen, LPSC Grenoble, Technion Haifa, Hampton, Harvard, Heidelberg, Hiroshima, Hiroshima IT, Indiana, Innsbruck, Iowa SU, Irvine UC, Istanbul Bogazici, KEK, Kobe, Kyoto, Kyoto UE, Lancaster, UN La Plata, Lecce, Lisbon LIP, Liverpool, Ljubljana, QMW London, RHBNC London, UC London, Lund, UA Madrid, Mainz, Manchester, CPPM Marseille, Massachusetts, MIT, Melbourne, Michigan, Michigan SU, Milano, Minsk NAS, Minsk NCPHEP, Montreal, McGill Montreal, FIAN Moscow, ITEP Moscow, MEPhI Moscow, MSU Moscow, Munich LMU, MPI Munich, Nagasaki IAS, Nagoya, Naples, New Mexico, New York, Nijmegen, BINP Novosibirsk, Ohio SU, Okayama, Oklahoma, Oklahoma SU, Olomouc, Oregon, LAL Orsay, Osaka, Oslo, Oxford, Paris VI and VII, Pavia, Pennsylvania, Pisa, Pittsburgh, CAS Prague, CU Prague, TU Prague, IHEP Protvino, Regina, Ritsumeikan, UFRJ Rio de Janeiro, Rome I, Rome II, Rome III, Rutherford Appleton Laboratory, DAPNIA Saclay, Santa Cruz UC, Sheffield, Shinshu, Siegen, Simon Fraser Burnaby, SLAC, Southern Methodist Dallas, NPI Petersburg, Stockholm, KTH Stockholm, Stony Brook, Sydney, AS Taipei, Tbilisi, Tel Aviv, Thessaloniki, Tokyo ICEPP, Tokyo MU, Toronto, TRIUMF, Tsukuba, Tufts, Udine/ICTP, Uppsala, Urbana UI, Valencia, UBC Vancouver, Victoria, Washington, Weizmann Rehovot, FH Wiener Neustadt, Wisconsin, Wuppertal, Würzburg, Yale, Yerevan

ATLAS superimposed to
the 5 floors of building 40

ATLAS

(A Toroidal LHC
ApparatuS)

Detector

Length: ~46 m
Radius: ~12 m
Weight: ~7000 tons
~ 10^8 electronic channels
~3000 km of cables

2T central solenoid

Air core toroidal magnets

Barrel and Endcap

Inner Detector (tracking)

Silicon Pixel

Silicon Strips (SCT)

Transition radiation tracker (TRT)

Calorimeter

EM LAr accordion

Hadronic LAr endcaps

Scintillating Tile

hadronic calorimeter

Muon Spectrometer

Monitored Drift Tubes (MDT)

Cathode Strip Chambers (CSC)

Resistive Plate Chambers (RPC)

Thin Gap Chambers (TGC)

ATLAS Reconstruction Framework

- Athena (adapted from LHCb's Gaudi) is the ATLAS software framework
- Used for
 - High-level trigger
 - Simulation
 - Reconstruction
 - Analysis and monitoring
- Runs at
 - Online: High-level trigger, monitoring
 - Tier-0: Prompt reconstruction
 - Calibration centers: Feedback to T0, T1
 - Tier-1: Reprocessing
 - Tier-2, Tier-3 computing centers
- Adapts to commissioning environment
 - Converging on final ATLAS configuration

Simulation for Commissioning

- Unusual particle scenarios
 - Cosmics
 - Beam halo and beam gas from single beams
- Various detector configurations
 - “Garaged” endcaps
 - Misalignments
 - With and without magnetic fields
- All impact how you generate, simulate, and digitize events, and how you reconstruct MC and real data
- e.g. A Cosmic Scenario
 - Generate ± 300 m, 10 GeV – 5 TeV
 - Simulate if pointing to sphere
 - Rock overburden, with asymmetric access shafts
 - Keep events only with simulated hit in detector

Example of Cosmics Simulation: Muon tracks extrapolated to surface

Cosmics data:

Muon impact points extrapolated
to surface as measured by
muon trigger chambers (RPC)

Cosmics MC:

(With main access shafts, missing elevator shafts)

Reconstructed muon position at the surface

muons from small shaft

muons from large shaft

- Full reconstruction runs in the ATLAS control room
- Detector monitoring and data quality
- Event displays
 - 2D and 3D displays, live feeds

First LHC beam events were reconstructed in real time in control room

Silicon tracker monitoring plots

Beam halo event from single LHC beam data

Monitoring track ϕ measured in the inner detector and muon spectrometer would e.g. allow you to see a loss of synchronization

Calibration and Alignment

- Dedicated data/trigger streams for calibration and alignment
 - Some subdetectors use dedicated calibration runs
- Dedicated computing facilities
- 1st pass calibration and alignment within 24 hours
 - Input to bulk reconstruction at Tier-0
- “Best effort” calibration and alignment can be applied to reprocessing at Tier-1 centers
 - Time scale ~months
- Tested extensively with cosmics and MC

Commissioning Reconstruction

- Reconstruction by standard and special-purpose algorithms
- Inner Detector and Muon Spectrometer
 - Tracks not point to nominal interaction point
 - Fewer constraints for fit
- Calorimeters
 - Events not synced with beam clock
 - Phase for optimal filtering calculations is unknown
 - TileCal uses specialized 3-parameter fit
 - LAr uses iterative application of optimal filter coefficients

$$E_{cell} \propto \sum a_i \cdot (s_i - p)$$

Optimal filter coefficients a_i

pedestal p

Pulse samples s_i

Examples of Tracking

- Tracking in various magnetic fields and combined tracking

Single beam event with toroidal field only
Halo-like muons caught up in field

Cosmic event with all magnetic fields, hits
in all barrel detectors, and a combined
track reconstructed

Detector Performance from Cosmics: Energy Reconstructed in Calorimeters

- LAr EM
 - Reconstruct E with 3x3 calorimeter cells, fit to Landau
 - Eta dependence of energy agrees with MC
 - Overall scale in MC has estimated 5% systematic uncertainty
- Tile
 - Muon trajectory fit from tile cells
 - Energy deposited is normalized to distance traveled in tile
 - Energy scale and uniformity tested to 2-3%

Detector Performance from Cosmics: Combined Studies

Track momentum as measured by the muon spectrometer and the inner detector. The effect of energy lost in the calorimeter is clear.

A 5 GeV track observed in the top of the muon spectrometer loses energy in the calorimeter, and is observed e.g. as a 2 GeV track in the inner detector.

Beam “Splash” Events

- Beam dumped on a collimator ~140 m from ATLAS
- Huge “splash” of energy in ATLAS
 - >1000 TeV in calorimeters
 - Hundreds of thousands of hits in muon spectrometer
 - Highest energy events ATLAS will ever record?

Detector Commissioning: Timing with Single Beam Events

- “Splash” events can leave signal in almost all channels in the same event
 - Good source for pulse shape studies
 - Excellent source for detector timing studies
 - Transition Radiation Tracker timing to 1 ns

Measured time, beam from C side

Time after TOF correction

Timing measurements from 700 single beam events in Tile Calorimeter.

Cell timing within modules already calibrated. Differences between modules otherwise difficult to measure.

Software Robustness

- Reconstruction software needs to be robust against a wide range of beam and detector conditions
 - E.g. Tracking that can ignore noisy modules
- Many months of cosmics, and three days of single beam data, has provided much opportunity for debugging

No crashes on high occupancy “splash” events.

In a recent 48 hours of cosmics, 3 crashes in 16,000 reconstruction jobs.

- ATLAS reconstruction software is being commissioned with first data
 - Vetted with many months of cosmics
 - Three days of single beam events
- Full offline reconstruction chain is in place
 - High Level Trigger, Monitoring, and Event Displays
 - Calibration and Alignment
 - Standard and commissioning-specific algorithms
 - Commissioning onsite and offsite (e.g. grid) computing infrastructure
- Operating all ATLAS sub-detectors, and all software as one system
 - Integrating with the infrastructure used for MC physics studies
 - Validate with real, installed detectors
 - Detector performance studies aid hardware commissioning
- Looking forward to LHC collisions in 2009!