Commissioning of the ATLAS High Level Muon Trigger with Beam Collisions

Mark Owen for the ATLAS Collaboration
The University of Manchester

Introduction

The ATLAS experiment at the LHC aims to probe the interactions of particles at the TeV energy scale. In 2010 the LHC is providing proton-proton collisions at $\sqrt{s}=7$ TeV. Once commissioned, the LHC will provide an event rate far higher than the rate ATLAS can write events to disk. The ATLAS trigger system is used to select the most interesting events for physics studies and as such is key to the successful operation of the ATLAS experiment.

The ATLAS High Level Muon Trigger (HLT) aims to refine the signals from the Level 1 muon trigger and efficiently identify muons from pp collisions. The HLT is split into two levels, Level 2 (L2) and Event Filter (EF).

In the early running period the HLT was not needed to control the event rate, allowing the performance of the algorithms to be studied in an unbiased way. This poster presents the results of early studies of the L2 and EF muon trigger algorithms.

ATLAS Muon System

The ATLAS Muon system (Fig. 1) aims to identify muons originating from pp collisions and to provide an independent measurement of the momentum of the muons. The system is made up of precision chambers (MDTs & CSCs) and trigger chambers (RPCs in the central region and TGCs in the forward region). All systems are available to L2 and EF, whereas only the trigger chambers are used at L1. A toroidal magnet system provides a magnetic field of ~ 0.5 T in the central region and ~ 1 T in the forward region.

Figure 1: The ATLAS Muon System.

High Level Muon Trigger

At both L2 and EF muons are reconstructed in the muon system to form a standalone muon. In addition the standalone muons can be combined with inner detector tracks to form a combined muon.

At L2, specialized fast algorithms are used in the reconstruction. At EF, algorithms very similar to the ones used in the offline reconstruction are used. This allows improved resolution relative to the L2 algorithms.

Data Selection

The data in these studies are selected from LHC 7 TeV pp collision runs. At least one muon is required to be reconstructed in the muon system and to be matched to a track in the inner detector tracking system. These requirements suppress the contribution from cosmic ray muons. In addition, the offline muon is required to fulfill the L1 trigger condition, which ensures the HLT algorithms are subsequently processed. Two event displays for muon events are shown in Fig. 2.

Figure 2: Examples of ATLAS events with reconstructed muons.

L2 Muon Trigger Performance

Fig. 3(left) shows the efficiency of the L2 standalone algorithm to reconstruct muons as a function of transverse momentum (p_T), relative to offline muons. Very good performance is observed. Fig. 3(middle) shows the efficiency, including the trigger selection designed to select muons with $p_T > 4$ GeV. Fig. 3(right) shows a comparison with the p_T measurement from L2 standalone muons with offline muons. A good correlation is observed.

Figure 3: Reconstruction efficiency of the L2 standalone algorithm (left) and the efficiency including the 4 GeV selection (middle) as a function of offline muon p_T . Comparison between the p_T measurement at L2 and offline (right).

Fig. 4 shows the efficiency of the L2 combined algorithm as a function of p_T , relative to offline muons. Very good performance is observed. Fig. 4(right) shows a comparison with the p_T measurement from L2 combined muons with offline muons. An improvement in the performance relative to the standalone algorithm is observed.

Figure 4: Efficiency of the L2 combined algorithm as a function of offline muon p_T for $|\eta| < 1.05$ (left) and $|\eta| > 1.05$ (middle). Comparison between the p_T measurement at L2 and offline (right).

EF Muon Trigger Performance

Fig. 5 shows the comparison between the p_T measurement obtained with the EF standalone and combined algorithms. An improvement relative to the L2 performance is observed and the combined algorithm provides a substantial improvement over the standalone algorithm. The efficiency of the standalone algorithm is shown in Fig. 6 and is $> 98\%$ for $p_T > 5$ GeV.

Figure 5: Comparison of the p_T measurement for offline muons with standalone EF muons (left) and combined EF muons (right).

Figure 6: Efficiency of the EF standalone algorithm as a function of offline muon p_T .

Summary

The ATLAS High Level Muon trigger will be used to select many of the physics channels to be studied at ATLAS. In the early running period of the LHC, the performance of the muon trigger algorithms has been studied and good performance has been observed.

Further Details:

<https://twiki.cern.ch/twiki/bin/view/Atlas/AtlasResults>