Offline calibrations and performance of the ATLAS Pixel Detector

Lidia Dell'Asta

Università degli Studi di Milano & INFN

on behalf of the ATLAS Collaboration

Pixel2010

Sep. 6-10, 2010 - Grindelwald

Outline

- The Pixel Detector at the ATLAS Experiment
- Offline calibrations
 - Noise mask
 - Charge sharing calibration
- Performance
 - Spatial resolution
 - Hit-to-track association efficiency
 - Lorentz angle measurement
 - Specific energy loss measurement

The ATLAS Pixel Detector

- **80 M channels**
- Sensor
 - thickness: $250\text{ }\mu\text{m}$
 - **$50\text{ }\mu\text{m}$ ($R\Phi$) $\times$ $400\text{ }\mu\text{m}$ (η)**
 - **328 rows (x_{local}) $\times$ 144 columns (y_{local})**
 - bias voltage: 150 V
- Three precise measurement points up to $|\eta| < 2.5$:
 - **$R\Phi$ resolution $\sim 10\text{ }\mu\text{m}$**
 - **η (R or z) resolution $\sim 115\text{ }\mu\text{m}$**

- Detector operates in an environmental temperature of about **-15°C** and within a **2 T solenoidal magnetic field**.

Detector Calibrations

- **Online calibrations:**

- Threshold tuning
- Time-over-threshold (ToT) calibration
- Time walk and timing

- **“Calibration Loop”:**

- first pass reconstruction of a subset of physics and calibration streams
- calibration program →
- reconstruction

- **Offline calibrations:**

- Noise maps
- Charge sharing

Noise Occupancy

- Noise is masked:

- online: noisy pixels not read out

- offline: pixels excluded from reconstruction.

- For offline noise mask, a dedicated calibration stream is used, with a random trigger on empty LHC bunches.

- Noisy pixels are detected during the offline prompt calibration.

- Noise rate is dominated by few pixels (**usually 300-1500 out of 80M**).

- During the bulk reconstruction, these pixels are masked and the remaining **noise occupancy is lower than 10^{-9} hit/pixel/BC**.

- This corresponds to less than 0.2 noise hits/event when a readout window of 5 BC is used.

Charge Sharing Calibration

- The cluster position can be determined using:
 - the digital position: without taking into account the charge released in each pixel
 - the analog position, which **exploits the charge information to improve the point resolution.**
- The method is based on the charge sharing between the pixels in the cluster:

$$\Omega_x = \frac{Q_{last\ row}}{Q_{first\ row} + Q_{last\ row}} \quad x = x_{centre} + \Delta \left(\Omega_x - \frac{1}{2} \right)$$

$$\Omega_y = \frac{Q_{last\ col}}{Q_{first\ col} + Q_{last\ col}} \quad y = y_{centre} + \Delta \left(\Omega_y - \frac{1}{2} \right)$$

- The position is corrected using the **charge sharing correction Δ** :
 - It depends on the track incident angle and on the cluster dimension.
 - It is determined from the centre-of-the-cluster residuals, as a function of Ω .

Charge Sharing Calibration

Performance

- Spatial resolution
- Hit-to-track association efficiency
- Lorentz angle measurement
- Specific energy loss measurement

Spatial Resolution

- To determine the resolution, the residuals between the cluster position and the track extrapolation are used.
- The impact of the charge sharing algorithm is clearly visible, in the angular regions where the charge sharing correction is computed.
- Resolution is affected by track extrapolation uncertainty (track momentum, detector misalignments...).

Hit-to-Track Association Efficiency

- The association efficiency is determined for active modules: **~99%**.
- Inefficiencies from:
 - track reconstruction (ambiguities, χ^2 cut)
 - dead regions.
- Intrinsic efficiency: **(99.974 ± 0.004(stat.) ± 0.003(syst.))%**.
- Measured with cosmic ray data.
- Inefficiency mainly due to known defective channels.
- 97.3% of the detector is included in data taking.

Lorentz Angle

- The Pixel Detector is immersed in a **2 T magnetic field**.
- The charge carriers drift with an angle respect to the normal to the sensor surface.
- The displacement is $\approx 30 \mu\text{m}$.
- The Lorentz angle corresponds to **the angle at which the cluster size is minimum**. The cluster size distribution is fitted and the angle extracted:

$$F(\alpha) = [a * (\tan \alpha - \tan \alpha_L) + b / \sqrt{\cos \alpha}] \oplus G(\alpha)$$

- The Lorentz angle has been measured during all data taking periods:

Period	$\alpha_L [\text{mrad}]$
Cosmic-ray	205.5 ± 0.5
900 GeV	211.6 ± 2.6
7 TeV	211.3 ± 1.6

Lorentz Angle: T dependence

- The Lorentz angle has a dependence on the sensor temperature.
- The Pixel Detector has changed its operational temperature during the different running periods.
- The T dependence has been computed and found to be (as predicted):

$$- 0.74 \pm 0.06 \text{ mrad/K.}$$

dE/dx

- The specific energy loss in silicon is described by the Bethe-Bloch formula.
- The deposited energy is proportional to the charge collected.
- For a good measurement, a selection at the cluster level has to be applied in order to be sure that the charge has been properly collected:
 - edge of the detector and special pixels regions excluded (97% of tracks, 91% of clusters)
 - use truncated mean, discarding the cluster with highest energy deposit.

Track dE/dx
resolution: 12%

The dE/dx
measurement
is used for
particle
identification
for $p < 1$ GeV.

Conclusions

- The ATLAS Pixel Detector has reached a good performance:
 - noise is masked both online and offline, resulting in an occupancy of less than **10^{-9} hits/pixel/BC**
 - the charge sharing algorithm is calibrated during prompt reconstruction and is important for the improvement of the Pixel Detector's spatial resolution
 - the track association efficiency is **99%**
 - the Lorentz angle in a 2 T magnetic field has been measured to be **211.3 ± 1.6 mrad** (7 TeV collisions) and its temperature dependence is **-0.74 ± 0.06 mrad/K**
 - the charge measurement allows to determine the specific energy loss with a resolution of **12%**
- The Pixel Detector is essential for many physics measurements (see F.Hirsch's talk later this week).

Lidia Dell'Asta
Pixel2010

Back up

The ATLAS Pixel Detector

□ **Barrel region:**

- three layers [$R = 5$ cm (BLayer), 9 cm (Layer1), 12 cm (Layer2)]
- 1456 modules in total
- modules tilted by 20° in the $R\phi$ plane

□ **Forward regions:**

- two end-caps (EC) with three disks each
- 288 modules in total

□ **80 M channels**

- Three precise measurement points up to $|\eta| < 2.5$:
- **$R\Phi$ resolution $\sim 10 \mu\text{m}$**
- **η (R or z) resolution $\sim 115 \mu\text{m}$**

- Detector operates in an environmental temperature of about **-15°C** and within a **2 T solenoidal magnetic field**.
- Low mass carbon-fiber support structure. $\sim 3\%$ of X_0 from each layer.

The Pixel Module

- **Sensor**
 - thickness: 250 μm
 - **50 μm ($R\Phi$) $\times$ 400 μm (η)**
 - bias voltage: 150 V
- 16 Front End (FE) chips
 - bump bonded to the sensor
- Flexible Kapton PCB
 - passive components
 - Module Controller Chip (MCC)
 - FE configuration
 - Trigger Timing & Control
 - Basic event building
- Radiation resistance:
 - Dose: 500 Gy
 - NIEL $10^{15} \text{ n}_{\text{eq}}\text{cm}^{-2}$ fluence

Pixel Types

Cluster Properties

- The **size of pixel clusters** depends on:

- particle incident angle w.r.t. the detector module surface

- readout threshold

- Cosmic rays cross the detector from top to bottom and particles originating in collisions come from the centre of the detector → they feature different incoming direction w.r.t. the detector modules.