LOW MOMENTUM KAON BEAM LINES

31 AOUT 1983

D.E. Lobb

TRIUMF and Physics Department, University of Victoria, Victoria, B.C., V8W 2Y2

Current low momentum (>500 MeV/c) high acceptance (>5 msr) kaon beam lines feature high ratios of charged contaminant particles to kaons. The results of computer calculations on scattering and pion production from K_S^0 decay are presented to indicate some of the sources of this contamination. Criteria for the design of beam lines are discussed and a new beam line design is proposed.

Introduction

Low momentum kaon beam lines at present accelerator facilities are as short as possible in order to provide an acceptable flux of kaons at an experimental location. Design studies are now underway for accelerators that would provide primary proton beam currents 100 to 1000 times greater than those provided by present accelerators.^{1,2} At such a facility, the total number of events per second in an experiment may well exceed the capabilities of the data collection and analysis systems. It then becomes imperative to reduce the number of events caused by contaminant particles. There is considerable scope for improvement in beam purity: contaminant particle to kaon ratios as large as 50:1 have been reported.³

In Table 1 we present some relative cross sections and some contamination ratios at the production target. These contamination ratios are enhanced by the different decay rates for the particles traveling down a channel. In Table 2 we present the ratio of the surviving fraction of pions to the surviving fraction of kaons as a function of the particle energy and the distance from the production target. In the absence of mass selection, the π^-/K^- ratio at the end of a channel of practical length is ~ 2000 . This presents a

Table 1

Calculated relative production cross sections and pion to kaon production ratios for $0.49 < p < 0.51$ GeV/c particles into an elliptical angular acceptance with half axes of 100 mrad in the zx plane and 10 mrad in the yz plane (3.1 msr). The results were obtained by a Monte-Carlo integration of the Sanford-Wang formula⁴⁻⁷ including kinematic reflection.^{8,9} The K^- cross section for 12 GeV protons is set equal to unity.

Proton beam energy (GeV)	K^-	π^-	π^-/K^-	K^+	π^+	π^+/K^+
12	1.00	204.0	204.0	3.06	243.0	80.0
18	1.09	266.0	244.0	2.69	304.0	113.0
24	1.17	324.0	276.0	2.46	370.0	151.0

Table 2

The ratio of the surviving fraction of pions to the surviving fraction of kaons.

Distance from production target (m)	Momentum (GeV/c)		
	0.5	0.7	1.1
10	10.0	5.2	2.8
12	15.9	7.2	3.5
14	25.2	10.0	4.3
16	39.9	13.9	5.3
18	63.3	19.4	6.6

stringent criterion for the quality of a channel: for a π^-/K^- ratio of 1:1, the channel must transmit only $<0.2\%$ of the pions which originally overlapped the accepted kaon phase space.

For particles originating within the primary proton beam spot on the target, practical electrostatic separators can cleanly separate the phase space of ~ 0.5 GeV/c kaons from the phase spaces of the contaminant pions, muons and electrons. In the following sections we present results for the processes of K_S^0 decay and pion scattering which give rise to pion trajectories that, when traced back to the plane of the production target, appear to come from a source disc much larger than the primary proton beam spot. In the final section, we present a design for a 0.55 GeV high purity kaon channel. The reader is also referred to the criteria for design and the proposed channel presented by Berien,³ and the channels proposed by Thiessen,¹⁰ Enge¹¹ and Lobb.¹²

Pions Produced by K_S^0 Decay

The K_S^0 particle has a very short half life resulting in decays very close to the production target: after a 1 m drift the survival of 5 and 10 GeV/c K_S^0 is only 2.4% and 15.6% respectively. The dominant decay mode (68.61%) is $K^0 \rightarrow \pi^+ \pi^-$; the decay products are referred to as cloud pions. In Table 3 we present results obtained using a Monte Carlo program¹² to calculate the effective ratios at the plane of the production target of cloud pions to π^+ and K^+ . These results indicate a cloud pion to K^- ratio of 15:1 at the production target which would be enhanced to a ratio $\sim 24:1$ after a 12 m drift. However, the effective source size is large: for $0.4 < p < 0.6$ GeV/c 68% lie outside a 1 cm radius disc, 48% lie outside a 2 cm radius disc, and 10% lie outside an 8 cm radius disc. A mass slit located at a dispersed horizontal focus images back to the target plane as a horizontal strip. If, for example, this image for pions is $1 < y < 3$ cm only 14% of the effective cloud pion source lies within the image of the mass slit, resulting in a cloud pion to K^- ratio of $\sim 3:1$ at the end of the 12 m channel. Therefore, while cloud pions are a significant source of contamination, they are not the major contributor to π^-/K^- ratios $>10:1$.

Glancing Angle Scattering

If the aperture of a focussing element defines the angular acceptance of the channel, many of the rays that strike the aperture do so at a small angle; for example, if a 50π cm² mrad emittance occupies an aperture of 10 cm half width, the angles of the trajectories with respect to the element axis are <5 mrad. Rays lying outside this emittance will strike the aperture somewhere inside the focussing element.

The program REVMOC¹⁴ has been used to investigate what happens when a pencil beam strikes a plane surface at a glancing angle. This program performs Monte Carlo calculations for multiple and nuclear scattering. (These calculations are not available inside a magnetic field so the actual problem of rays reaching a maximum distance from the central trajectory inside a focussing element cannot be modelled accurately.)

Results are presented for copper and iron in Table 4; the basic geometry is illustrated in Fig. 1. The incoming rays lie in a zx plane while the material

Table 3

The effective ratio at the plane of the production target of pions produced from K_S^0 decay (cloud pions) to $\pi^\pm$ and $K^\pm$ for 25 GeV/c proton momentum and an angular acceptance of 50 mrad half angle (7.8 msr). Also presented are the π^+/K^+ and π^-/K^- ratios for direct production.

p(GeV/c)	cp/ π^+	cp/ π^-	cp/ K^+	cp/ K^-	π^+/K^+	π^-/K^-
0.4 + 0.6	0.006	0.007	0.73	1.52	122	215
0.6 + 0.8	0.009	0.010	0.73	1.33	83	126
0.8 + 1.0	0.013	0.016	0.77	1.38	59	86
1.0 + 1.2	0.014	0.018	0.62	1.15	43	63
1.2 + 1.4	0.018	0.023	0.58	1.14	32	49
1.4 + 1.6	0.017	0.022	0.42	0.86	24	38
1.6 + 1.8	0.016	0.021	0.19	0.64	18	31
1.8 + 2.0	0.015	0.020	0.25	0.55	16	27

Table 4

Glancing-angle scattering for 0.5 GeV/c charged pions incident on 6 cm of iron and copper.

θ_i (mrad)	Percent reflected back			$\bar{\ell}_e$ (cm)		$\bar{\theta}_e$ (mrad)	$(\theta_e)_{rms}$ (mrad)	$(\bar{\theta}_e - \theta_i)$ (mrad)	$(\theta_e - \theta_i)_{rms}$ (mrad)	ϕ_{rms} (mrad)	$(\Delta p/p)$ (%)	$(\Delta p/p)_{rms}$ (%)
	Total	Nuclear scatter	Multiple scatter	Nuclear scatter	Multiple scatter							
RESULTS FOR IRON												
10	51.1	5.7	45.4	2.6	1.3	-31.7	48.4	-77.5	85.6	45.7	-3.9	5.5
20	35.6	7.1	28.5	2.7	2.0	-45.4	62.7	-65.4	78.4	57.4	-5.7	7.1
30	25.4	7.0	18.4	2.8	2.6	-57.4	74.6	-87.4	99.7	66.7	-7.2	8.3
40	18.3	6.5	11.8	3.0	3.0	-65.1	81.9	-105.2	116.3	72.0	-8.1	9.2
50	12.9	5.8	7.0	3.0	3.5	-76.7	93.2	-126.7	137.4	79.8	-8.8	9.9
RESULTS FOR COPPER												
10	50.1	5.8	44.4	2.7	1.4	-30.3	47.4	-40.3	54.4	44.8	-3.7	5.2
20	32.8	6.4	26.4	2.8	2.2	-44.6	63.0	-64.6	78.4	56.3	-5.6	6.8
30	22.6	6.3	16.2	2.9	2.8	-56.7	74.4	-86.7	99.2	66.7	-6.9	7.9
40	16.0	6.2	9.8	3.1	3.2	-68.4	86.1	-108.4	120.3	74.8	-7.8	8.7
50	11.1	5.2	5.9	3.1	3.6	-78.5	96.4	-128.5	140.2	77.7	-8.2	9.2

Fig. 1. The geometry for glancing angle scattering; $p_\perp$ refers to the component of $\vec{p}$ normal to p_z .

boundary lies in a yz plane. The rays that exit the material through this boundary (that are "reflected") make an angle ϕ with respect to the zx plane. Calculations have been performed for 0.5 GeV/c charged pions. The program keeps track of the longitudinal bin in which the first and last scattering events occur; the latter defines the point of exit of the ray from the material.

From Table 4 it can be seen that for 10 mrad angle of incidence, ~50% of the rays are reflected back; even for 50 mrad angle of incidence a substantial number (~10%) are reflected back. The nuclear scattered rays emerge fairly uniformly along the length considered; the multiple scattered rays emerge near the point of incidence for small angles of incidence and fairly uniformly along the length considered for larger angles of incidence. The change in the direction of the emer-

gent rays in the plane of incidence is about twice the change in direction normal to the plane of incidence. The momentum loss for reflected rays is ~5% to ~10%.

For rays initially in a horizontal plane, the large phase space acceptance in this plane will result in some of these rays being accepted by the downstream system. The scattering in the vertical direction for these rays will result in a halo being formed about the vertical beam spot at the mass slit. Referring back to the comment that a number of pions equivalent to ~0.2% of the pions coming directly from the target will result in a π^-/K^- ratio ~1:1 at the end of a channel, we see that trajectories just adjacent to the accepted phase space and trajectories with an initial higher momentum whose momentum loss brings them down into the system momentum acceptance band can easily provide the required number of pions to produce the observed levels of contamination. It is clear that the system phase space acceptance must be defined by slits and collimators and not by the vacuum chamber inside a focussing element.

A Proposed High Purity 0.55 GeV/c Kaon Beam Line

The features of this design are slits located to define the phase space acceptance and a separator section that has an object-image relationship between two achromatic stigmatic foci. Design calculations were performed using TRANSPORT.¹⁶

The channel consists of three parts (see Fig. 2). The 5.6 m long first section, from the production target to the achromatic stigmatic focus as FHV1, defines the beam emittance. Midway within this section a horizontal slit located along the tilted horizontal focal plane defines the momentum acceptance and a vertical slit defines the vertical angular acceptance off the

target. A sextupole (2.5 kG at 12.0 cm radius, 0.2 m long) at this location is used to set $y|\phi\delta = 0_0$ at the mass slit downstream (location FHV2). The uniform field wedge bending magnets have 14.4 kG across a vertical gap of 7 cm, the effective length is 1.0 m. A collimator at FHV1 defines the x, y and θ phase space transmission.

Table 5

Quadrupole parameters for the system presented in Fig.2.

long separator operated with 0.98 MV across 14 cm plate separation (70.3 kV/cm) providing a 6.0 mrad angular separation between the pion and kaon central trajectories. TURTLE¹⁶ calculations indicate a clean separation of the two beam spots: the kaon beam lying within the limits $-0.65 < y < 0.65$ cm and the pion beam lying within the limits $1.05 < y < 2.30$ cm.

Conclusions

Acknowledgements

References

CERN LIBRARIES, GENEVA

CM-P00067218