6 SEP. 1983

CERN LIBRARIES, GENEVA

CM-P00068468

ELECTRON AND PLASMA PHYSICS

ROYAL INSTITUTE OF TECHNOLOGY

S - 100 44 STOCKHOLM SWEDEN

TRITA-EPP-83-05

SPONTANEOUS TRANSFER OF MAGNETICALLY
STORED ENERGY TO KINETIC ENERGY BY
ELECTRIC DOUBLE LAYERS

L. Lindberg and S. Torvén

May 1983

Department of Plasma Physics
Royal Institute of Technology
S-100 44 Stockholm, Sweden

SPONTANEOUS TRANSFER OF MAGNETICALLY STORED ENERGY TO KINETIC ENERGY BY ELECTRIC DOUBLE LAYERS

L. Lindberg and S. Torvén

Royal Institute of Technology, Department of Plasma Physics,
S-100 44 Stockholm, Sweden

Abstract

Current disruptions are investigated in a magnetized plasma column with an inductive external electric circuit. It is found that they persist in spite of the fact that each disruption gives rise to a large inductive over-voltage. This drops off at an electric double layer formed in the plasma where most of the magnetic energy, initially stored in the circuit inductance, is released as particle energy.

Simultaneously as the current disrupts, the potential level at a local potential minimum in the plasma decreases. This is expected to cause the disruption by reflection of electrons.

1. Introduction

In low density plasmas spontaneous current "disruptions" may appear when the electric current density along the magnetic field is sufficiently large. Each disruption is characterized by a marked decrease of the current during a certain time interval, which typically is of the order of many ion plasma periods.

In spite of the relatively numerous observations of this phenomenon, the physical processes causing it are not very well-known. In most observations only the total potential drop over the plasma has been measured, and there seems to be only a few cases (Lutsenko et al. 1975, Torvén and Babić 1975, Iizuka et al. 1982, Stenzel et al. 1982, Torvén and Lindberg 1983) where the spatial distribution of the electric field has been investigated. In these cases the phenomenon has been found to be associated with electric double layers.

In this paper we present investigations of a magnetized plasma column when the external electric circuit is dominated by an inductance L . We find that the current disruptions persist in spite of the fact that the rapid decrease of the circuit current produces inductive voltage drops up to several hundred volts over the plasma. This voltage drop is concentrated to an electric double layer, formed within the plasma, where magnetic energy is released as particle energy. This type of energy transfer has been proposed for applications in cosmic plasmas (Alfvén 1981).

2. Experimental device and methods

The measurements are made in a triple plasma machine (Torvén 1982) consisting of a central chamber and two plasma sources, S_1 and S_2 (Fig. 1). Plasmas are produced in the sources by discharges between heated tungsten filaments and the cylindrical chamber walls. A cylindrical plasma column is obtained in the central chamber by inflow of plasma through the apertures A_1 and A_2 . These determine the diameter of the

column (3 cm) which is radially confined by a homogeneous axial magnetic field (11 mT). Since the aperture diameter is much smaller than the diameter of the main pump, a pressure difference can be maintained between the sources and the central chamber, when gas (argon) is let in at G_1 and G_2 . Effects of impact ionization in the chamber are reduced in this way, and the plasma density there ($5 \cdot 10^{15} \text{ m}^{-3}$) is controlled by the source discharge currents I_1 and I_2 (Fig. 1). The auxiliary electrodes B_1 and B_2 have not been used in this experiment.

The external electric circuit between S_1 and S_2 consists of a voltage source U_0 and an inductance L (110 mH). R (2.6 ohm) is the sum of the series resistance of the inductor and a shunt (1 ohm) for measurement of the current I_L . C (3 nF) is the distributed capacitance relative to ground of the plasma source S_2 and its electric supply circuits. The plasma current I_{p1} is measured by means of another shunt (1 ohm).

Electric potentials are measured with axially and radially moveable electron emitting probes. These are operated close to floating potential by using high impedance voltage dividers (100 Mohm) to limit the probe current. The distributed capacitance (50 pF) of the probe and its heating circuit limits the time resolution. However, it should be noted that it is the dynamic resistance of the plasma, defined by the slope of the probe characteristic at floating potential, which is the relevant resistance determining the time resolution. In the present experiment this has values between 5 and 30 kohm, giving an upper cut-off frequency (3 dB) of at least 100 kHz. The floating potential of the emitting probe is lower than the plasma potential, but still it gives a good measure of the relative variation of the plasma potential in space and time. The same probes are also used as Langmuir probes.

The disruptions appear approximately periodically, and time-resolved potential profiles are obtained by boxcar averaging technique. To improve the reproducibility, the analogue output of a transient recorder, operated in the

pre-triggering mode, is averaged.

3. Investigations of the disruptive plasma

Previous observations (Torvén 1982), without inductance, showed that stable double layers form in this device when a voltage (U_0) is applied between the sources, and that the potential drop across the double layer takes approximately the value of the applied voltage.

Also in the present experiments a steady double layer forms when no inductance is introduced in the circuit. However, when there is a large inductance in the circuit (0.11 H), periodic disruptions occur, and they become most regular when the sources are operated differently. Typical parameters are for S_1 : $p = 20$ mPa, $U_1 = 40$ V, $I_1 = 1.0$ A (temperature limited), and for S_2 : $p = 100$ mPa, $U_2 = 17$ V, $I_2 = 3.5$ A (space charge limited). When no current is drawn between the sources the plasma at $z = 6$ cm outside A_1 has $T_e \approx 11$ eV, $n_e \approx 5 \cdot 10^{15} \text{ m}^{-3}$, and at 6 cm outside A_2 ($z = 54$ cm) $T_e \approx 6$ eV, $n_e \approx 10^{16} \text{ m}^{-3}$. (z is the axial coordinate; $z = 0$ at A_1 , $z = 60$ cm at A_2 .)

3.1 Plasma potential variations during a disruption

With no current flowing the potential distribution along the axis has a local minimum at $z \approx 10$ cm. Between the minimum and A_2 there is an electric field accelerating electrons towards S_2 . This potential distribution prevails also when a low voltage is applied and a steady current flows (e.g. $U_0 = 20$ V, $I_{pl} = 45$ mA). When U_0 is increased to about 30 V, a threshold is passed and disruptions begin to occur sporadically. When U_0 is increased further, the disruption frequency increases and becomes regular, as in Fig. 2(a), (b), (c) for $U_0 = 100$ V. The shape and amplitude of the over-voltage pulses change only little with U_0 . Between the pulses U_{S2} is low compared with U_0 .

It is seen in Fig. 2(a) that the potential of the probe P_1 ($z = 56$ cm) near S_2 closely follows the potential of S_2 , while the potential of the probe P_2 ($z = 49$ cm) does not vary very much and in fact goes down a little. This shows that the whole inductive voltage drop during the disruption is taken up by an electric double layer, which is located between P_1 and P_2 all the time. Fig. 2(b) shows that the potential during a disruption drops also at $z = 30$ cm, but remains almost constant at $z = 11$ cm.

In Fig. 2(c) the plasma current, I_{pl} and the current in the inductance, I_L , are compared. The difference $I_{pl} - I_L$ is the current to the unavoidable distributed capacitance, C . It is seen that I_L goes down to below 20 percent of its initial value during a disruption, which means that 95 percent or more of the stored magnetic energy is transferred to the double layer and will be converted to particle energy.

Fig. 3 shows potential profiles along the axis in the left part of the experimental chamber, recorded at times before, during, and after a disruption. It is seen that the potential minimum becomes deeper during the disruption. As discussed further below the depth of this potential minimum is expected to control the plasma current during a disruption by reflection of electrons.

Fig. 4 shows corresponding potential profiles in the right part of the chamber, where the double layer appears. When the voltage builds up the double layer moves slightly toward S_2 . This is in agreement with earlier observations on stationary double layers (Torvén 1982).

In the intermediate region, $z = 32$ to 43 cm, not covered by Figs. 3 and 4, the plasma potential continues to rise monotonically but with lower gradient than in Fig. 3 for most of the times, but during the interval $t = 0$ to $30 \mu s$ it goes down a few volts to another minimum in front of the double layer ($z = 45$ cm). The level of that minimum is however much above the minimum observed around $z = 12$ cm.

Sampled Langmuir- and emitting probe characteristics at $t = 20 \mu s$ have been measured at three points, (a) $z = 4$, (b) $z = 12$ and (c) $z = 20$ cm (marked in Fig. 3). The characteristics at (a) and (b) indicate approximately Maxwellian distributions with (a) $T_e \approx 12$ eV, $n_e \approx 7 \cdot 10^{15} \text{ m}^{-3}$, (b) $T_e \approx 12$ eV, $n_e \approx 2 \cdot 10^{15} \text{ m}^{-3}$. At (c) the distribution is far from Maxwellian and the average energy is larger than at (a) and (b). The saturation probe current is about half of that at (b). Electrons are obviously accelerated in the region of high electric field between (b) and (c), which may be regarded as a weak double layer.

Characteristics recorded at $t = 40 \mu s$ do not show a high average energy at (c) consistent with the smaller electric field between (b) and (c) at that time.

3.2 Time averages of potential and current

Time averages of the plasma potentials at six different points along the axis are recorded in Fig. 5(a) as functions of the applied voltage, U_0 , which is swept slowly. The average current is recorded in Fig. 6(b). The average plasma potentials at $z = 11, 20, 30$ and 49 cm rise slowly with U_0 up to the threshold value, $U_0 \approx 28$ V, and then saturate at lower values when U_0 is increased further. The average current also saturates at the threshold and then reduces a little.

The average potentials at $z = 56$ and 58 cm on the contrary increase linearly with U_0 , and the average potential difference between P_1 and P_2 is equal to the average potential drop across the double layer. This increase is essentially due to the increasing frequency of the disruptions, because the inductive voltage pulses have approximately the same shapes and amplitudes for different U_0 , and the potential between the pulses is low and gives a negligible contribution to the time-average.

3.3 Discussion

According to Figs. 2(a)-(c) the current drops during the whole over-voltage pulse, and simultaneously the potentials at P_2 and P_3 decrease and reach their lowest values at the end of the over-voltage pulse, i.e. at the current minimum. The potential level at the minimum in the profiles given in Fig. 3 behaves in the same way. The plasma sources are very little affected by the plasma in the central chamber, and the electric current is supplied essentially by electrons from S_1 , because the rapidly increasing double layer voltage drop should prevent electrons from S_2 to reach the potential minimum. Accordingly, the increasing depth of the minimum should cause the disruption by reflection of electrons, and the minimum should act essentially as a virtual cathode (Nezlin 1964).

Such a behaviour of localized potential dips has been observed in numerical simulations, and a model equation describing the deepening of the dip has been proposed (Chanteur et al. 1983, Nishihara et al. 1982). In other simulations "explosive" double layers, appearing recurrently with life times up to a few ion plasma periods (Belova et al. 1980) have been observed. Effects from the external electric circuit have also been simulated (Sato and Okuda 1981, Smith 1982). We believe that there are interesting connections between our experiment and these numerical simulations, and we expect that further investigations will demonstrate this. However, three-dimensional effects may also introduce important differences between the simulations and the experiment.

Once the double layer has formed, another mechanism may also be of importance for the current disruption. When the potential drop of the double layer has reached a level of some tens of volts, all the ions from S_1 are reflected at the layer. Ions from S_2 are accelerated in the layer and enter the plasma with a high velocity. If the flux of ions from S_2 is constant, the density of ions in the plasma on the low potential side of the layer will consequently decrease. Then

quasineutrality requires a decrease of the electron number density, too, as is observed at the potential minimum.

As already mentioned (Sect. 3.1), another weak potential minimum also exists just in front of the double layer ($z = 45$ cm), and its role in the current disruption process should also be investigated.

Between two over-voltage pulses the current rises slowly (Fig. 2). The voltage induced in L is then negative and keeps U_{S2} low: $U_{S2} = U_0 - L \, dI_L/dt$, and the current is regulated by the low value of U_{S2} . This pre-phase of a disruption can be seen as a slowly increasing U_{S2} in Fig. 2. Already in this phase a deepening of the potential minimum is seen in the profiles, Fig. 3, $t = -40$ to $0 \, \mu s$.

Finally the point of current saturation is reached and dI/dt approaches zero. Then U_{S2} rises to U_0 at a rate limited mainly by the capacitance to ground, C . The current starts to decrease due to the deepening of the potential minimum which causes the induced over-voltage pulse. The voltage is in good agreement with the observed dI_L/dt , and the formation of the double layer should be caused by the induced voltage at S_2 .

4. Disruptions in different external circuits

In all the experiments described hitherto we have used $L = 0.11 \, H$ and $C = 3 \, nF$ (stray capacitance). Experiments with other values have also been made. Increasing L to $1.0 \, H$ led to so high over-voltages that break-down (arcing) through the double layer occurred before the voltage maximum. This is due to the relatively high pressure in S_2 in this experiment. To limit the inductive over-voltage we have also increased C and combinations of $L = 0.05, 0.11, 0.21, 1.0 \, H$ and $C = 3, 8, 16, 70$ and $800 \, nF$ have been tested. An example, with $L = 1.0 \, H$, $C = 70 \, nF$, is illustrated in Fig. 6. Here the time scale is a factor of ten slower than in Fig. 2(a)-(c). The voltage pulse has nearly the shape of a half period of a sinusoidal oscillation which ends abruptly with almost no over-swing like

in Fig. 2(a)-(c). The current oscillogram is quite different. The current drops rapidly at first, at a rate similar to that in Fig. 2(a)-(c), and then slowly to a minimum which occurs before the end of the voltage pulse. At the end (e in Fig. 6) another downwards step to the absolute current minimum just after the end of the voltage pulse is very marked.

In a loss-free parallel resonance circuit a sudden complete interruption of the current would produce a sinusoidal oscillation with the voltage amplitude $U = I_0 \sqrt{L/C}$ and period $T = 2\pi\sqrt{LC}$. Presence of losses would increase the period a little and the oscillations would be damped. For the LC-combinations tested we find the shape of the voltage pulse similar to a half period of a sine-wave with a duration of about 1.1 - 1.4 times the half-period for the undamped circuit. The amplitudes are found to be 0.3 to 0.6 times the one calculated for an undamped circuit. This suggests that we should make a distinction between the time of current decrease, defined as the time during which the current decreases rapidly in the beginning of the disruption, and the duration of the over-voltage pulse. In Fig. 2(a)-(c) these are approximately equal, but for large LC-values they become quite different. The time of current decrease is, however, of the same order in the two cases. It can be expected to depend mainly on processes in the plasma, such as ion transport times, but also to some extent on the rate of rise of U_{S2} .

The duration of the over-voltage pulse on the contrary, is mainly determined by the resonance period of the circuit $T/2 = \pi\sqrt{LC}$. When this is much longer than the time of current decrease, the effect of the disruption is to switch from one state of low voltage and comparatively high current to another state of lower current, with a double layer taking up the voltage. The behaviour of the plasma in this state is what can be expected from its static characteristics (Torvén 1982), i.e. a double layer with a voltage determined by the circuit voltage is maintained until most of the energy initially stored in the inductance is transferred to the double layer. The over-voltage pulse is initiated during the time of current

decrease. The current does never go to zero but to a low value approximately corresponding to the static double layer voltage-current characteristic.

The sudden end of the over-voltage pulse is remarkable. The voltage goes to a low, stationary value almost without over-swing. Only a negative over-swing of a few volts can be seen when the oscilloscope amplification is increased. At this time a sudden step-down in the current can be seen, e in Figs. 2(c) and 6. If the voltage decreased further, it would imply a reversal of the current, i.e. electron emission from S_2 , which could become large already at a low reverse voltage since the electron density in S_2 is higher than in S_1 . Reversal of the current has, however, not been observed in the present experiments.

5. Conclusions

When the electric field applied to a plasma column in an inductive electric circuit exceeds a certain threshold value spontaneous current disruptions are excited. A disruption produces an inductive over-voltage in the external circuit, which drops off at a double layer in the plasma.

The energy initially stored as magnetic energy in the inductance is transferred to particle energy in the double layer. Under suitable conditions more than 95% of the energy can be transferred in this way.

Simultaneously as the current disrupts, the potential level at a local potential minimum in the plasma decreases. This is expected to cause the disruption by reflection of electrons.

Acknowledgements

We are very grateful to Mr S. Rydman, Mr J. Wistedt and Mr B. Johansson for technical assistance. We also thank Drs M. Raadu and G. Chanteur for interesting discussions. This work was supported by the Swedish Natural Science Research Council.

References

- Alfvén, H., 1981: Cosmic Plasma (Reidel Publ. Co., Dordrecht, Holland)
- Belova, N.G., Galeev, A.A., Sagdeev, R.Z. and Sigov, Yu.S., 1980: Pis'ma Zh. Eksp. Teor. Fiz. 31, 551 (English transl. JETP Lett. 31, 518).
- Chanteur, G., Adam, J.C., Pellat, R. and Volokhitin, A.S., 1983: Phys. Fluids, in the press.
- Iizuka, S., Michelsen, P., Rasmussen, J.J., Schrittwieser, R., Hatakeyama, R., Saeki, K. and Sato, N., 1982: Phys. Rev. Lett. 48, 145.
- Lutsenko, E.I., Sereda, N.D. and Kontsevoi, L.M., 1975: Zh. Tekh. Fiz. 45, 789 (English transl. Sov.Phys. - Techn. Phys. 20, 498).
- Nezlin, M.V., 1964: Zh. Eksp. Teor. Fiz. 46, 36 (English transl. Sov. Phys. JETP 19, 26).
- Nishihara, K., Sakagami, H., Taniuti, T. and Hasegawa, A., 1982: Symposium on Plasma Double Layers, Risø Report 472, Risø National Laboratory, DK-4000 Roskilde, Denmark.
- Sato, T. and Okuda, H., 1981: J. Geophys. Res. 86, 3357.
- Smith, R.A., 1982: Physica Scripta 25, 413.
- Stenzel, R.L., Gekelman, W. and Wild, N., 1982: Int. Conf. on Plasma Physics, Göteborg, Proceedings, Contributed Papers, p. 27.

Torvén, S., 1982: J. Phys. D: Appl. Phys. 15, 1943.

Torvén, S. and Babić, M., 1975: Proc. 12th Int. Conf. Phenomena in Ionized Gases (Ed. J.G.A. Hölscher and D.C. Schram, North Holland) p. 124.

Torvén, S. and Lindberg, L., 1983: Proc. XVI International Conference on Phenomena in Ionized Gases, Düsseldorf, 1983.

Fig. 1. Schematic picture of the experimental device.
 A plasma column is maintained in the central chamber
 between A_1 and A_2 by inflow of plasma from the sources
 S_1 and S_2 . ---- glass, — stainless steel.

Fig.2. (a) Periodic current disruptions (lowest trace) showing the potential variations of S_2 and of two emitting probes P_1 ($z = 56$ cm) and P_2 ($z = 49$ cm), separated by 7 cm (z is the coordinate measured from A_1).

The inductive voltage (350 V) appears as a potential drop across a double layer in the plasma between P_1 and P_2 . The zero levels are marked in the same order as the traces. $U_0 = 100$ V, $I_{pl} = 105$ mA.

(b) Same conditions as (a) but with two more probes; P_1 ($z = 56$ cm), P_2 ($z = 49$ cm), P_3 ($z = 30$ cm) and P_4 ($z = 11$ cm). P_3 and P_2 show a potential dip of about 20 V whose leading edge is seen to propagate towards S_2 with a velocity of about 10^4 m/s, while the potential of P_4 remains about constant. Compare Fig.3.

(c) Same conditions as (a) and (b). The potentials of P_1 and P_2 are shown together with the plasma current, I_{pl} and the current in the inductance, I_L . Note a sudden decrease in the current (marked g) at the end of the over-voltage pulse.

Fig.3. Potential profiles along the axis in the left part of the experimental chamber at times before, during and after a disruption. The times are indicated by open circles in the inserted oscillogram of a disruption voltage pulse. The curves were obtained by sampled measurements of the floating potential of an emitting probe. Sampled Langmuir probe measurements were made at the points, a,b,c.

Fig.4. Potential profiles showing the double layer in the right part of the experimental chamber at times before and during the build-up of a disruption (cf. Fig.3). The transition from low to high potential is seen to take place within 5 cm or less.

Fig.5. (a) Time averages of the potential variations at six different distances from A_1 when the applied d.c. voltage U_0 is varied slowly. At the threshold for disruptions, $U_0 \approx 28$ V, disruptions begin to occur sporadically. When U_0 is increased further, the frequency of disruptions increases while the wave-forms of each disruption remains approximately the same. For each disruption a transient double layer is formed between the probes P_1 and P_2 . The probes between $z = 11$ and 49 cm indicate a monotonic electric field directed towards A_1 .

(b) Time average of the current I_{p1} .

Fig.6. Oscillograms from an experiment with increased L and C .
 $L = 1.0$ H, $C = 70$ nF. The double layer is maintained during the whole voltage pulse, which has a duration 1.25 times the half period of the undamped LC circuit.
 $U_0 = 100$ V.

The plasma current oscillogram is quite different from Fig. 2(c), and the negative step at a is very marked.

TRITA-EPP-83-05

Royal Institute of Technology, Department of Plasma Physics,
S-100 44 Stockholm, Sweden

SPONTANEOUS TRANSFER OF MAGNETICALLY STORED ENERGY TO KINETIC
ENERGY BY ELECTRIC DOUBLE LAYERS

L. Lindberg and S. Torvén

May 1983, 18 pp. incl. illus., in English

Current disruptions are investigated in a magnetized plasma column with an inductive external electric circuit. It is found that they persist in spite of the fact that each disruption gives rise to a large inductive over-voltage. This drops off at an electric double layer formed in the plasma where most of the magnetic energy, initially stored in the circuit inductance, is released as particle energy.

Simultaneously as the current disrupts, the potential level at a local potential minimum in the plasma decreases. This is expected to cause the disruption by reflection of electrons.

Key words: Double layer, Current disruption, Current limitation, Energy transfer