FSP 101
ATLAS

Performance of the ATLAS Level-1 Calorimeter Trigger in high luminosity proton-proton collisions at the LHC

The ATLAS Collaboration
Presented by Rainer Stamen
(Kirchhoff-Institut für Physik, Heidelberg)

The ATLAS Level-1 Calorimeter Trigger

ATLAS Trigger

- First Level based on custom hardware
 - Reduce 40MHz collision rate to 75 kHz
 - L1Muon and L1Calo
 - Central Trigger Processor
- L2 and EF computing farms:
 - Further reduce rate to 6 kHz and 1 kHz
 - Offline-like software algorithms used in EF

Object Identification in L1Calo

- **Exclusive Objects:** Electrons, Jets, Taus
- **Inclusive Quantities:** Missing E_T , Sum E_T

- Based on:
Trigger Towers
($\Delta\eta \times \Delta\phi = 0.1 \times 0.1$)
up to 60 cells
contribute

Timing and Energy Calibration

Calibration Objectives

- ✓ Trigger Tower synchronisation < 5ns
 - Bunch Crossing Identification
 - Energy measurement (sampling the peak)
- ✓ Energy calibration < 2%

Various calibration techniques

- Pulsar systems (Calorimeter)
 - Initial analogue calibration
- Collision data
 - Fit signal position (at most 3 + 0.5 ns syst.)
 - Final energy calibration (at most 2% syst.)

Pile-up Noise

Challenge

- In time pile-up
 - Overlapping events
- Out of time pile-up
 - Due to long pulse length (400 ns) events influence later events
- Increased energy flow in forward direction (FCAL)
- Pile-up dependent resolution
- Non-linear trigger response with luminosity

Noise cut optimisation

- η -dependent noise cut adjustment (forward: $|\eta| > 2.5$)

Substantial fake $E_{T, \text{Miss}}$ Trigger rate decrease

Hardware Implementation

Analogue Signal Processing

- Analogue Energy Calibration
- Conditioning of analogue input
- Synchronisation
- Digitization of analogue signals

Digital Preprocessing

- Bunch Crossing Identification
- Electronic Noise Filtering
- Digital Energy Calibration

4 channel (trigger tower) Multi Chip Module

Digital Processing

Jet-Energy-Sum Processor

- Based on 0.2×0.2 ($\Delta\eta \times \Delta\phi$) jet elements
- Sliding window algorithm (4×4 jet elem.)

Cluster Processor

- Based on trigger towers
- Sliding window algorithm (2×2)
- Isolation (EM and HAD)

Installed System

(electronic cavern; close to the detector, to minimize latency)

- Receiver System
- PreProcessor
- Cluster Processor
- Jet-Energy-Processor

Efficiency

Performance

- Efficiency as function of transverse momentum
 - Sharp turn-on curve
 - High plateau efficiency
 - Good agreement with simulation
- Efficiency as function of pile-up
 - Pile-up independent high efficiencies

Rates

Luminosity dependence

- Single object triggers
 - Linear scaling with lumi.
 - Fwd. triggers show non-lin. Component
- Multi object triggers
 - Jets show non-linear scaling
- Missing Energy Triggers
 - Non linear scaling with lumi.
 - Increased rate at beginning of bunch train (starting at BCID 104) due to in-time pile-up.