The Compact Muon Solenoid Experiment

Conference Report

Mailing address: CMS CERN, CH-1211 GENEVA 23, Switzerland

26 September 2013 (v4, 07 October 2013)

Calibration and Monitoring of the CMS Electromagnetic Calorimeter

Chiara La Licata for the CMS Collaboration

Abstract

The CMS Electromagnetic Calorimeter (ECAL) is an homogeneous and hermetic calorimeter with high granularity and fast response, designed to provide high resolution measurements of electron and photon energy. Precise calibration of the ECAL must be performed in situ at the LHC, in order to achieve and maintain its design performance and to fully exploit the physics reach of CMS. Several techniques have been developed for the inter-calibration of ECAL using collision data. These methods are based on the reconstruction of the invariant mass peak of unconverted photons from low mass particle decays (π^0 and η) and the azimuthal symmetry of the average energy deposition at a given pseudorapidity. Further inter-calibration is carried out by using isolated electrons from W and Z bosons to compare the energy measured in ECAL to the momentum of the reconstructed track. The absolute calibration of the energy scale is performed using Z decays into electron-positron pairs. Changes in the ECAL response due to crystal radiation damage and changes in photo-detector output must be monitored. A system based on the injection of laser light into each crystal is used to track and correct for these variations during LHC operations.

Presented at *ICATPP Villa Olmo 14th ICATPP Conference on Astroparticle, Particle, Space Physics and Detectors for Physics Applications*

Calibration and Monitoring of the CMS Electromagnetic Calorimeter

C. La Licata on behalf of the CMS Collaboration

Università degli Studi di Trieste e Sezione INFN di Trieste

The CMS Electromagnetic Calorimeter (ECAL) is a homogeneous and hermetic calorimeter with high granularity and fast response, designed to provide high resolution measurements of electron and photon energy. Precise calibration of the ECAL must be performed in situ at the LHC, in order to achieve and maintain its design performance and to fully exploit the physics reach of CMS. Several techniques have been developed for the intercalibration of ECAL using collision data. These methods are based on the reconstruction of the invariant mass peak of unconverted photons from low mass particle decays (π^0 and η) and on the azimuthal symmetry of the average energy deposition at a given pseudorapidity. Further intercalibration is carried out by using isolated electrons from W and Z bosons decays to compare the energy measured in ECAL to the momentum of the reconstructed tracks. The absolute calibration of the energy scale is performed using Z decays into electron-positron pairs. Changes in the ECAL response due to crystal radiation damage and changes in photo-detector output must be monitored. A system based on the injection of laser light into each crystal is used to track and correct for these variations during LHC operations.

1. Introduction

The Compact Muon Solenoid (CMS) electromagnetic calorimeter (ECAL)¹ is a high resolution, fine-grained calorimeter, designed to provide excellent performance for energy and position measurements. These requirements are essential to explore the large new physics search program of the CMS experiment, in particular the study of the physics of electroweak symmetry breaking through the Higgs decay channel into two photons. At low mass, the Higgs mass resolution is dominated by the instrumental resolution. ECAL is a scintillating crystal calorimeter and consists of a central Barrel, $|\eta| < 1.479$, made of 61200 lead tungstate crystals, each read out by avalanche photodiodes (APDs), and of two lateral ($1.478 < |\eta| < 3.0$) End-caps (EE), with a total of 14648 crystals read out by vacuum phototriodes (VPTs). In the high η region ($1.653 < |\eta| < 2.6$), a Si/Pb preshower detec-

tor (ES) enhances the π_0/γ separation in the forward region. The choice of lead tungstate crystals (PbWO_4) provides a very compact electromagnetic calorimeter system with high granularity due to the high density of the crystal (8.3 g/cm^3), the small Molière radius (2.2 cm) and the short radiation length (0.89 cm). The high performance must be maintained in the harsh radiation environment and beam crossing rates at the Large Hadron Collider (LHC). For these reasons continuous monitoring and calibration of the calorimeter are crucial ingredients to reach the design performance. In this report the strategy used to calibrate and monitor the calorimeter is discussed and the performance reached by ECAL in 2012 is presented. An electromagnetic particle impinging on the calorimeter deposits its energy over several ECAL crystals and the measurement of the energy requires a sum over the corresponding channels. The energy is computed using Eq. 1 and involves the sum of the ADC signal amplitudes (A_i) of each channel of the cluster, corrected for imperfect clustering and geometry effects ($F_{\gamma,e}$), for time response variation (L_i) and calibrated with the ADC-to-energy conversion factor (G). The different response of each channel has to be corrected by applying the intercalibration constants (c_i). The preshower energy E_{ES} has to be added in the case of supercluster in the forward region.

$$E_{\gamma,e} = F_{\gamma,e} \cdot \left[\sum_{i \in \text{cluster}} G \cdot c_i \cdot A_i \cdot L_i + E_{ES} \right] \quad (1)$$

2. ECAL Monitoring

The ECAL crystals have been chosen for their properties that ensure a high performance calorimeter despite the exposure to a high dose rates. The scintillation mechanism in the crystal is not affected by radiation. However the response changes under irradiation because of the formation of colour centers inside the crystals, reducing the transparency. In the endcap the response changes also have a significant component from VPT conditioning. A monitoring system² is used to track and correct for these variations (L_i) during LHC operation, as well as to track the partial recovery of the crystals that occurs when no radiation is present (periods without beams) or during low luminosity runs (Heavy Ion runs). The laser monitoring system is based on the injection of laser light close to the emission peak of scintillation light from PbWO_4 in each crystal and into a pn diode that is used as a reference. Response corrections are then delivered in less than 48 h for the prompt reconstruction of CMS data. The channel response to laser light as a function of time for 2011 and 2012 data and for different η regions

is shown in Fig. 1. The response drops during data taking but it partially recovers due to the thermal annealing of the colour centres.

Fig. 1. Relative response to laser light (440 nm in 2011 and 447 nm in 2012) measured by the laser monitoring system, averaged over all crystals in bins of pseudorapidity, for the 2011 and 2012 periods.

3. Calibration procedure

Variations in channel response (c_i) ascribed to intrinsic differences across crystals, photodetectors and the electronics readout chain have to be treated through the calibration procedure. The ECAL channels are calibrated by using both absolute and relative calibrations between channels.³ The energy scale (absolute calibration) is determined by using $Z \rightarrow e^+e^-$ events and extracting the dielectron invariant mass distribution. Different inter-calibration methods have been developed *in situ* using collision data. The first method involves the reconstruction of the invariant mass peak of pairs of unconverted photons from the decay of π^0 and η mesons. This provides fast feedback and is facilitated by a dedicated CMS trigger stream. The method is also used to monitor the stability of the calibration system with time. The second method is based on the comparison between the energy, E , measured in ECAL and the momentum, p , measured in the Tracker for isolated electrons from the decays of W and Z bosons. The third technique is based on the assumption that, for a large number of minimum bias events, the total transverse energy deposited in a ring of crystals at a given pseudorapidity is expected to be the same. The precision of these three methods has been determined by the comparison of the *in situ* constants and those

Fig. 2. Left plot: Precision of the intercalibration methods and their combination as a function of η for the EB (right) and EE (left).

derived at beam tests. Results obtained in the 2012 run are shown in Fig. 2 as a function of pseudorapidity for EB and EE and the precision of the combination of the three methods is also reported. The precision of the combination is better than 1% in EB and from 2% to 5% in EE.

4. Mass and energy resolution

$Z \rightarrow e^+e^-$ events are used to determine the ECAL mass and energy resolution.⁴ To estimate the instrumental contribution to the Z boson width, the invariant mass distribution is fitted with a Breit Wigner convoluted with a Crystal Ball function. The parameters of the Breit Wigner are fixed to the PDG values of Z mass and width. The tail parameters of the Crystal Ball function are fixed to the values obtained from the Monte Carlo simulation. The width parameter of the Crystal Ball function is taken as a measure of the mass resolution. In Fig. 3 the mass resolution as function of time is reported for EB and EE. The Z boson mass resolution is 1.7% in the barrel and about 2.8% in the endcap regions. The electron energy resolution is derived from an unbinned maximum likelihood fit to the e^+e^- invariant mass distribution, where the energy resolution of each electron is floated as a function of η . Using the full statistics available in 2012, the electron energy resolution (Fig. 4) obtained is of the order of 2% in EB while it is better than 5% in EE.

5. Conclusions

Excellent energy resolution has been achieved with the CMS ECAL. The resolution was crucial for the successful discovery of the Higgs boson

Fig. 3. Z mass resolution as a function of time for EB (right) and EE (left). Resolution and stability improve after re-reconstruction with dedicated calibrations obtained with full 2012 data.

Fig. 4. Relative energy resolution for the inclusive sample (left) and low bremsstrahlung electrons (right) in data and MC as a function of the η variable. The resolution is shown separately for MC (red), prompt reconstructed (gray) and re-reconstructed data (blue).

through its decay to two photons, and is a consequence of the intrinsic ECAL resolution, which has been verified at test beams, the stability of ECAL channel response with time, and the precision of the energy calibration.

References

1. The CMS Collaboration, *The CMS experiment at the CERN LHC*, JINST 3 (2008) S08004. 732 doi:10.1088/1748-0221/3/08/S08004.
2. M. Anfreville et al., *Laser monitoring system for the CMS lead tungstate crystal calorimeter*, Nuclear Instruments and Methods in Physics Research A, vol. 594, pp. 292320, Sep. 2008.
3. The CMS Collaboration, *Electromagnetic calorimeter calibration with 7 TeV data*, 2010, CMS PAS EGM-10-003.
4. The CMS Collaboration, *Energy calibration and resolution of the CMS electromagnetic calorimeter in pp collisions at $\sqrt{s} = 7\text{ TeV}$* , J. Inst. 8 (2013) - P09009.