13th Pisa Meeting on Advanced Detectors
24–30 May 2015

Preparation and commissioning of LHCb for Run-II of LHC

Albert Puig on behalf of the LHCb collaboration

The LHCb experiment

[JINST 3 S08005 (2008)]

[Int. J. Mod. Phys A 30 (2015)]

The LHCb experiment

[JINST 3 S08005 (2008)]

[Int. J. Mod. Phys A 30 (2015)]

Forward-arm spectrometer

$\sigma(b\bar{b}) = 284 \pm 53 \mu\text{b}$ at $\sqrt{s} = 7 \text{ TeV}$ [PLB 694 209]

$\sim 100,000 \text{ } b\bar{b}$ pairs/second

The LHCb experiment

[JINST 3 S08005 (2008)]

[Int. J. Mod. Phys A 30 (2015)]

Forward-arm spectrometer

$\sigma(b\bar{b}) = 284 \pm 53 \mu\text{b}$ at $\sqrt{s} = 7 \text{ TeV}$ [PLB 694 209]

$\sim 100,000 \text{ } b\bar{b} \text{ pairs/second}$

High trigger rate

Hardware trigger feeds 1 MHz to software trigger

Output of 5kHz to disk in Run-I

90% efficient for muon channels, 30% for multibody hadronic states

The LHCb experiment

[JINST 3 S08005 (2008)]

[Int. J. Mod. Phys A 30 (2015)]

Forward-arm spectrometer

$\sigma(b\bar{b}) = 284 \pm 53 \mu\text{b}$ at $\sqrt{s} = 7 \text{ TeV}$ [PLB 694 209]
~100,000 $b\bar{b}$ pairs/second

High trigger rate

Hardware trigger feeds 1 MHz to software trigger
Output of 5kHz to disk in Run-I
90% efficient for muon channels, 30% for multibody hadronic states

Precise tracking and vertexing

vertex resolution: $20 \mu\text{m}$ IP resolution
momentum resolution: $\Delta p/p$ of 0.4% @ 5GeV/c, 0.6% @ 100GeV/c

The LHCb experiment

[JINST 3 S08005 (2008)]

[Int. J. Mod. Phys A 30 (2015)]

Forward-arm spectrometer

$\sigma(b\bar{b}) = 284 \pm 53 \mu\text{b}$ at $\sqrt{s} = 7 \text{ TeV}$ [PLB 694 209]
~100,000 $b\bar{b}$ pairs/second

High trigger rate

Hardware trigger feeds 1 MHz to software trigger
Output of 5kHz to disk in Run-I
90% efficient for muon channels, 30% for multibody hadronic states

Precise tracking and vertexing

vertex resolution: $20 \mu\text{m}$ IP resolution
momentum resolution: $\Delta p/p$ of 0.4% @ 5GeV/c, 0.6% @ 100GeV/c

Excellent particle identification

π/K separation: K ID efficiency of 95% with 5% misidentification
powerful muon identification of 97% with 1–3% misidentification

Run-I at LHCb

- Very successful physics program, thanks to the excellent performance of the detector and the LHC
 - Heavy flavor physics: CP violation, very rare B decays, charm physics, CKM matrix
 - Central Exclusive Production
 - Spectroscopy
 - p - Pb collisions
 - ...

Run-II: Physics at 13 TeV

- $b\bar{b}$ and $c\bar{c}$ cross-sections expected to increase more than 60% in Run-II
- Larger cross-sections, especially charm, demand a more efficient trigger
 - *Solution*: move more of the offline selections into the trigger
 - *Requirement*: offline-like tracking and alignment, Particle Identification (PID) at trigger level
- LHCb to continue pursuing its physics program with increased statistics
- Addition of HeRSChel (*High Rapidity Shower Counters for LHCb*) to expand the physics reach in Central Exclusive Production studies

Infrastructure LS1 activities

- Enhance detector stability and performance
 - Replacement of 1 section of the beampipe
 - Repair/replacement of problematic hardware and electronics
 - Power supply and cooling system maintenance
 - Consolidation of gas system
- New magnetic field measurement
- New control room (under construction)

Online

- Detector Control PCs moved to Virtual Machines
 - Increased failure recovery speed
 - All control PCs can run in one of two chassis clones
- ECS software changed, operating systems updated
- Bandwidth to storage increased to 1.5GB/s (2 reads and 1 write) ~ 5GB/s raw
- Trigger farm upgrade
 - Double CPU capacity, upgrade of older servers to state-of-the-art
 - Addition of 5PB of mirrored local storage to accommodate the new trigger scheme

Trigger in Run-I

- L0 Hardware trigger, using muons and calorimeter
- High Level Trigger (HLT), implemented in software
 - *HLT1*: simplified tracking
 - *HLT2*: full reconstruction, with differences wrt offline
- Deferred trigger
 - L0-accepted data buffered to disk for processing during interfill gaps
 - Extra time used to lower reconstruction thresholds in HLT

Trigger in Run-II

- New trigger strategy based on experience from Run-I and increased needs for Run-II
 - All HLT2 processing deferred
 - Calibration and alignment of subdetectors will be performed on a fill-by-fill basis [see Z. Xu and M.Tobin poster]
 - PID available in HLT2
 - HLT processing much closer to offline
- Larger CPU farm, thus more time
- Increase output rate to 12.5 kHz

Trigger streams in Run-II

Larger HLT2 rate means larger offline storage requirements

+

Online reconstruction is going to be almost the same as offline

Perform some high-rate analyses online!

- The Turbo stream [S. Benson and A.Puig poster] is designed to save part of the HLT2 bandwidth in a special format that allows bypassing offline reconstruction and directly perform analysis

(Trigger) Optimizations for Run-II

- Optimization and speed up of code
 - Large areas of the code base are heavy on vector algebra, build faster implementation by exploiting vector instructions, with gains of 30% on several important algorithms
 - New algorithms allow to improve the performance and/or reduce execution time
- Add linear extrapolation of tracks from VELO to TT as input to forward tracking
 - x3 faster reconstruction chain and x4 less ghost rate
- Primary vertex reconstruction updated and reoptimized, same for online and offline

Vertex Locator (VELO)

- Primary tracking and vertexing detector
- Silicon strip sensors in r and φ , separated from LHC vacuum by 300 μm Al foil
- Close to beam (8 mm), so built with retractable halves
- Great performance in Run-I, ready for Run-II
 - Effect of radiation according to expectations

Vertex Locator in Run-II

- Non-uniform bias voltages due to non-uniform radiation damage to ensure good charge collection efficiency (CCE)
 - Special CCE scan data taking for monitoring
- Low voltage system refurbished, replacement of power supplies
- ECS and monitoring software improvements
- VELO alignment performed fill-by-fill
 - Improvement of the performance, since the VELO opens and closes every fill

Silicon tracker

- Two sets of silicon trackers
 - *Upstream of the magnet (TT)*, with 1 station of 4 detection layers
 - *Downstream of the magnet (IT)*, with 3 stations of 4 detection layers
- Degradation in performance of cooling during Run-I
 - Lubricant mixing with coolant, manual recirculation every 2–3 days in 2012
 - New chiller installed for Run-II

Silicon tracker in Run-II

- IT too low on frame to compensate for beam pipe movement
 - New mechanics installed to adjust to nominal position
- Brandeis CCD Angle Monitor (BCAM) monitoring system installed
- ECS and monitoring software improvements
- Alignment to be performed fill-by-fill

Outer tracker

- Straw tube tracker downstream of magnet with max 50 ns drift time
- It surrounds the IT, with 3 stations of 4 detection layers each
- No aging effects observed during Run-I
 - Addition of O_2 to the straw tube gas mixture to help

Outer tracker in Run-II

- Studies performed to assess the effect of 25 ns running on performance
 - Since maximum drift time is 50 ns, spillover effects are expected to be larger
- The spillover from neighbouring bunch crossings is seen in the drift time distribution
 - Straw occupancy is increased as a result
- Operation of the detector will be as expected

RICH

- Two Ring Imaging CHerenkov detectors
- Excellent separation of K , π , ρ
- Hybrid Photon Detectors (HPDs)
 - Able to detect individual photons
 - Aging problems seen in Run-I due to vacuum degradation (~3% failure per year)

RICH1 Aerogel removal

- Difficult to integrate in Run-II HLT
 - Large rings, many photon candidates, very CPU intensive
- Harsher environment than designed
 - Higher instantaneous luminosity, photon multiplicity
 - Slightly lower Aerogel performance than expected
- Removal of Aerogel provides
 - Improved π/K separation, lower radiation length
 - More accurate efficiency determination (same algorithms online and offline)

RICH in Run-II

- Fill-by-fill calibration, allowing the use of accurate PID information in HLT2
 - Gas refractive index
 - HPD image drift
 - Mirror alignment
- 82 new HPDs with almost zero ion feedback
 - Improved design with getter strips
 - Best HPDs in RICH1 to avoid frequent refurbishment
 - HPD settings improved for L0 rate of 1 MHz

Calorimeters

- Sampling calorimeters
- Composed of 4 detectors
 - SPD/PS read out with multi-anode pixel PMT
 - ECAL/HCAL read out with single anode PMT
- During Run-I
 - Regular HV calibration needed
 - Aging in ECAL/HCAL PMTs, gain adjustments during interfill gaps

Calorimeters in Run-II

- Replacement of fibers for ECAL LED monitoring system by quartz ones
 - Aging due to radiation damage, not seen in detector fibers
- Calibration to be performed fill-by-fill
 - Automatic
 - More frequent gain adjustments
 - Method based on detector occupancy

Muon system

- 5 stations of drift chambers interleaved with iron absorbers
 - Multi Wire Proportional Chambers (MWPC)
 - Triple GEM in inner region of M1
- First station (M1) placed upstream of the calorimeters to improve transverse momentum in L0 trigger

Muon system in Run-II

- HV channel doubling to improve redundancy
- Improvement of MWPC grounding to reduce noise and increase stability
- Reconditioning of some chambers to prevent discharges by flipping HV polarity
 - O₂ used as cleaning agent
- Shielding added behind last station (30t of iron) to reduce backslash

HeRSChel

- Low pileup in Run-II offers good opportunity for Central Exclusive Production (CEP) studies in LHCb
- In Run-I, large background from diffractive events with high-rapidity particles outside the LHCb acceptance
- HeRSChel idea is to tag background in a very forward region ($5 < |\eta| < 8$)
 - Potential integration into L0 trigger
 - Luminosity measurement and understanding of machine backgrounds also benefitted

HeRSChel

- Install scintillation counters in the tunnel (where accessible) to detect showers from high-rapidity particles hitting the beampipe
 - 5 stations of 4 plastic scintillators with PMT
- Similar systems successfully deployed at CDF and CMS

HeRSChel status

- Detector installation finished
- TED runs show detectors are working well
- Final commissioning of readout and trigger electronics
 - Commission LED system integrated to the LHCb readout
 - Install electronic system to integrate to central trigger
 - Implement the trigger logic in front-end FPGA chips

First collisions

- First collisions delivered on 5–6 May
 - 1 colliding + 1 non-colliding nominal bunch at 450 GeV
 - Global time alignment done
 - Calorimeter sides time-aligned
 - Data taken with complete detector
- 13 TeV collisions delivered on 21 May

SMOG test

- Inject gas into the VELO with SMOG (System for Measuring the Overlap with Gas) and test the luminosity calibration configuration
- Test readout chain including HLT1
 - L0 configuration as in physics
 - HLT1 rate of $\sim 5\text{kHz}$ with 200Hz physics
 - Afterwards, run HLT2 processing pass

Start gas injection

Stop gas injection

SMOG test

- Inject gas into the VELO with SMOG (System for Measuring the Overlap with Gas) and test the luminosity calibration configuration

- Test readout chain in
 - L0 configuration as in
 - HLT1 rate of $\sim 5\text{kHz}$
 - Afterwards, run HLT

SMOG test: subdetectors

- VELO position monitoring working
- Silicon Tracker and Outer Tracker timing OK
- Cherenkov rings seen in RICH1 and RICH2
- Calorimeter time alignment begun, new automatic gain adjustment running
- Muon timing checked to be consistent with 2012
- HerSCHel showing signal

Conclusions

- A lot of work has been done during LS1 to get LHCb ready for Run-II: consolidation of infrastructure, upgrades and refurbishment of detectors, etc
- A new trigger scheme has been implemented, allowing for better reconstruction and more physics rate
 - Online reconstruction to offline level, so analysis selections can be performed at HLT2
- A new detector (HerSCHel) has been installed to expand the physics program
- First collisions successful, detector in good shape
- Eagerly awaiting 13 TeV data, stay tuned for the first measurements!

Thank you!

Trigger optimizations for Run-II

- Pattern recognition: vectorization of Hough transform
- Track reconstruction
 - Adjustment of precision of magnetic field, Bethe-Bloch energy loss computation
 - Vectorization of magnetic field interpolation, matrix operations in Kalman filter
- Coding improvements
 - Reduce copying of `std::string`, usage of `dynamic_cast`
 - Use contiguous containers (`std::vector`, `std::array`)
 - Improve memory usage with `reserve`, bitfields instead of booleans, ...
 - Write vectorized APIs, use SIMD