The Timepix3 Telescope and Sensor R&D for the LHCb VELO Upgrade

Elena Dall'Occo

on behalf of the LHCb VELO Upgrade Group

IEEE NSS/MIC 2018

Sydney 10-17/11/2018

VELO Upgrade

LHCb Detector (Upgrade 2019/2020)

Luminosity:

$$4 \times 10^{32} \text{ cm}^{-2} \text{ s}^{-1} \xrightarrow{\times 5} 2 \times 10^{33} \text{ cm}^{-2} \text{ s}^{-1}$$

Vertex Locator

from strip sensors to
hybrid pixel detectors

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Prototype Sensors

Challenges

- Increased data rate and fluence
- Non uniform radiation exposure:
 - 8×10^{15} 1 MeV n_{eq}/cm^2 at the close edge
 - 0.2×10^{15} 1 MeV n_{eq}/cm^2 at the outer edge
- Minimise material in the acceptance

Requirements

- Sensor must withstand 1000V at the end of lifetime
- Charge collection $> 6000 e^-$
- Efficiency $> 99\%$ and uniform
- Excellent spatial resolution
- Narrow edge

for impact parameter resolution
minimise material before the first measured point

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Prototype Sensors

- two different vendors (HPK and Micron)
- n-on-p and n-on-n type
- different thickness (150-200 μm)
- different implant width (35-39 μm)
- different guard ring size (150-600 μm)
- irradiated up to a fluence of $8 \times 10^{15} \text{ 1 MeV } n_{\text{eq}}/\text{cm}^2$ (uniformly and non-uniformly irradiated)

HPK n-on-p

Micron n-on-p

Micron n-on-n

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Sensors tested in combination with Timepix3 ASIC

Timepix3

- matrix 256x256 square pixels
- pixel size 55x55 μm^2
- can measure simultaneously ToA and ToT (can be converted to charge)
- gives a timestamp with 1.6 ns resolution (bin size of the TDC)
- calibration with test pulse, cross checked with radioactive sources

ideal for sensor testing!

Timepix3 Telescope

- Operated on a 180 GeV hadron beam at the CERN SPS

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Timepix3 Telescope

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Performance: Timing Resolution

- Telescope planes are time aligned

Mean of the biased track time residuals

Biased time residuals for one plane after time alignment

- Measured intrinsic resolution of each plane ~ 1.1 ns
- Telescope time resolution:

$$\sigma_{\text{telescope}} = \sigma_{\text{intrinsic}} / \sqrt{N_{\text{planes}}}$$

**Telescope time resolution 0.39 ns
at 150 V bias voltage**

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Performance: Spatial Resolution

- pointing resolution depends on: resolution of each plane, space between planes and material traversed
- pointing resolution is obtained from simulation
- simulation is validated by comparing resolution of telescope planes obtained from data and simulation

Pointing resolution at DuT position $< 2 \mu\text{m}$

- resolution per plane $\sim 5 \mu\text{m}$ in both x and y directions
- good alignment: residual variation across the the beam spot $< 0.2 \mu\text{m}$
- width very stable

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Performance: High Rate

- fraction of non-associated clusters studied as a function of rate
- no significant dependence found
- rate limited by the SPS beam: the telescope should be able to operate at least twice the maximum rate

No degradation in efficiency up to the high rate of 5 million tracks / s / cm²

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- **Sensor Characterisation**
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

HV Tolerance

sensors must withstand 1000 V after full fluence
(in both hottest and coolest part)

typical fluence profile at IRRAD

sensors non-uniformly proton irradiated at IRRAD

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Charge Collection

sensors must collect >6000 e⁻ at -1000V after full irradiation

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Efficiency

efficiency must be > 99% everywhere in the sensor

- $\epsilon = n_{\text{DUT_Associated_Clusters}} / n_{\text{Tracks}}$
- non irradiated assemblies are fully efficient over the entire pixel cell
- irradiated assemblies show inefficiencies at pixel corners at lower applied V, but are fully efficient at 1000 V

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Spatial Resolution

before irradiation

spatial resolution must be excellent after full dose

- analog resolution: position reconstructed using the Centre of Gravity technique
- binary resolution: position reconstructed ignoring the charge information

after irradiation

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

- Guard ring structure to gradually reduce the electric field towards the edge of the sensor
- Occupancy is already higher close to edge
- Distortion of the electric field that would lead to a worst spatial resolution must be avoided

sensor must be fully efficient up to edge

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

The sensor is rotated at a very large angle (83-89 deg) with respect to the beam

Exploiting the relation between the hit pixel position in the cluster and the depth sampled by the track:

- Charge collection as a function of depth
- Time required to cross the threshold as a function of depth

Non-irradiated

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

The sensor is rotated at a very large angle (83-89 deg) with respect to the beam

Exploiting the relation between the hit pixel position in the cluster and the depth sampled by the track:

- Charge collection as a function of depth
- Time required to cross the threshold as a function of depth

Uniformly neutron irradiated ($8 \times 10^{15} \text{ 1 MeV n}_{\text{eq}} \text{ cm}^{-2}$)

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

Non uniformly proton irradiated full fluence

typical fluence profile at IRRAD

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

Non uniformly proton irradiated full fluence

typical fluence profile at IRRAD

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

Non uniformly proton irradiated full fluence

typical fluence profile at IRRAD

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

Non uniformly proton irradiated full fluence

typical fluence profile at IRRAD

HPK n-on-p, 200 μm thick

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Summary & Outlook

- Timepix3 telescope has outstanding performance
- Allowed to characterise a large variety of prototype sensors for the LHCb VELO upgrade
- 400 sensors already delivered and under test
- First VELO upgrade modules are being constructed

VELO modules tested in beam a couple of weeks ago using the Timepix3 telescope!

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Back Up

Grazing Angles

The sensor is rotated at a very large angle (83-89 deg) with respect to the beam

- long tracks through multiple adjacent pixels
- The number of columns traversed by the track depends on the angle
- a fit of the nominal cluster length as a function of the angle allows to extract the effective **depletion depth!**

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Spatial Resolution

before irradiation

**spatial resolution
as a function of angle**

**fractions clusters
as a function of angle**

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

Grazing Angles

Non uniformly proton irradiated full fluence

- VELO Upgrade
- Prototype Sensors
- Timepix3 Telescope
 - Time Resolution
 - Pointing Resolution
 - Rate Performance
- Sensor Characterisation
 - HV Tolerance
 - Charge Collection
 - Efficiency
 - Spatial Resolution
 - Edge
 - Grazing Angles
- Summary

HPK n-on-p, 200 μm thick