AT00000022

295

pt. 1

Cours/Lecture Series

1993 - 1994 ACADEMIC TRAINING PROGRAMME LECTURE SERIES FOR POSTGRADUATE STUDENTS

SPEAKER : E.J.N. WILSON / CERN-AC
TITLE : Introduction to particle accelerators
TIME : 28 February, 1, 2, 3, 4, 7, 8, 9, 10 & 11 March
from 11.00 to 12.00 hrs
PLACE : Auditorium

ABSTRACT

1. Mathematical introduction ; matrices
2. Mathematical introduction : differential equations
3. The circulating beam : phase stability and focusing
4. Lattice design principles
5. Liouville's theorem and closed orbit errors
6. Linear accelerators (by Guest Speaker : M. Weiss in person)
7. Magnets multipoles and resonances
8. RF bunches and buckets
9. Electron dynamics
10. Instabilities

CERN
BIBLIOTHEQUE
Acad. Train.
295
pt. 1

This is a wide-screen video retransmission of a previous popular series.

The course is intended for anyone with a technical or scientific background who would like to become familiar with the principles of accelerator design. It starts with two optional lectures which revise mathematical techniques. The level of the course is chosen with the intention of preparing students for specialist training at the CERN Accelerator School (Level 1) but is also of interest to a wider audience. The ten lectures on all aspects of circular machines cover in a simple way the principles of focusing, betatron motion, dispersion, chromaticity, radio-frequency systems, phase stability and beam instabilities.

1994/Div. DSU/CP-CC
Distr. int. & ext.

201696

ACADEMIC TRAINING LECTURE NOTES

AN INTRODUCTION TO PARTICLE ACCELERATORS

E.J.N.Wilson

1. Mathematical Introduction : Matrices
2. Mathematical Introduction : Differential Equations
3. The Circulating Beam : Phase Stability and Focussing
4. Lattices
5. Imperfections and Multipoles
6. Linear Accelerators (by guest speaker M.Weiss)
7. RF Bunches and Buckets
8. Electrons
9. Instabilities

This course is intended for anyone with a technical or scientific background who would like to become familiar with the principles of accelerator design. The level of the course is chosen with the intention of preparing students for the CERN Accelerator School but is also of interest to a wider audience. The nine lectures on all aspects of circular machines were given over the first three months of 1991 and complemented by discussion of set questions in tutorials. They cover in a simple way the principles of focussing, betatron motion, dispersion, chromaticity, radio-frequency systems, phase stability and beam instabilities. Special features of electron machines are treated in one lecture and another, given by guest speaker M. Weiss treats the principles of Linacs

CERN Geneva June 1991

INTRODUCTION TO PARTICLE ACCELERATORS

LECTURE 1. (MATHS INTRODUCTION)

"Matrices and Such"

SCALARS

E.g. : $\left. \begin{array}{c} 3 \\ -5 \\ 25.2 \\ a \\ x \end{array} \right\} \text{ Magnitude}$

Multiply: $x = m x \quad (\text{or} = x m)$

Reciprocal: $x = \frac{1}{m} x \quad (\text{or} = m^{-1} x)$

VECTORS - Two Numbers

Magnitude and Direction

Eg. (i) 5 km, East
(distance), (direction)

(ii) Line joining two points

$$x = r \cos \theta$$

$$y = r \sin \theta$$

(ii) Velocity (speed, direction)

$$\left(\frac{ds}{dt}, \hat{s} \right)$$

unit vector.

MULTPLYING

Scalar Rule - Doesn't work.

$$\neq \begin{cases} X = m x & Y = m y & \equiv \text{Enlarging} \\ R = m r & \Theta = m \theta & \equiv \text{Enlarge + Rotate} \end{cases}$$

Vector Rule

In general ~~two~~ ^{four} different multipliers
to give independent control $\delta_j(r, \theta)$
or (x, y)

$$r_{\text{new}} = \underline{\alpha} r_{\text{old}} + \underline{\beta} \theta_{\text{old}}$$

$$\theta_{\text{new}} = \underline{\gamma} r_{\text{old}} + \underline{\delta} \theta_{\text{old}}$$

Also in Cartesian.

$$x_{\text{new}} = ax_{\text{old}} + by_{\text{old}}$$

$$y_{\text{new}} = cx_{\text{old}} + dy_{\text{old}}$$

IN MATRIX FORM [just NOTATION]

$$\begin{pmatrix} x_n \\ y_n \end{pmatrix} = \begin{pmatrix} a & b \\ c & d \end{pmatrix} \begin{pmatrix} x_{\text{old}} \\ y_{\text{old}} \end{pmatrix} \leftarrow \text{VECTOR.}$$

PROVIDED WE OBEY MULTIPLYING RULE
[just a technique]

$$\begin{pmatrix} x \end{pmatrix} = \begin{pmatrix} a & + & b \end{pmatrix} \begin{pmatrix} x_{\text{old}} \\ y_{\text{old}} \end{pmatrix}$$

$$\begin{pmatrix} y \end{pmatrix} = \begin{pmatrix} c & + & d \end{pmatrix} \begin{pmatrix} x_{\text{old}} \\ y_{\text{old}} \end{pmatrix}$$

MATRIX OF A XEROX MACHINE

"Copy:"

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix} + \begin{pmatrix} * \\ * \end{pmatrix}$$

$$\begin{aligned} x_2 &= x_1 \\ y_2 &= y_1 \end{aligned}$$

} also called
"unit" matrix

"Enlarged Copy:"

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} 1.32 & 0 \\ 0 & 1.32 \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix} + \begin{pmatrix} * \\ * \end{pmatrix}$$

MIRROR MATRIX

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} -1 & 0 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix} + \begin{pmatrix} * \\ * \end{pmatrix}$$

SHEAR MATRIX

$$\begin{aligned} x_2 &= x_1 + b y_1 \\ y_2 &= y_1 \end{aligned}$$

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} 1 & b \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix} + \begin{pmatrix} * \\ * \end{pmatrix}$$

2.5

GENERAL RULE

$$(C) = (B)(A)$$

B "operates" on A to make C

$$C_{rc} = \sum_i b_{ri} a_{ic}$$

! NON COMMUTATIVE ! $BA \neq AB$

IF $D = CBA$

B operates first on A
C operates on (BA)

TRACE OF A MATRIX

$$\begin{pmatrix} a_{11} & & & & \\ & a_{22} & & & \\ & & a_{33} & & \\ & & & a_{44} & \\ & & & & a_{nn} \end{pmatrix}$$

Sum of diagonal elements

$$\text{Tr}(A) = \sum_i a_{ii}$$

- Useful check on stability of transport matrices $|\text{Tr}|/2 \leq 1$
- Phase advance $\cos \mu = \text{Tr}/2$

ROWS, COLUMNS, DIAGONAL

$$\begin{pmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{pmatrix} \begin{matrix} \leftarrow \text{2nd Row} \\ \uparrow \\ \text{3rd Column} \end{matrix}$$

a_{RC} is element

Diagonal Matrix

$$\begin{pmatrix} x \\ y \\ z \end{pmatrix} = \begin{pmatrix} a_{11} & 0 & 0 \\ 0 & a_{22} & 0 \\ 0 & 0 & a_{33} \end{pmatrix} \begin{pmatrix} x \\ y \\ z \end{pmatrix}$$

- Special property - does not mix x, y and z

$$- x = a_{11}x, y = a_{22}y, z = a_{33}z$$

x, y, z are "ORTHOGONAL"

DETERMINANTS

$$\det M = \underline{\text{number}}$$

For 2×2 it is easy:

$$a_{11}a_{22} - a_{21}a_{12}$$

If $\det M = 1$ and M is a transformation in x and y , area is conserved.

For 3×3 it is harder

Take det of this
and $\times a_{11}$

A_{11}
= cofactor
of a_{11}

+

det of these four
and $\times (-a_{12})$

all odd terms. (1+2 is odd)

+

det of these four
and $\times (+a_{13})$

i.e. cofactors are negative $\times$,
if $|n+m|$ is odd

ROTATION OF AXES

$P = (x, y) \rightarrow (X, Y)$
(transformation of coordinates)

$$X = x \cos \theta + y \sin \theta$$

$$Y = -x \sin \theta + y \cos \theta$$

Note suppose we rotate back
ie an angle θ , matrix is
then not

$$R = \begin{pmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{pmatrix}$$

but the reciprocal

$$R^{-1} = \begin{pmatrix} \cos(-\theta) & \sin(-\theta) \\ -\sin(-\theta) & \cos(-\theta) \end{pmatrix}$$

$$= \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$$

Note also:

$$\det R = \begin{pmatrix} - & - \end{pmatrix} \cos^2 \theta + \sin^2 \theta = 1$$

$$\begin{aligned} (R)(R^{-1}) &= \begin{pmatrix} \cos^2 \theta + \sin^2 \theta & -\cos \theta \sin \theta + \cos \theta \sin \theta \\ -\cos \theta \sin \theta + \sin \theta \cos \theta & \sin^2 \theta + \cos^2 \theta \end{pmatrix} \\ &= \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} = \text{UNIT MATRIX} \end{aligned}$$

COFACTORS of elements

$$\begin{pmatrix} a_{11} & \boxed{a_{12}} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{pmatrix} = M$$

- Look at element i, k . (say a_{12})
- Elements are "odd" if $i+k = \text{odd}$ (a_{12} is odd)
- Cofactor is formed by crossing out all elements ~~in~~ in same row + column

TAKE THEIR DETERMINANT AND
MULTIPLY BY (-1) if a_{ik} is ODD

Cofactor of a_{12} $(i+j)$

$$= A_{12} = (-1)(a_{21}a_{33} - a_{31}a_{23})$$

INVERSE or RECIPROCAL MATRIX

This is just the cofactors / $\det M$.

$$M^{-1} = \frac{1}{\det M} \begin{pmatrix} A_{11} & A_{21} & A_{31} \\ A_{12} & A_{22} & A_{32} \\ A_{13} & A_{23} & A_{33} \end{pmatrix}, \quad MM^{-1} = \overset{\uparrow}{1} \text{ unit matrix}$$

FOR 2×2

$$M^{-1} = \frac{1}{\det M} \begin{pmatrix} a_{22} & -a_{12} \\ -a_{21} & a_{11} \end{pmatrix}$$

COFACTORS OF ELEMENTS

$$\begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{pmatrix}$$

i

Cofactor of a_{12} is A_{12}

" " a_{ij} is A_{ij}

1. Cross out row i and col j
2. Take DETERMINANT of remainder
(called "minor of a_{ij} ")
3. Multiply by -1 if $i+j$ is odd
is $\times (-1)^{(i+j)}$

GIVING COFACTOR OF $a_{ij} = A_{ij}$

Example $A_{12} = (-1)(a_{21}a_{33} - a_{31}a_{23})$

INVERSE or RECIPROCAL MATRIX

$$MM^{-1} = 1 = \text{Unit Matrix}$$

(e.g. Rotate by an angle then back)

$$X = Mx \quad \text{then} \quad x = M^{-1}X$$

Uses : - Solves simultaneous equations.
- Reverses paths in a guide field.

$$M^{-1} = \frac{1}{\det M} \begin{pmatrix} A_{11} & A_{21} & A_{31} \\ A_{12} & A_{22} & A_{32} \\ A_{13} & A_{23} & A_{33} \end{pmatrix}$$

Note A 's are cofactors

They have been "Transposed"
i.e. rows $\rightleftharpoons$ columns.

FOR 2×2

$$M = \begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \quad M^{-1} = \frac{1}{\det M} \begin{pmatrix} a_{22} & -a_{12} \\ -a_{21} & a_{11} \end{pmatrix}$$

SOLVING SIMULTANEOUS EQUATIONS

Q_H and Q_V are related to I_F and I_D quadrupole currents jointly:

$$\Delta Q_H = a \Delta I_F + b \Delta I_D$$

$$\Delta Q_V = c \Delta I_F + d \Delta I_D$$

$$\begin{pmatrix} \Delta Q_H \\ \Delta Q_V \end{pmatrix} = \begin{pmatrix} a & b \\ c & d \end{pmatrix} \begin{pmatrix} \Delta I_F \\ \Delta I_D \end{pmatrix}$$

DO AN EXPERIMENT CHANGING I_F, I_D IN TURN

$$\text{Measure } \begin{pmatrix} \Delta Q_H \\ \Delta Q_V \end{pmatrix} = M \begin{pmatrix} \Delta I_F \\ \Delta I_D \end{pmatrix}$$

INVERT M TO BE ABLE TO FIND ΔI 's FOR A DESIRED ΔQ .

$$I = M^{-1} Q$$

$$\begin{pmatrix} \Delta I_F \\ \Delta I_D \end{pmatrix} = M^{-1} \begin{pmatrix} \Delta Q_F \\ \Delta Q_D \end{pmatrix}$$

HOW TO FIND MATRIX ELEMENTS

FROM EXPERIMENTS

IN displacement x
divergence angle x' } vector

↑
unknown optical system

$$\begin{pmatrix} x_{out} \\ x'_{out} \end{pmatrix} = \begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \begin{pmatrix} x_{in} \\ x'_{in} \end{pmatrix}$$

① Try $x_{in} = 1$, $x'_{in} = 0$ ("cosine case")

$$\begin{pmatrix} x_{out} \\ x'_{out} \end{pmatrix} = \begin{pmatrix} a_{11} \\ a_{21} \end{pmatrix} \quad \text{sometimes written } \begin{pmatrix} C \\ C' \end{pmatrix}$$

② Try $x_{in} = 0$, $x'_{in} = 1$ ("sine case")

$$\begin{pmatrix} x_{out} \\ x'_{out} \end{pmatrix} = \begin{pmatrix} a_{12} \\ a_{22} \end{pmatrix} \quad \text{sometimes written } \begin{pmatrix} S \\ S' \end{pmatrix}$$

Now we have $\begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} = \begin{pmatrix} C & S \\ C' & S' \end{pmatrix}$

COMPLEX NUMBERS

$$z = x + iy$$

Real part Imaginary Part.

z is just a vector

Simple Rules

$$i = \sqrt{-1}$$

$$i \times i = -1$$

$$(x + iy)(a + ib) = (ax - by) + i(ay + bx)$$

$$(x + iy)^2 = (x^2 - y^2) + i(2xy)$$

$$|z| = (x^2 + y^2)^{1/2} \text{ i.e. } [(Re)^2 + (Im)^2]^{1/2}.$$

$$\theta = \tan^{-1}\left(\frac{y}{x}\right) = \tan^{-1}\left(\frac{Im}{Re}\right)$$

TO BE COMPLETE

TRANPOSED (conjugate)

A (N rows, m columns) $\rightarrow A'$ (m rows, N columns)

a_{ji} a'_{ij}

INVERTED (Reciprocal)

A (square) $\rightarrow A^{-1}$ (square)

calc cofactors A_{jk} and det $\rightarrow a_{jk}^{-1} = \frac{A_{kj}}{|A|}$

ORTHOGONAL IF:

$$A' = A^{-1}$$

HERMITIAN CONJUGATE

A (complex, $a+ib$) $\rightarrow \tilde{A}$

first change $a+ib$ to $a-ib$ then TRANSPOSE

$$\text{IF } \tilde{A}_{pq} = A^{-1}_{pq}$$

Matrix is UNITARY OR HERMITIAN CONJUGATE

(Used in advanced dynamics + quantum th)

Question Sheet. Introduction to Particle Accelerators Lect 1

Q.1. Write down vectors (in cartesian coordinates)

for each of the points in Fig 1 above from the origin 0

Q.2. $x_{\text{new}} = a x_{\text{old}} + b y_{\text{old}}$

$$y_{\text{new}} = c x_{\text{old}} + d y_{\text{old}}$$

$$a = 1.2 \quad b = -0.5 \quad c = 2.32 \quad d = 1.8$$

a) - calculate (x, y) new for A B C D above.

b) - plot them.

Q 3.

Find the product of the matrices.

$$(a) A = \begin{pmatrix} 4 & 2 \\ 1 & 3 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \end{pmatrix} \quad (b) A = \begin{pmatrix} 1 & -4 \\ -2 & 3 \end{pmatrix} \begin{pmatrix} 7 \\ 8 \end{pmatrix}$$

$$(c) A = \begin{pmatrix} m & 0 \\ 0 & -m \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} \quad (d) A = \begin{pmatrix} 0 & m \\ -m & 0 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

$$(e) A = \begin{pmatrix} a & b \\ c & d \end{pmatrix} \begin{pmatrix} \alpha & \beta \\ \gamma & \delta \end{pmatrix}$$

$$(f) A = \begin{pmatrix} 1 & l_1 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & l_2 \\ 0 & 1 \end{pmatrix}$$

$$(g) A = \begin{pmatrix} 1 & l_2 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} 1 & l_1 \\ 0 & 1 \end{pmatrix}$$

Q 4. What is the determinant of the answer to (e) and (g)

Q5 What is the matrix for:

- (a) An enlargement by factor m .
- (b) A rotation by angle $\pi/4$
- (c) A reflection in the yOy axis

Q6

If the matrix equation relating the "Q" of a machine to quadrupole current is:

$$\begin{pmatrix} Q_H \\ Q_V \end{pmatrix} = \begin{pmatrix} 1.2 & 0.3 \\ 0.2 & 2.1 \end{pmatrix} \begin{pmatrix} I_F \\ I_D \end{pmatrix} = M \begin{pmatrix} I_F \\ I_D \end{pmatrix}$$

- a) What is the determinant $\det(M)$
- b) What are the cofactors of the four elements of M ?
- c) What is the reciprocal of M , i.e. M^{-1} ?
- d) What changes to I_F and I_D are needed to change Q_H by 0.1 unit.

$$A1. \quad A = \begin{pmatrix} 4 \\ 8 \end{pmatrix} \quad B = \begin{pmatrix} -3 \\ 3 \end{pmatrix} \quad C = \begin{pmatrix} 2 \\ -4 \end{pmatrix} \quad D = \begin{pmatrix} -6 \\ -5 \end{pmatrix}$$

$$A2(a) \quad \begin{pmatrix} 0.8 \\ 5.12 \end{pmatrix} \quad \begin{pmatrix} -5.1 \\ 12.36 \end{pmatrix} \quad \begin{pmatrix} 4.4 \\ -11.84 \end{pmatrix} \quad \begin{pmatrix} -4.7 \\ 4.92 \end{pmatrix}$$

$$A3.(a) \quad \begin{pmatrix} 14 \\ 6 \end{pmatrix} \quad (b) \quad \begin{pmatrix} -25 \\ 10 \end{pmatrix} \quad (c) \quad \begin{pmatrix} mx \\ -my \end{pmatrix} \quad (d) \quad \begin{pmatrix} my \\ -mx \end{pmatrix}$$

$$(e) \quad \begin{pmatrix} a\alpha + b\gamma & a\beta + b\delta \\ c\alpha + d\gamma & c\beta + d\delta \end{pmatrix} \quad (f) \quad \begin{pmatrix} 1 & l_1 + l_2 \\ 0 & 1 \end{pmatrix}$$

$$(g) \quad \begin{pmatrix} 1 - \frac{l_2}{f} & l_1 + l_2 - \frac{l_1 l_2}{f} \\ -\frac{1}{f} & 1 - \frac{l_1}{f} \end{pmatrix}$$

$$A4. \quad (a\alpha + b\gamma)(c\beta + d\delta) - (c\alpha + d\gamma)(a\beta + b\delta)$$

$$ac\alpha\beta + bc\gamma\beta + ad\alpha\delta + bd\gamma\delta$$

$$- ac\alpha\delta - ad\beta\gamma - bc\alpha\delta - bd\gamma\gamma$$

$$= ad(\alpha\delta - \beta\gamma) - bc(\alpha\delta - \beta\gamma) = \det \begin{vmatrix} a & b \\ c & d \end{vmatrix} \cdot \det \begin{vmatrix} \alpha & \beta \\ \gamma & \delta \end{vmatrix}$$

$$A5(a) \quad \begin{pmatrix} m & 0 \\ 0 & m \end{pmatrix} \quad (b) \quad \begin{pmatrix} \frac{1}{T_2} & \frac{1}{T_2} \\ -\frac{1}{T_2} & \frac{1}{T_2} \end{pmatrix} \quad (c) \quad \begin{pmatrix} -1 & 0 \\ 0 & 1 \end{pmatrix}$$

$$A6 \quad a) \quad \det M = 1.2 \times 2.1 - 0.2 \times 0.3 = 2.46$$

$$b) \quad \begin{array}{ccc} \text{cofactor} & 11 & 2.1 \\ & 12 & -0.2 \\ & 21 & -0.3 \\ & 22 & 1.2 \end{array}$$

$$c) \quad \frac{1}{2.46} \begin{pmatrix} 1.2 & -0.3 \\ -0.2 & 2.1 \end{pmatrix} \\ = \begin{pmatrix} 0.49 & -0.122 \\ -0.0813 & 0.853 \end{pmatrix}$$

$$d) \quad \begin{pmatrix} \Delta I_F \\ \Delta I_D \end{pmatrix} = \begin{pmatrix} 0.49 & , & -0.122 \\ -0.0813 & , & 0.853 \end{pmatrix} \begin{pmatrix} 0.1 \\ 0 \end{pmatrix}$$

$$\Delta I_F \quad \Delta I_E = 0.049$$

$$\Delta I_D = -0.00813$$

E. WILSON - LECTURE 2 - DIFFERENTIAL EQUATIONS

SIMPLE PENDULUM

l = length

m = mass.

Restoring force = $m \times$ acceleration

$$-mg \sin \theta = m \frac{d^2(l\theta)}{dt^2} = \cancel{m} l \frac{d^2\theta}{dt^2}$$

We usually rearrange it and write :

$$\frac{d^2\theta}{dt^2} + \left(\frac{g}{l}\right) \sin \theta = 0$$

Approximate for $\theta \ll \pi/2$

$$\sin \theta = \theta$$

$$\therefore \frac{d^2 \theta}{dt^2} + \left(\frac{g}{l}\right) \theta = 0$$

Note: to save ink we often write

$$\frac{d\theta}{dt} = \dot{\theta} \quad \frac{d^2 \theta}{dt^2} = \ddot{\theta}$$

So

$$\ddot{\theta} + \left(\frac{g}{l}\right) \theta = 0$$

is a shorthand way to write it

Note also:

Shorthand for

$$\frac{dy}{dx} = y' \quad \text{and} \quad \frac{d^2 y}{dx^2} = y''$$

Returning to the pendulum.

$$\frac{d^2\theta}{dt^2} + \left(\frac{g}{l}\right)\theta = 0 \quad (\text{DIFF. EQU})$$

IS A SECOND ORDER DIFFERENTIAL EQUATION whose coefficients are constant.

We expect (for a pendulum) that the solution will oscillate with $\sin 2\pi ft$ or $\cos 2\pi ft$ where f is the frequency.

Note :

we shall write

$$\omega = 2\pi f$$

in future.

Solving the equation is like integrating twice there will be two arbitrary constants which we choose to be A = amplitude and ϕ = starting angle of phase (not starting θ)

SOLUTION IS :

$$\theta = A \cos(\omega t + \phi) \quad \text{--- (GUESS)}$$

BUT WHAT IS ω

One way to solve the equation and find the value of ω is just to forget the arbitrary constants and substitute our GUESS in the DIFFERENTIAL equation.

$$\theta = A \cos(\omega t + \phi)$$

$$\frac{d\theta}{dt} = \dot{\theta} = -\omega A \sin(\omega t + \phi)$$

$$\frac{d^2\theta}{dt^2} = \ddot{\theta} = -\omega^2 A \cos(\omega t + \phi)$$

$$\therefore -\omega^2 A \cos(\omega t + \phi) + \left(\frac{g}{L}\right) A \cos(\omega t + \phi) = 0$$

$$\omega = \sqrt{\frac{g}{L}}$$

WE CAN NOW WRITE DOWN OUR SOLUTION

$$\theta = A \cos\left(\sqrt{\frac{g}{L}}t + \phi\right)$$

The same technique could be used to solve the displacement x of a weight on a spring

$$m \frac{d^2 x}{dt^2} + kx = 0$$

This is just Newton's second law.

k is the restoring force per unit displacement.

Solution can be found by substituting

$$x = x_0 \cos(\omega t + \phi)$$

↑
amplitude.

Why not try it. You will find

$$\omega = \sqrt{k/m}$$

Phase Diagrams

All problems like this will have solutions

$$x = x_0 \cos(\omega t + \phi_0)$$

Velocity $\dot{x} = \frac{dx}{dt} = -\omega x_0 \sin(\omega t + \phi)$

Plotting $\dot{x}$ against x (two quantities in quadrature makes a circle - or in this case an ellipse)

One revolution adds 2π to $(\omega t + \phi_0)$
 $\phi = (\omega t + \phi_0)$ is called "The phase angle"
and the diagram is a "phase diagram" or "phase plot".

IN GENERAL y axis is velocity, momentum or energy.

NUMERICAL (COMPUTER) SOLUTION

Suppose we only know the Differential equation:

$$m \frac{d^2 x}{dt^2} + kx = 0$$

(we could have taken a much harder example which can't be solved otherwise)

We can also write

$$m \left(\frac{d(v)}{dt} \right) + kx = 0$$

This tells us what the change in the "up" position in the phase plot is per second when the "left-right" coordinate is x .

Taking small intervals of Δt we can trace out the phase plot.

- A start with $x_0 = x_0$ $v_0 = 0$

- B after δt , $x_1 = x_0 + \int v dt = v \delta t = 0$

$$v_1 = \int \frac{dv}{dt} dt = \delta t \left(-\frac{kx_0}{m} \right)$$

- C δt later.

$$\begin{aligned} x_2 &= x_1 + v \delta t \\ &= x_1 - \frac{kx_1}{m} \delta t^2 \end{aligned}$$

$$v_2 = v_1 - \frac{kx_1}{m} \delta t$$

TRY IT FOR MANY STEPS AND YOU GET AN ELLIPSE

RIGID PENDULUM (Example of Numerical Method)

$$m \frac{d^2(l\theta)}{dt^2} + mg \sin \theta = 0$$

$$l \frac{d^2\theta}{dt^2} + g \sin \theta = 0$$

Hard because θ and $\sin \theta$ (not θ)

Put in the new form:

$$l \frac{d}{dt} \left(\frac{d\theta}{dt} \right) = -g \sin \theta$$

(Plot $d\theta/dt$ or $\dot{\theta}$ "up" and θ "left-right",

Different kind of motion - continuously rotates

FORCED OSCILLATIONS

$$m \frac{d^2 x}{dt^2} + kx = f(t)$$

$f(t)$ can mean exciting the motion of a weight on a spring by attracting it with a solenoid driven by an oscillator of frequency ω .

In general, the value of ω is not the frequency $\omega_0 = \sqrt{k/m}$ that we get if we solve the motion with $f(t) = 0$.

$$x = x_0 \cos \omega t$$

How much does the weight move and with what frequency?
- ω_0 or ω ?

STEP 1 Solve $m \frac{d^2 x}{dt^2} + kx = 0$

substitute $x = a \cos \omega t$

$$a \cos \omega t (m \omega^2 - k) = 0 \dots$$

CALLLED CHARACTERISTIC EQUATION

Given $\omega_0 = \pm \sqrt{k/m}$ as its roots.

SOPHISTICATED DEFINITIONS

$x = a \cos \omega t$ - our "guessed solution"

$m\omega^2 - k$ - "characteristic Equation"

$x = A \cos(\omega_0 t + \phi_0)$ - general solⁿ

or $A, \cos \omega_0 t + B, \sin \omega_0 t$ "COMPLEMENTARY FUNCTION"

STEP 2 (Take it on trust from Piaggio)

IF YOU CAN WRITE:

$$(m\omega_0^2 - k) a \cos \omega_0 t = 0 \quad (\text{we just did!})$$

YOU CAN ALSO WRITE (for ω not ω_0 !)

$$(m\omega^2 - k) a \cos \omega t = d \cos \omega t$$

we wrote this as
drawing $f(t)$ before

Solve to find a as a function of d
the driving amplitude
Resulting Response.

$$a = \frac{d}{m\omega^2 - k} = \frac{d}{k(\omega^2 - \omega_0^2)} \quad (\omega_0 = \sqrt{\frac{k}{m}})$$

FULL SOLUTION

STEADY STATE PARTICULAR INTEGRAL

$$x = \frac{d \cos \omega t}{m\omega^2 - k} +$$

$$A \cos \omega_0 t + B \sin \omega_0 t$$

COMPLEMENTARY

FOURIER SERIES

Any function that repeats every 2π in some phase angle can be written as a harmonic series

$$f(\theta) = a_0 + \sum_{n=1}^{\infty} (a_n \cos n\theta + b_n \sin n\theta)$$

$$a_0 = \text{average value} = \frac{1}{2\pi} \int_0^{2\pi} f(\theta) d\theta.$$

$$a_n = \frac{1}{\pi} \int_0^{2\pi} f(\theta) \cdot \cos n\theta d\theta.$$

$$b_n = \frac{1}{\pi} \int_0^{2\pi} f(\theta) \sin n\theta d\theta$$

PROOF IS TO WRITE $f(\theta)$ IN INTEGRAL AS A SERIES

$$a_n = \frac{1}{\pi} \int_0^{2\pi} \cos n\theta (a_1 \cancel{\cos \theta} + a_2 \cancel{\cos^2 \theta} + \dots a_n \cos n\theta + \dots)$$

$$\int_0^{2\pi} \cos n\theta \cos m\theta = 0 \text{ if } n \neq m$$

$$\int_0^{2\pi} d\theta \cos n\theta \cos n\theta = \int_0^{2\pi} \frac{1}{2} (\cos 2\theta + 1) d\theta = \pi$$

$$\therefore b_n = a_n \quad \checkmark$$

27

DIGRESSION ON COMPLEX NUMBERS

THREE WAYS OF WRITING THEM.

$$z = x + iy$$

$\nearrow$ real pt $\uparrow$ image part.

② "POLAR"

$$z = r(\cos \theta + i \sin \theta)$$

$\nearrow$ Re $\nearrow$ Im

③

"EXPONENT"

$$z = A e^{i\theta}$$

$e^{i\theta}$ is defined to mean $(\cos \theta + i \sin \theta)$

MULTIPLY BY $e^{i\theta}$
MEANS ROTATE
BY ANGLE θ .

$\theta = 0$	$e^{i\theta} = 1$	Real
$\theta = \pi/2$	$e^{i\theta} = i$	Imag
$\theta = \pi$	$e^{i\theta} = -1$	
$\theta = 3\pi/2$	$e^{i\theta} = -i$	

IF YOU ARE WORRIED ABOUT $e^{i\theta}$ STILL.

Remember: $\cosh x = (e^x + e^{-x})/2$

$$\sinh x = (e^x - e^{-x})/2$$

$$\cos x = (e^{ix} + e^{-ix})/2$$

$$\sin x = (e^{ix} - e^{-ix})/2i \quad \left. \vphantom{\sin x} \right\} \textcircled{A}$$

Substitute in $\cos x + i \sin x$ to obtain e^{ix}

You can even see what equations A mean graphically on an ARGAND ($x = \text{real}, y = \text{imag}$) plot.

NOW TRY TO CONSTRUCT

$\sin \theta$!

EXPONENT METHOD IS POWERFUL
TOOL!

Example:

What is $\sin 2\theta$, $\cos 2\theta$ expressed as function of $\sin \theta$, $\cos \theta$ etc.

$$e^{i2\theta} = e^{i\theta} \times e^{i\theta}$$

(just like ordinary $x^2 = x \times x$)

$$\begin{aligned} \cos 2\theta + i \sin 2\theta &= (\cos \theta + i \sin \theta)(\cos \theta + i \sin \theta) \\ &= \cos^2 \theta + 2i \sin \theta \cos \theta + \cancel{\sin^2 \theta} \end{aligned}$$

Collecting real terms to the left

$$= (\cos^2 \theta + \sin^2 \theta) + i(2 \sin \theta \cos \theta)$$

EQUATING REAL TERMS.

$$\cos 2\theta = \cos^2 \theta + \sin^2 \theta$$

EQUATING IMAGINARY TERMS.

$$\sin 2\theta = 2 \sin \theta \cos \theta$$

QUESTION 1

A pendulum has length l and a bob of mass m .

- Show a force diagram
- What is the restoring force?
- What is the equation of motion?
- What is the solution to the equ. of motion.
- Write down an expression for the frequency.

QUESTION 2

A ball rolls down a gutter of radius R . Its mass is m and its velocity (out of page) is v .

- Draw a force diagram to show the restoring force.
- What is the equation of motion + solution (time is the independent variable)
- What is the trajectory equation? (substitute to change t to s)
- What is the wavelength?
- If the length of the gutter is L ... ? ($L/2$)

Question 3

- a) Given the solution for the motion of the pendulum which starts at maximum swing ($t=0$) what is the expression for its velocity.
- b) What shape is the path traced out by its motion in a phase space diagram

Question 4

Repeat Question 3 for the case of a ball in a gutter.

[Hint. The coordinates are $(x, \frac{dx}{ds})$

where s is measured along the gutter.]

$\frac{dx}{ds}$ is also called x'
or divergence

Question 5

Fig 1. shows the trajectory of a particle in a "drift space"

- write an expression for θ
- plot a point in phase space (x, x') corresponding to the start and finish.
- what can we say about x_1' and x_2'
- how are x_1 and x_2 related to x_1' and l .
- Try to write down a matrix with 4 terms which Transforms (x_1, x_1') into (x_2, x_2')
(you may leave this until after the next set of questions)

Question 6

A point (x_1, y_1) rotates about O to (x_2, y_2)

a) write down equations for
 $x_2 = ? x_1 + ? y_1$

$$y_2 = ? x_1 + ? y_1$$

b) This is a linear Transformation and can be written in matrix form

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} \\ m_{21} & m_{22} \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix}$$

c) What is the matrix?

d) What is its determinant?

e) What is its inverse

Question 7.

- There is a change of angle at a convex lens. Write down θ as a function of x .
- Is θ dependent on where the ray comes from?
- Can you write down a matrix (2×2) which changes the divergence by θ but leaves x unchanged.
- Is this the matrix for a lens? and if so repeat for a diverging lens.

Question 8

What are the matrices for this system?
 What do they do in phase space?

QUESTION 9.

Any differential equation is simple to solve if you know the form of the answer.

$$\frac{d^2x}{dt^2} + kx = 0$$

a) ~~$\frac{d^2y}{ds^2} + ky = 0$~~

Substitute $x = ae^{\pm i\omega t}$ to find ω as a function of k .

b) ^{if} ω is not a frequency (the independent variable is s) how is it related to wavelength

QUESTION 10

- a) Demonstrate that

$$y = E^{1/2} \beta(s)^{1/2} \cos(\phi(s) + \lambda) = E^{1/2} w(s) \cos(\phi(s) + \lambda)$$

is a solution of:

$$\frac{d^2y}{ds^2} + k(s)y = 0$$

provided $\phi(s) = \int \frac{ds}{\beta(s)}$ and $w'' + kw - \frac{1}{w^3} = 0$.

b) What do you understand by $\beta(s)$.

Solⁿ 1.

$$m\ddot{x} = -T \sin \theta \quad \dots (1)$$

$$mg = T \cos \theta \quad \therefore T = \frac{mg}{\cos \theta}$$

Subs in (1)

$$m\ddot{x} = -mg \tan \theta$$

$$\text{if } \theta \ll \pi/2, \quad x = l \sin \theta \approx l\theta, \quad \ddot{x} = l\ddot{\theta}$$

$$m\ddot{x} = -mg\theta$$

$$\text{or } \ddot{\theta} = -\frac{g}{l}\theta$$

$$\ddot{\theta} + \left(\frac{g}{l}\right)\theta = 0$$

$$\text{or } \ddot{x} + \left(\frac{g}{l}\right)x = 0$$

$$x = a \cos(\omega t + \lambda)$$

$$\text{where } \omega = \sqrt{\frac{g}{l}}$$

$$\text{check. } \dot{x} = -a\omega \sin(\omega t + \lambda)$$

$$\ddot{x} = -a\omega^2 \cos(\omega t + \lambda)$$

$$= -\omega^2 x$$

$$\boxed{\frac{\dot{x}}{\omega} = -a \sin(\omega t + \lambda)}$$

Soln 2

As before $m\ddot{\alpha} = -F\sin\theta$
 $mg = F\cos\theta$

$$\ddot{\theta} + \left(\frac{g}{R}\right)\theta = 0$$

$x \approx R\theta.$

$$\ddot{x} + \left(\frac{g}{R}\right)x = 0$$

$$x = a \cos(\omega t + \lambda)$$

but $s = \text{distance along gutter} = vt$

$$\frac{d^2x}{dt^2} = \frac{dx}{ds} \cdot \frac{ds}{dt} = v \frac{dx}{ds}, \quad \frac{d^2x}{dt^2} = v^2 \frac{d^2x}{ds^2}$$

~~$$\frac{d^2x}{dt^2} = \frac{d}{dt} \left(\frac{dx}{ds} \frac{ds}{dt} \right) = \frac{d}{ds} \left(\frac{dx}{ds} \right) \frac{ds}{dt} = v \frac{d^2x}{ds^2}$$~~

$$x'' = \frac{d^2x}{ds^2} = -\left(\frac{g}{v^2}\right)x$$

$$\text{if } x = a \cos\left(2\pi \frac{x}{\lambda} + \mu\right)$$

$$x' = -a \cdot \frac{2\pi}{\lambda} \sin\left(2\pi \frac{x}{\lambda} + \mu\right)$$

$$x'' = -a \left(\frac{2\pi}{\lambda}\right)^2 \cos\left(2\pi \frac{x}{\lambda} + \mu\right)$$

$$= -\left(\frac{2\pi}{\lambda}\right)^2 x = -\left(\frac{g}{Rv^2}\right)x$$

~~$\therefore \text{Ans}$~~

$$\frac{2\pi}{\lambda} = \frac{1}{v} \sqrt{\frac{g}{R}}$$

$$\lambda = 2\pi v \sqrt{\frac{R}{g}}$$

$$\text{wave number} = \frac{1}{\lambda} = \frac{1}{2\pi} \cdot \frac{1}{(v^2 R/g)^{1/2}}$$

$$\text{Analogy for synchrotron: } Q = \frac{1}{2\pi} \int \frac{ds}{\beta}$$

$$\beta^{1/2} \equiv \frac{\lambda}{2\pi} \quad \text{locally.}$$

Soln 3

a) $x = a \cos \omega t$

$$\dot{x} = \frac{dx}{dt} = -a\omega \sin \omega t$$

Parametric Ellipse

$(a \cos \phi, b \sin \phi)$

$$b = m\dot{x} = m a \omega$$

Soln 4

$$x = a \cos 2\pi \left(\frac{x}{\lambda} \right)$$

$$\lambda = 2\pi v \sqrt{\frac{R}{g}}$$

$$\therefore x = a \cos \left(\frac{1}{v} \sqrt{\frac{g}{R}} \cdot x \right)$$

$$x'' = -\frac{1}{v} \sqrt{\frac{g}{R}} \sin \left(\right) = b \sin \left(\right)$$

2.24

Sol 1.1

Same as rotating coordinates - t .

a)

$$x_2 = \cos t x_1 + \sin t y_1$$

$$y_2 = -\sin t x_1 + \cos t y_1$$

c)

$$\begin{pmatrix} x_2 \\ y_2 \end{pmatrix} = \begin{pmatrix} \cos t & \sin t \\ -\sin t & \cos t \end{pmatrix} \begin{pmatrix} x_1 \\ y_1 \end{pmatrix}$$

Q5 2.25

Solⁿ 5

Maths Books

$$y = mx + c$$

$$\theta = \tan^{-1} m$$

$$m = \frac{dy}{dx} (= x')$$

Accelerators Books

$$x = ms + c$$

$$x = x_1' s + x_1$$

a) $\theta = \tan^{-1}(x_1')$

c) Note $x_2' = x_1'$

d) $x_2 = l x_1' + x_1$

$$x_2 = x_1 + l x_1'$$

$$x_2' = x_2' + 0 x_1'$$

e)

$$\begin{pmatrix} x_2 \\ x_2' \end{pmatrix} = \begin{pmatrix} 1 & l \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ x_1' \end{pmatrix}$$

$$\begin{aligned}
 a) \quad \det M &= m_{11}m_{22} - m_{21}m_{12} \\
 &= \cos^2\theta - (-\sin^2\theta) \\
 &= \cos^2\theta + \sin^2\theta = 1
 \end{aligned}$$

$$b) \quad \theta \rightarrow -\theta.$$

$$(M^{-1}) = \begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix}$$

$$\left[\begin{array}{l} \text{Formally} \\ (M^{-1}) = \frac{1}{|\det M|} \begin{pmatrix} a_{ij} & \dots \\ \vdots & \end{pmatrix} \end{array} \right]$$

a_{ij} is the ~~det~~ submatrix (or its determinant) if you cross out the i th row and j th column.

Solution 7

b) yes.

c)

$$x_2 = x_1 + 0 x_1'$$

$$x_2' = -\frac{x_1}{f} + x_1'$$

$$\begin{pmatrix} x_2 \\ x_2' \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ x_1' \end{pmatrix}$$

d) yes.

$$\begin{pmatrix} x_2 \\ x_2' \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ +\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ x_1' \end{pmatrix}$$

Soln. 8

(8)

$$\begin{pmatrix} 1 & 0 \\ -\frac{1}{f_1} & 1 \end{pmatrix} \begin{pmatrix} 1 & d_1 \\ 0 & 1 \end{pmatrix}$$

$$\begin{pmatrix} 1 & d_2 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & d_1 \\ -\frac{1}{f_1} & 1 - \frac{d_1}{f_1} \end{pmatrix}$$

$$\begin{pmatrix} 1 & 0 \\ \frac{1}{f_2} & 1 \end{pmatrix} \begin{pmatrix} 1 - \frac{d_2}{f_2} & d_1 + d_2 - \frac{d_1 d_2}{f_1} \\ \frac{1}{f_2} & 1 - \frac{d_1}{f_1} \end{pmatrix}$$

$$\begin{pmatrix} 1 & 0 \\ \frac{1}{f_2} - \frac{1}{f_1} - \frac{d_2}{f_1 f_2} & 1 + \frac{d_2}{f_2} + \frac{d_1}{f_2} - \frac{d_1}{f_1} - \frac{d_1 d_2}{f_1 f_2} \end{pmatrix}$$

1

2

Solution 9

$$\begin{aligned} \text{a)} \quad \dot{x} &= \pm j\omega a e^{\pm j\omega t} \\ \ddot{x} &= (\pm j\omega)^2 a e^{\pm j\omega t} \\ &= -\omega^2 a e^{\pm j\omega t} \\ &= -\omega^2 x \end{aligned}$$

$$\therefore \omega = \sqrt{k}$$

$$\text{b)} \quad x = a e^{\pm j\omega s}$$

since the solution is periodic
every time s increases by $\frac{2\pi}{\omega}$
the wavelength is $\frac{2\pi}{\omega}$.

INTRODUCTION TO ACCELERATORS LECTURE 3.
RELATIVITY (E.J.N. WILSON)

Energy of a particle at rest = $E_0 = mc^2$

Total Energy of a Moving Particle
 (definition of γ)

$$E = \gamma E_0 = mc^2 \gamma$$

Another relativistic variable is defined:

$$\beta = \frac{\text{momentum}}{\text{energy}} = \frac{pc}{E} = \frac{v}{c}$$

Solve these equations to get

$$p = \frac{E\beta}{c} = mc(\beta\gamma)$$

$\rightarrow$ used in rf
phase plots.

Fig. 2. The Alvarez linear accelerator (from *Cyclic Particle Accelerators* by J. J. Livingood).

Since the particle gains energy at each gap, the lengths of successive tubes must be tailored to its increasing velocity. Eventually, as the particle approaches the velocity of light, its velocity no longer increases significantly with energy, and the drift tubes and their spacing become regular:

$$\beta = \frac{v}{c} = \sqrt{1 - \left(\frac{E_0}{E}\right)^2}$$

where

E_0 is the rest mass of the particle
 E is its total energy

PHASE STABILITY

① is the synchronous particle - gets the right amount of energy:

$$V = V_0 \sin \phi_s = \frac{\text{energy}}{\text{turn}}$$

to follow the rising B.

③ is late - in meantime r.f. wave has grown so it gets more volts than A - speeds up - and catches it

Fig. 22 Cylindrical coordinate system rotates with beam, demonstrates meaning of RF phase angle in longitudinal phase space

$$NB f = \frac{\beta c}{2\pi R}$$

In fact B, overtakes A, overshoots and oscillates about A.

In phase space ($\Delta\beta\gamma, \phi$) it follows an ellipse and makes phase oscillations with frequency:

f_s which defines a number of oscillations / machine turn:

$$Q_s [\text{or } Q_s] = f_s / f_0$$

Usually $\ll 1 \approx 0.05$

BUCKET AREA AND PENDULUM
 ANALOGY.

MAGNETIC RIGIDITY

Force = (Centripetal) acceleration

$$F = e\vec{v} \times \vec{B} = \frac{mv^2}{\rho}$$

$$(B\rho) = \text{magnetic rigidity} = \frac{mv}{e} = \frac{p}{e}$$

where: p = momentum

Fortunately as $v \rightarrow c$ this is also true

With all the conversion factors

$$(B\rho) = 3.3356 \times p$$

[Tesla.m]

[GeV/c]

for the tutorial

Add up all the bending magnets in the ring

$$B \times \text{Number} \times \text{length} = 2\pi\rho B = 2\pi \times 3.3356 \times p$$

Effect of a uniform bending (dipole) field
of length l

$$\sin \frac{\theta}{2} = \frac{l}{2\rho} = \frac{1}{2} \frac{lB}{(B\rho)}$$

if $\theta \ll \pi/2$

$$\theta = \frac{lB}{(B\rho)}$$

48
3.6

TRANSVERSE MOTION IN PHASE SPACE (x, x')

Imagine a circular gutter around which the marble wobbles. Measure and plot the displacement x and divergence angle x' ($\propto$ velocity in x direction). If phase is different on each turn measurements will lie on an ellipse. (Just a description of SHM)

ϵ is a property of the beam. **EMITTANCE**

β is a property of the focussing system and will vary around the ring for AG focusing changing aspect ratio of ellipse and tilting it depending on where you sit.

EFFECT OF A QUADRUPOLE FOCUSSING MAGNET

④ Here field is in opposite direction so it'll bend to centre.

① There is no field on the axis

② The field is strong near

③ In fact in the median plane

Fig. 2.2

∴ focussing is linear

F_x is towards $x=0$

and focussing
if F_y is away
on axis

F in H plane
D in V plane.

Characterised by
FIELD GRADIENT

$$\frac{\partial B_y}{\partial x}$$

FOCUSING STRENGTH

$$k = \frac{1}{(B\rho)} \frac{\partial B_y}{\partial x} = \frac{1}{f}$$

ALTERNATING
GRADIENT
FOCUSSING
IS USED

Components of field and force in a magnetic quadrupole. Positive ions approach the reader on paths parallel to the s axis (from *Cyclic Particle Accelerators* by J. J. Livingood). (This is such a nice drawing I did not want to change all the y 's to z)

8

8

4

2.9

AG . FOCUSING

(a) Optical analogy - lenses which are concave in one plane and convex in the other. - the defocusing lenses have zero effect since rays pass down their centre.

EQUATION OF MOTION OF PARTICLES IN TRANSVERSE FOCUSING SYSTEM

(2.5) HILL'S EQUATION

Quadrupole strength

$$\frac{d^2 y}{ds^2} + k(s)y = 0$$

- This is a linear equation with periodic coefficient:

$k(s)$ which is the focussing strength distributed around the ring
(this is like the restoring constant in simple harmonic motion)

- The solution is not unlike SHM but the amplitude, which we call $\sqrt{\epsilon\beta}$ and the phase ϕ are functions of s . Thus:

$$y = \sqrt{\epsilon} \cdot \sqrt{\beta(s)} \cos[\phi(s) + \lambda]$$

Look carefully - each term has a physical significance

$\sqrt{\epsilon}$ is the BEAM'S emittance

$\sqrt{\beta(s)}$ is a periodic function which describes the machine LATTICE

$\sqrt{\epsilon\beta(s)}$ is the beam envelope (for $\frac{d\phi}{ds} = 0$)

$\cos[\phi(s) + \lambda]$ is the oscillation of the particle within the envelope (is a constant) 15

- ALSO $\phi(s) = \int \frac{ds}{\beta(s)}$, $\dot{y} = \sqrt{\epsilon\beta(s)}$, $\dot{y}' = \sqrt{\epsilon/\beta(s)}$
 $2\pi Q = \oint \phi(s) ds \cdot Q \approx 2\pi Q$

→ AARHUS 1989

(2.7) This is a 64 m long PERIOD of the CERN Super Proton Synchrotron (about 1% of the ring)

The functions β (vertical) and β (horizontal) describe the focussing properties of the machine. and define the beam size.

They define the ENVELOPE of Trajectories which oscillate within them in a distorted form of simple harmonic motion which advances in phase as ϕ_h and ϕ_v

$$B \times N_B \times l_B = 2\pi(pB) = 2\pi \times 3.3356 \text{ p[GeV/c]}$$

$$N_{\text{periods}} \times \left[\frac{l_D}{2} + 0.4 + l_B + \dots + \frac{l_D}{2} \right] = 2\pi R.$$

TUTORIAL QUESTIONS FOR LECTURE #3

1. Find an expression for beta (v/c) as a function of Momentum (eV/c) and plot it for momenta in the range 1 GeV/c to 100 GeV/c for protons. (on log paper). What is the value for 8.0 GeV electrons?

Answer : $\beta = (1 + (E_0/pc)^2)^{-0.5}$

2. Measure the radius of the ISR tunnel on the CERN phone book map.

Answer : 150 m.

3. If 43 % of an electron synchrotron ring consists of bending magnets and it matches the ISR tunnel - what is the radius of curvature in these magnets?

Answer : 64.5

4. Assuming the maximum field is 0.5 Tesla what would be $B \cdot \rho$ and from it calculate the maximum energy?

Answer ; 26.68 T.m. ; 8 GeV kinetic

5. Suppose the quadrupoles have a bore diameter of 70 mm. and the field at this radius is 0.42 Tesla. What is the maximum field gradient?

Answer 12 T/m

6. Suppose there are 144 quadrupoles - and the focal length is about equal to 2/3 of their spacing. What is the length of each one?

Answer ; 0.51 m.

7. Allowing 0.5 m at one end of the Bending magnet and 1.5 m at the other - what will be the length of the bending magnet? (Hint there are two bending magnets and two quads per FODO period)

Answer : 4.035 m.

8. How many bending magnets are needed and how many full and empty half periods are there.

Answer 84 half periods will have bends and 60 will be empty.

	A	B	C	D
1	IMPROVED	ISR BEAUTY FACT	ORY FOR TUTORIAL OF	2.Feb.91
2				
3			Esub 0	r sub 0
4			0.000511	0.000000
5				
6			Outlined data is input	
7				
8			Formulae	Data
9		Kinetic energy(GeV)	8	8
10		Energy[GeV]	=C9+\$C\$4	8.000000
11		gamma	=C10/\$C\$4	15655.57
12		beta	=SQRT(1-1/C11^2)	0.999999
13		Momentum[GeV/c]	=C10*C12	8
14		B*rho(T.m)	=3.3356*C13	26.6848
15		Ring radius(m)	150	150
16		Fraction bend	0.43	0.43
17		Curvature (m)	=C15*C16	64.5
18		Circumference (m)	=2*3.14159*C15	942.477
19		Dipole field (T)	0.5	0.5
20		pc Max (GeV)	=C14/3.3356	8
21		Etot (max- GeV)	=C20/C12	8.000000
22		Quad bore diam.(m)	0.07	0.07
23		Pole tip field(T)	0.42	0.42
24		Quad gradient	=C23/(0.5*C22)	12
25		Normalised grad (k)	=C24/C14	0.449694
26		Number of quads	144	144
27		Spacing (m)	=C18/C26	6.544979
28		Focal length (m)	=2*C27/3	4.363319
29		Quad length (m)	=1/C28/C25	0.509642
30		Short straight (m)	0.5	0.5
31		Longer straight (m)	1.5	1.5
32		Bending length	=C27-C29-C30-C31	4.035336
33		Number dipoles	=2*3.14159365*(C14/C19)/C32	83.09869
34		Number half periods	=C26	144
35		Filled/empty	=C33/C34	0.577074
36				
37				
38		Cos mu	=1-(C27^2/(2*C28^2))	-0.125
39		Mu(rad)	=ACOS(C38)	1.696124
40	Ans 6b	Mu(deg)	=360*C39/2/3.142	97.16815
41		m12	=2*C27*(1+C27/(2*C28))	22.90742
42	Ans 6c	Beta max	=C41/(SIN(C39))	23.08851
43		m12	=2*C27*(1-C27/(2*C28))	3.272489
44	Ans 6d	Beta max	=C43/SIN(C39)	3.298359
45				