CM-P00064124

AR/Int. SR/63-4

12th March, 1963

THERMAL VELOCITY EFFECTS IN AXIALLY SYMMETRIC SOLID BEAMS

by

P. T. Kirstein

Abstract

The effect of a Maxwellian distribution of emission velocities, on the longitudinal current density variation in axially symmetric solid beams, is investigated to the paraxial approximation. The effects of both longitudinal and transverse initial emission velocities are included. The treatment permits variable magnetic fields, and also apertures which intercept some of the beam. Some particles may be turned back because all their energy is forced into the transverse motion. The reduction of the transmitted current density due to this effect is evaluated. A simple illustrative example is given.

INTRODUCTION

Several authors have estimated the effects of thermal velocities in electron beams. In some cases the treatment has been very general^{1,2)}, but has only treated some special cases in detail. Other references have considered electrostatic^{3,4,5)} or electromagnetic^{6,7,8)} paraxial beams without allowing for the effects of longitudinal velocity spread. In this paper the work of Refs 3-7 will be extended by including the effects of longitudinal velocity spread, non-uniform cathode emission, and non-uniform magnetic fields, in one treatment. In practical cases, the transverse dimension of the beam is limited, therefore the treatment allows the beam to be restricted by one or more round apertures. The approach of this paper relies heavily on Refs 5 and 7. The introductions of these two references could well also serve as introduction to this paper.

In all the references on paraxial beams quoted, it is assumed that the electromagnetic fields in the finite temperature beam are the same, to first order, as those in the zero temperature case. If this is not so, higher order corrections are required. The higher order corrections are discussed in Refs 4 and 5 for electrostatic beams, and can be applied in much the same way for the beams of this paper. A more thorough and general treatment of higher order corrections is given in Ref. 9.

In a paraxial theory it is assumed that the forces due to space-charge vary linearly with distance from the axis. This assumption is equivalent to one that the effect of transverse variation in charge density on the electric field are neglected. Since the space-charge term is itself usually a first-order term, variation in it may be considered second order. Thus it is not inconsistent to consider thermal effects in beams with non-uniform cathode emission to the paraxial approximation.

The paraxial theory relates the transverse position and velocity, and hence transverse energy, of a particle at one plane z in terms of their initial values at the cathode; for solid axially symmetric beams, this reaction does not, to first order, depend on the initial longitudinal velocity. Moreover the total kinetic energy of a particle at z is related to its energy at the cathode by the conservation of energy. From the difference of these two relations, a negative longitudinal energy may be required by a particle to reach a given plane with given transverse energy. This is physically impossible, and means the particle would have been turned back and cannot reach the plane z of interest. An aperture in the system would also intercept particles, and so will impose additional restrictions on the range of permissible transverse velocities of particles which reach the plane z at a specified distance from the axis.

In section 2, the transverse position, velocity, and total energy of a particle at a plane z is related to its values at the cathode in general terms. An axially symmetric current density distribution is assumed at the cathode, having a half-Maxwellian velocity distribution. Based on Liouville's theorem, the longitudinal current density at z is related to that at the cathode by an integral over all permissible velocities. The range of permissible velocities is discussed. In section 3, the results of section 2 are used to find the longitudinal current density on the axis for uniform cathode current density; while in section 4 the methods of section 3 are applied to points off the axis. In section 5, the extension to non-uniform cathode emission, and to sheet and hollow beams with curvilinear ray axes, is discussed. Finally, in section 6, a simple illustrative example is given. In this example, a beam comes from an electrostatic cylindrical Pierce gun, passes through a defining aperture, and then drifts in a uniform magnetic field. For algebraic simplicity the uniform field is such that its cyclotron frequency is equal to the plasma frequency of the beam.

2. THE GENERAL FORMALISM

In this section general expressions are derived for the axial current density in solid axially symmetric paraxial beams assuming a Maxwellian distribution of emission, and the regions over which the appropriate integrals must be evaluated are discussed.

The Transformation Laws for a Single Particle. Let $(x, y, \dot{x}, \dot{y}, \dot{z})$ represent the transverse position and the velocity components of an electron at a plane z , and $(X, Y, \dot{X}, \dot{Y}, \dot{Z})$ the corresponding parameters of the same electron at a plane $z = 0$. We assume the beam is a solid, paraxial, axially symmetric beam. This means:

- (1) The transverse position and transverse velocity components of that part of the beam which has significant charge density is small.
- (2) The spread of longitudinal velocity, at a plane z , of particles in that part of the beam which has significant charge density is small.
- (3) Over the transverse dimensions in which there is a significant charge density, the electric and magnetic fields vary linearly with distance from the axis and are axially symmetric.

Under the above assumptions, it is shown in Appendix A, Eqs (A.13), (A.16), (A.17), and (A.22) that one may define complex variables w, u, W, U related to the position and velocity components of a particle by

$$w = (x + i y) e^{-i\chi}, \quad W = X + i Y, \quad (2.1)$$

$$u = (\dot{x} + i \dot{y}) e^{-i\chi} - i\omega_L w, \quad U = (\dot{X} + i \dot{Y}) - i\Omega_L W \quad (2.2)$$

$$\left. \begin{aligned} \Phi_0(z) &= 2\eta\phi_0(z), \quad \omega_L = \frac{1}{2} \eta B_0(z), \\ \Omega_L &= \frac{1}{2} \eta B_0(0), \quad \chi = \int_0^z \omega_L(z) \Phi_0(z)^{-1/2} dz \end{aligned} \right\} \quad (2.3)$$

where η is the ratio of charge to mass, $B_0(z)$ is the axial magnetic field on the axis at the plane z , and $\phi_0(z)$ is the electrostatic potential on the axis relative to the cathode. In Eqs. (2.1) - (2.3), the lower case letters refer to the values at the initial plane $z = 0$.

From Eqs. (A.24) and (A.28), the parameters $w, u, \dot{z}$ of an electron at the plane z are related to their value W, U, Z at the initial plane by the laws

$$\begin{pmatrix} w \\ u \end{pmatrix} = \begin{pmatrix} M & S \\ \dot{M} & \dot{S} \end{pmatrix} \begin{pmatrix} W \\ U \end{pmatrix} \quad (2.4)$$

$$\left| u + i \omega_L(z) w \right|^2 + \dot{z}^2 - \frac{\Phi_0}{2}(z) + \frac{\Phi_2}{2}(z) \left| w \right|^2 = Z^2 + \left| U + i \Omega_L W \right|^2 \quad (2.5)$$

Here $M, S, \dot{M}, \dot{S}$ are real functions of z satisfying Eqs. (A.20) and (A.27), so that, from Eq. (A.30),

$$M \dot{S} - \dot{M} S = 1 \quad (2.6)$$

while $\frac{\Phi_2}{2}$ is given, from Eq. (A.25), by

$$\frac{\Phi_2}{2}(z) = \frac{\eta}{2} \left[\rho_0(z) + \phi''(z) \right] \quad (2.7)$$

At a cathode ρ_0 and $\phi''(z)$ both become infinite. However, the right-hand-side of Eq. (2.7) is proportional to the derivative with respect to r of the radial electric field. Now if the cathode is chosen as an equipotential at $z = 0$, this term will be zero, so that $\frac{\Phi_0}{2}(0)$ and $\frac{\Phi_2}{2}(0)$ are both zero. From now on we will only consider the transformation laws² of Eqs. (2.4) - (2.6). The relation between the functions $M, \dot{M}, S, \dot{S}, \omega_L, \Omega_L, \frac{\Phi_0}{2}, \frac{\Phi_2}{2}$ and the electromagnetic fields will not be considered. However, we might note that if no magnetic field threads the cathode, $\Omega_L = 0$, while if there is no magnetic field at the plane z , $\omega_L = 0$.

The Phase Space Density Distribution at the Cathode

The probability that a particle at a particular point (X, Y) of the cathode $z = 0$, will leave the cathode with velocity components in the ranges $(\dot{X}, \dot{X} + d\dot{X})$, $(\dot{Y}, \dot{Y} + d\dot{Y})$, $(\dot{Z}, \dot{Z} + d\dot{Z})$ is $P(\dot{X}, \dot{Y}, \dot{Z}) d\dot{X} d\dot{Y} d\dot{Z}$ where P has the form

$$P(\dot{X}, \dot{Y}, \dot{Z}) = 2\lambda^3 \pi^{-3/2} \exp\left[-\lambda^2(\dot{X}^2 + \dot{Y}^2 + \dot{Z}^2)\right] \quad (2.8)$$

and λ is given by

$$\lambda = \sqrt{m / (2 k T)} \quad (2.9)$$

where m is the mass of the electron, T the cathode temperature, and k is Boltzman's constant.

If the beam is axially symmetric, the total number of particles emitted from an area $dX dY$ of cathode about the point X, Y may be expressed in the form $N_T(R) dX dY$ where R is the distance of (X, Y) from the axis. The function N_T is related to the axial current density at the cathode. In terms of N_T , the number density distribution of particles in $(X, Y, \dot{X}, \dot{Y}, \dot{Z})$ phase space is N where

$$N(X, Y, \dot{X}, \dot{Y}, \dot{Z}) = 2\lambda^3 \pi^{-3/2} N_T(R) \exp\left[-\lambda^2(\dot{X}^2 + \dot{Y}^2 + \dot{Z}^2)\right] \quad (2.10)$$

If the cathode current density is $i_c(R)$, then N_T is related to i_c by the expression

$$i_c(R) = e \int_0^\infty \dot{Z} d\dot{Z} \int_{-\infty}^\infty \int_{-\infty}^\infty N(X, Y, \dot{X}, \dot{Y}, \dot{Z}) d\dot{X} d\dot{Y} \quad (2.11)$$

Substituting Eq. (2.11) into Eq. (2.10) we see that

$$i_c(R) = e N_t(R) \pi^{-1/2}/\lambda \quad (2.12)$$

Hence N becomes

$$N(X, Y, \dot{X}, \dot{Y}, \dot{Z}) = 2\lambda^4/(\pi e) i_c(R) \exp\left[-\lambda^2(\dot{X}^2 + \dot{Y}^2 + \dot{Z}^2)\right]. \quad (2.13)$$

Now our transformation laws are written not in $(x, y, z, \dot{x}, \dot{y}, \dot{z})$ space but in $(w, z, u, \dot{z})$ space. In this space the density is NJ where J is the Jacobian of the transformation from the $(x, y, \dot{x}, \dot{y})$ system to the (w, u) system. This Jacobian is unity, because the transformation of $x + iy$ to w is a simple rotation, while that from $(\dot{x} + i\dot{y})$ to u is a simple rotation plus an added term independent of u . In order to determine the number density distribution of electrons omitted from the cathode $|U|^2$ must be related to $\dot{X}^2$ and $\dot{Y}^2$. From Eq. (2.2) we see that

$$\dot{X}^2 + \dot{Y}^2 = |U + i\Omega_L W|^2 \quad (2.14)$$

Using Eq. (2.13) we now see that the number density of particles omitted from W with transverse velocity U and normal velocity Z is $N(W, U, Z)$ where

$$N(W, U, Z) = 2\lambda^4/(\pi e) i_c(R) \exp\left[-\lambda^2(|U + i\Omega_L W|^2 + \dot{Z}^2)\right] \quad (2.15)$$

Equation (2.15) will be required in later sections to derive expressions for the current density at planes other than the cathode.

The Axial Current Density Distribution

We are now in a position to find the axial current density distribution. From Liouville's Theorem, the phase space density n is preserved for an ensemble of particles in an electromagnetic field. Hence if a particle at

(x, y, z) , with velocity components $(\dot{x}, \dot{y}, \dot{z})$, comes from the point (X, Y) at the cathode with initial velocity components $(\dot{X}, \dot{Y}, \dot{Z})$, the number density in phase-space $n(x, y, z, \dot{x}, \dot{y}, \dot{z})$ is equal to $n(X, Y, 0, \dot{X}, \dot{Y}, \dot{Z})$. In accordance with our notation, the phase-space density at the cathode will be denoted by $N(X, Y, \dot{X}, \dot{Y}, \dot{Z})$. Using the conservation of phase-space density and Eq. (2.13), the axial current density is $i(x, y, z)$ where i is given by

$$\begin{aligned} i(x, y, z) &= \int_{\dot{x}} \int_{\dot{y}} \int_{\dot{z}} e n(x, y, z, \dot{x}, \dot{y}, \dot{z}) \dot{z} d\dot{x} d\dot{y} d\dot{z} \\ &= \int_{\dot{x}} \int_{\dot{y}} \int_{\dot{z}} e N(X, Y, \dot{X}, \dot{Y}, \dot{Z}) \dot{z} d\dot{x} d\dot{y} d\dot{z} \\ &= \frac{2\lambda^4}{\lambda} \int_{\dot{x}} \int_{\dot{y}} \int_{\dot{z}} \dot{z} i_c(R) \exp\left[-\lambda^2(\dot{X}^2 + \dot{Y}^2 + \dot{Z}^2)\right] d\dot{x} d\dot{y} d\dot{z} \quad (2.16) \end{aligned}$$

The regions of $(\dot{x}, \dot{y}, \dot{z})$ space over which Eq. (2.16) must be integrated is defined by several boundaries. If the cathode is finite, or if there are apertures in the systems, then this will impose bounds on (x, y) at some plane z_0 , possibly the cathode. From Eqs. (2.1) - (2.4), these bounds will impose conditions on u, v and hence $\dot{x}, \dot{y}$; these conditions will not, however, effect the permissible $\dot{z}$. For a particle to arrive at (x, y, z) , it must have, at all z between the cathode and the plane of interest, positive axial velocity $\dot{z}$. From the energy balance equation, Eq. (2.5), this implies a condition on $\dot{z}$ of the form

$$\dot{z} \geq \dot{z}_{\min}(x, y, \dot{x}, \dot{y}). \quad (2.17)$$

The exact expressions for $\dot{z}_{\min}$ will be discussed later.

If a constraint of the type of Eq. (2.17) is applied, Eq. (2.16) may be integrated, using the energy balance equation Eq. (2.5)

$$\begin{aligned}
 i(x,y,z) &= \frac{2\lambda^4}{\lambda} \iint_{\dot{x}, \dot{y}} i_c(R) \int_{\dot{z}=\dot{z}_{\min}}^{\infty} \dot{z} \exp \left[-\lambda^2 (\dot{x}^2 + \dot{y}^2 + \dot{z}^2 - \Phi_0 + \Phi_2 r^2) \right] d\dot{x} d\dot{y} d\dot{z} \\
 &= \frac{\lambda^2}{\lambda} \iint_{\dot{x}, \dot{y}} i_c(R) \exp \left[-\lambda^2 (\dot{x}^2 + \dot{y}^2 + \dot{z}_{\min}^2 - \Phi_0 + \Phi_2 r^2) \right] d\dot{x} d\dot{y} \quad (2.18)
 \end{aligned}$$

In substituting for $\dot{z}$ in Eq. (2.16) we have used the connection between $\dot{x}$, $\dot{y}$ and u , w , and replaced $|w|^2$ by r^2 the distance from the axis. The evaluation of Eq. (2.18), the choice of $\dot{z}_{\min}$ and the bounds of integration form the subject of this paper.

In general it is best to put everything in terms of the independent variables (x, y) of the point of interest in the z plane, (X, Y) the point on the cathode from which the particles came, and Z the initial axial velocity. The integration over $\dot{x}$, $\dot{y}$, $\dot{z}$ must then be replaced by one over X , Y , Z using the Jacobian of the transformation developed in Appendix B. From Eqs. (2.4) and (2.6) we see that

$$u = (\dot{S} w - W) / S, \quad U = (w - M W) / S \quad (2.19)$$

Using Eqs. (2.1), (2.2) and (2.19), the relation between $\dot{x}$, $\dot{y}$, x , y , X , Y can be written

$$\begin{aligned}
 \dot{x} + i\dot{y} &= e^{i\chi} (u + i\omega_L w) \\
 &= e^{i\chi} \left[(\dot{S} + i\omega_L) w - W \right] / S \\
 &= e^{i\chi} \left[(\dot{S} + i\omega_L) w - (X + iY) \right] / S \quad (2.20)
 \end{aligned}$$

The transformation from $(\dot{x}, \dot{y}, \dot{z})$ to $(X, Y, \dot{Z})$ is seen from Eqs. (2.5) and (2.20) to have the form of Eq. (B.1) with

$$q_1 = \dot{x}, q_2 = \dot{y}, q_3 = \dot{z}, Q_1 = X, Q_2 = Y, Q_3 = \dot{Z}, C = e^{i\chi}/S \quad (2.21)$$

Hence the volume elements in the $(\dot{x}, \dot{y}, \dot{z})$ and $(X, Y, \dot{Z})$ systems are related, from Eq. (B.6), by the expression

$$d\dot{x} d\dot{y} d\dot{z} = \dot{Z}/(S^2 \dot{Z}) dX dY d\dot{Z} \quad (2.22)$$

An alternative expression for $i(x, y, z)$ is therefore, from Eq. (2.16)

$$\begin{aligned} i(x, y, z) &= \frac{2\lambda^4}{\Lambda S^2} \iint_{X, Y} i_c(R) \exp\left[-\lambda^2(\dot{X}^2 + \dot{Y}^2)\right] dX dY \int_{\dot{Z}} e^{-\lambda^2 \dot{Z}^2} \dot{Z} d\dot{Z} \\ &= \frac{2\lambda^4}{\Lambda S^2} \iint_{X, Y} i_c(R) \exp\left[-(\lambda/S)^2 |w - (M - i\Omega_L S)w|^2\right] dX dY \int_{\dot{Z}} \dot{Z} e^{-\lambda^2 \dot{Z}^2} d\dot{Z} \end{aligned} \quad (2.23)$$

In Eq. (2.23) we have used Eqs. (2.2) and (2.19); (W, w) are related to (X, Y, x, y) by Eq. (2.1) :

The condition that $\dot{Z}, \dot{z} > 0$ may be written, instead of as Eq. (2.17), in the form

$$\dot{Z} \geq \dot{Z}_{\min}(x, y, \dot{x}, \dot{y}) \quad (2.24)$$

where $\dot{z}_{\min}$ and $\dot{Z}_{\min}$ are related, from Eq. (2.5), by

$$\dot{z}_{\min}^2 = \text{Max} \left[0, -\dot{X}^2 - \dot{Y}^2 + \dot{x}^2 + \dot{y}^2 + \dot{z}_{\min}^2 - \Phi_0(z) + \Phi_2(z) r^2 \right] \quad (2.25)$$

Using this bound on $\dot{Z}_{\min}$, Eq. (2.23) becomes

$$i(x,y,z) = \frac{\lambda^2}{S^2} \int \int_{X,Y} i_c(R) \exp - \lambda^2 \left[\left| w - (M - i\Omega_L S)W \right|^2 + \dot{Z}_{\min}^2 \right] dX dY \quad (2.26)$$

Again the region of integration of X, Y and the form of $\dot{Z}_{\min}$ will be discussed later.

The transformation leading to Eq. (2.26) is only possible as long as $S \neq 0$. If $S = 0$, we are at a cathode image plane, and the integral becomes degenerate. We may use the fact that one definition of the Dirac delta function $\delta(a)$ is

$$\delta(a) = \lim_{S \rightarrow 0} \left[e^{-(a/S)^2} / (\sqrt{\pi} S) \right] \quad (2.27)$$

Hence the limiting form of Eq. (2.23) is

$$i(x, y, z) = (1/M^2) i_c(r/M) e^{-\lambda^2 \dot{Z}_{\min}^2} \quad (2.28)$$

In Eq. (2.28) we have used the fact that $\left| w - (M - i\Omega_L S)W \right|$ can be zero, as $S \rightarrow 0$, only if $WM = w$, so that $R = r/M$.

The Region of Integration

Physically there are several restraints on the range of the variables $(\dot{x}, \dot{y}, \dot{z})$ of Eq. (2.18) or (X, Y, Z) of Eq. (2.23). The restraints we will consider may be put in three categories:

- (i) Due to the finite nature of the cathode
- (ii) Due to an axially symmetric aperture in the system
- (iii) Those imposed by energy considerations.

The restraint of type (i) may be included in the choice of $i_c(R)$, the current density distribution at the cathode. However, it is often convenient to choose for $i_c(R)$ as simple a function as possible. When the cathode current density is constant, the integrals of Eqs. (2.18) and (2.26) may be evaluated explicitly in terms of known functions. For this reason it may be preferable to allow for a cathode of radius a by putting the restraint

$$R < a \quad (2.29)$$

This restraint will not be discussed further, for the moment, since it is a special case of type (ii). If $x_0, y_0, r_0, \dot{x}_0, u_0$ etc. refer to the values of $x, y, r, \dot{x}, u$ etc. of a particle at z_0 , and there exists a circular aperture radius a_0 at z_0 , then this restraint may be written, from Eq. (2.1),

$$r_0 = |w_0| \leq a_0 \quad (2.30)$$

It is clear that Eq. (2.29) is a special case of Eq. (2.30). If the transformation from the plane z_0 to z is as Eq. (2.4) namely with M_0, S_0, w_0 etc. replacing M, S, W etc.

$$\begin{pmatrix} w \\ u \end{pmatrix} = \begin{pmatrix} M_0 & S_0 \\ \dot{M}_0 & \dot{S}_0 \end{pmatrix} \begin{pmatrix} w_0 \\ u_0 \end{pmatrix} \quad (2.31)$$

Eq. (2.30) may be expressed in the form

$$|\dot{M}_0 w - \dot{S}_0 u| \leq a_0 \quad (2.32)$$

Clearly if we are using (W, U) coordinates, and Eq. (2.31) denotes the matrix of transformation from (w_0, u_0) to (W, U) then Eq. (2.32) will again hold with (W, U) replacing (w, u) . Depending on the variation of $M, \dot{M}, S, \dot{S}$

with z , there will be a limitation of the form of Eq. (2.32) at each axial plane z . We will usually assume, however, that the limitation at one particular plane z_0 is the most stringent.

The third type of restraint requires that

$$\dot{z} \geq 0, \quad \dot{z}_0 \geq 0 \quad (2.33)$$

where $\dot{z}_0$ is the value of $\dot{z}$ at the plane z_0 . Using Eq. (2.5) with ω_{L0} , Φ_{00} , Φ_{20} etc. denoting the values of ω_L , Φ_0 , Φ_2 at z_0 etc. we see that energy balance requires that at each plane z_0

$$\left| u + i\omega_L w \right|^2 + \dot{z}^2 - \Phi_0 + \Phi_2 \left| w \right|^2 = \left| u_0 + i\omega_{L0} w_0 \right|^2 + \dot{z}_0^2 - \Phi_{00} + \Phi_{20} \left| w_0 \right|^2 \quad (2.34)$$

For the particle to arrive at all at z , it is necessary that for all z_0 in the interval $0 \leq z_0 \leq z$, $\dot{z}_0 \geq 0$ so that Eq. (2.34) gives

$$\dot{z}^2 \geq \dot{z}_{\min,0}^2 \equiv \left| u_0 + i\omega_{L0} w_0 \right|^2 - \left| u + i\omega_L w \right|^2 - \Phi_{00} + \Phi_0 + \Phi_{20} \left| w_0 \right|^2 - \Phi_2 \left| w \right|^2 \quad (2.35)$$

For each z_0 there will exist a $\dot{z}_{\min,0}$ which depends on u , w as given by Eq. (2.35). For each w , u it is possible to define a $\dot{z}_{\min}$ by

$$\dot{z}_{\min} = \text{Max} \left(\dot{z}_{\min,0} \right) \quad (2.36)$$

The $\dot{z}_{\min}$ of Eq. (2.36) is the one which should be used in Eqs. (2.18) or (2.26). However, we will usually assume that if a particle left the cathode with positive axial velocity and reaches the plane z with positive axial velocity, then it has positive $\dot{z}_0$ at all intermediate planes z_0 .

This condition is equivalent to putting

$$\dot{z}_{\min}^2 = \text{Max} \left[0, \left| U + i \omega_L W \right|^2 - \left| u + i\omega_L w \right|^2 + \Phi_0 - \Phi_2 \left| w \right|^2 \right] \quad (2.37)$$

Both Eqs. (2.35) and (2.37) can be put in terms of only (w, u) by using the relations between (w, u) and (w_0, u_0) or (W, U) of Eqs. (2.31) or (2.4).

It may be noted that the convenient bounds of integration are not on $(\dot{x}, \dot{y})$ or (X, Y) but on u or W . We may change coordinates from an integral over $(\dot{x}, \dot{y})$ to one over the u plane by using Eqs. (2.2), (B.1) and (B.6) with $q = (\dot{x} + i \dot{y})$, $Q = u$, $C = e^{i\chi}$, $D = ie^{i\chi} \omega_L W$, $E = 0$, $q_3 = Q_3$, so that

$$d\dot{x} d\dot{y} = du_x du_y \quad (2.38)$$

and an integral over the u plane is identical to one over the $(\dot{x}, \dot{y})$ plane. Also an integral over the (X, Y) plane is identical to one over the W plane. Hence using Eqs. (2.2) and (2.38), Eq. (2.18) may be written

$$i(x, y, z) = \frac{\lambda^2}{\Lambda} \iint_u i_c(R) \exp \left\{ -\lambda^2 \left[u + i\omega_L W \right]^2 + z_{\min}^2 - \Phi_0 + \Phi_2 \right\} du_x du_y \quad (2.39)$$

It is unnecessary to rewrite Eq. (2.26), since a restriction on W is automatically one on (X, Y) .

It now remains only to integrate Eqs. (2.26) and (2.39) under the restrictions of the form of Eqs. (2.32) and (2.35) or (2.37).

3. THE CURRENT DENSITY ON THE AXIS FOR UNIFORM CATHODE CURRENT DENSITY

If the current density at the cathode is uniform, it is possible to evaluate the integrals of Section 2 explicitly under certain assumptions. In this section we will restrict ourselves to evaluating the current density on the axis; the algebra is much simpler for this case, and yet the essential ideas are well illustrated. In this case we may put $w = 0$, $i = i(0, 0, z)$ in the equation of Section 2, and take i_c outside the integral sign of Eq. (2.39), to obtain

$$i(0,0,z) = i_c \frac{\lambda^2}{\Lambda} \iint_u \exp \left[-\lambda^2 \left(|u|^2 + \dot{z}_{\min}^2 - \Phi_0 \right) \right] du_x du_y \quad (3.1)$$

If we further assume that the field is such that if a particle leaves the cathode and reaches z with positive axial velocity, it will never have zero axial velocity between these two planes, then Eq. (2.37) will be satisfied and will give

$$\dot{z}_{\min}^2 = \text{Max} \left\{ 0, (M^2 + \Omega_L^2 S^2 - 1) |u|^2 + \Phi_0 \right\} \quad (3.2)$$

Equation (3.2) is derived from Eq. (2.37) by using Eq. (3.1) and putting $w = 0$.

If in addition there is an aperture a_0 at a plane z_0 with matrix of transformation as given by Eq. (2.31), then on the axis the possible range of u is given, from Eq. (2.32) by

$$|S_0 u| \leq a_0 \quad (3.3)$$

Equation (3.1) must therefore be integrated over the u specified by Eq. (3.3) with the $\dot{z}_{\min}$ of Eq. (3.2). Writing

$$u = |u| e^{i\gamma} \quad (3.4)$$

Eq. (3.1) may be immediately integrated over γ to give

$$i(0,0,z) = i_c \lambda^2 \int_{|u|} 2|u| \exp \left[-\lambda^2 \left(|u|^2 + \dot{z}_{\min}^2 - \Phi_0 \right) \right] d|u| \quad (3.5)$$

There are now several cases, as $(M^2 + \Omega_L^2 S^2 - 1) \leq 0$ and $a_o / |\dot{S}_o| \leq \bar{\Phi}_o / (M^2 + \Omega_L^2 S^2 - 1)$; the first condition determines whether the beam is highly convergent for the given magnetic field, the second the relation between the aperture size, the energy and the convergence.

Clearly one important parameter is $M^2 + \Omega_L^2 S^2$; writing for brevity

$$\alpha^2 = M^2 + \Omega_L^2 S^2 \quad (3.6)$$

we may deduce from Eq. (3.2) that

$$\left. \begin{aligned} \text{If } \alpha > 1, \text{ or if } \alpha < 1 \text{ and } |u|^2 < \bar{\Phi}_o / (1 - \alpha^2), \quad \dot{z}_{\min}^2 = \bar{\Phi}_o + (\alpha^2 - 1) |u|^2 \\ \text{If } \alpha < 1 \text{ and } |u|^2 > \bar{\Phi}_o / (1 - \alpha^2), \quad \dot{z}_{\min}^2 = 0 \end{aligned} \right\} (3.7)$$

Combining Eqs. (3.7) and (3.3), Eq. (3.5) can be integrated to give

If $\alpha > 1$, or if $\alpha < 1$ and $a_o^2 / \dot{S}_o^2 < \bar{\Phi}_o / (1 - \alpha^2)$

$$i(0,0,z)/i_c = \left[1 - \exp \left(- \lambda^2 a_o^2 \alpha^2 / \dot{S}_o^2 \right) \right] / \alpha^2 \quad (3.8)$$

If $\alpha < 1$ and $a_o^2 / \dot{S}_o^2 > \bar{\Phi}_o / (1 - \alpha^2)$

$$i(0,0,z)/i_c = \left\{ 1 - (1 - \alpha^2) \exp \left[- \lambda^2 \bar{\Phi}_o \alpha^2 / (1 - \alpha^2) \right] \right\} / \alpha^2 - \exp \left[- \lambda^2 \left(a_o^2 / \dot{S}_o^2 - \bar{\Phi}_o \right) \right] \quad (3.9)$$

In deriving Eqs. (3.8) and (3.9) we have assumed $\bar{\Phi}_o$ positive, which is the case of most practical interest.

Under the conditions of Eq. (3.8), it is seen that energy considerations do not affect the axial current. It is not possible to obtain infinite axial current density by compressing the beam - i.e. letting $\alpha \rightarrow 0$.

Under such conditions Eqs. (3.8) and (3.9) give

$$\text{if } a_o^2/S_o^2 < \Phi_o, \quad \alpha \rightarrow 0, \quad i(0,0,z)/i_c \rightarrow \lambda^2 a_o^2/S_o^2 \quad (3.10)$$

$$\text{if } a_o^2/S_o^2 > \Phi_o, \quad \alpha \rightarrow 0, \quad i(0,0,z)/i_c \rightarrow 1 + \lambda^2 \Phi_o - \exp \left[-\lambda^2 (a_o^2/S_o^2 - \Phi_o) \right] \quad (3.11)$$

The expression of Eq. (3.11), with $a_o \rightarrow \infty$, is that derived by Pierce²⁾ from more elementary considerations for the maximum current density at a point.

It is easy to derive an expression for maximum beam which can arrive within a cone of half-angle β , neglecting energy restrictions. For this it is only necessary to repeat the integration for $\dot{z}_{\min} = |u| \tan \beta$. This expression has also been derived by Pierce, but is probably of less importance than the results of Eqs. (3.10) and (3.11) which give the maximum current density at an anode plane if there is an aperture a_o placed at an arbitrary position between the cathode and anode planes.

It is possible to derive many physical properties of Eqs. (3.8) - (3.11), but we will only stress that the principal parameter governing the current density is not M , the paraxial magnification of the beam, but $(M^2 + \Omega_L^2 S)$, i.e. α . Thus unless the beam is very stiff, i.e. unit transverse velocity will produce little deviation from the axis so that S is small, and there is little magnetic field threading cathode so that Ω_L is small, it may not help much to reduce the magnification.

If there are several apertures a_i at z_i with transfer matrix element M_i , S_i etc. then a_o/S_o in Eqs. (3.8) - (3.11) must be defined by

$$a_o/S_o = \text{Min} (a_i/S_i). \quad (3.12)$$

Clearly a finite cathode of radius a is considered by considering an aperture of radius a at the cathode plane $z = 0$.

4. CURRENT DENSITY OFF THE AXIS FOR UNIFORM CATHODE CURRENT DENSITY

The results of the previous section will now be extended to give the longitudinal current density off the axis in the presence of an aperture and the energy restrictions of Section 3. Again a uniform current density at the cathode will be assumed.

The energy balance condition, Eq. (2.37) can be written, using Eq. (2.4),

$$\begin{aligned} \dot{z}_{\min}^2 &= \text{Max} \left\{ 0, \left| (-\dot{M} + i\Omega_L \dot{S})w + (\dot{M} - i\Omega_L \dot{S})u \right|^2 - \left| u + i\omega_L w \right|^2 + \dot{\Phi}_0 - \dot{\Phi}_2 |w|^2 \right\} \\ &= \text{Max} \left\{ 0, \alpha^2 |u - \beta_1 w|^2 - \left| u + i\omega_L w \right|^2 + \dot{\Phi}_0 - \dot{\Phi}_2 |w|^2 \right\} \end{aligned} \quad (4.1)$$

where α is given by Eq. (3.6) and

$$\beta_1 = (\dot{M} - i\Omega_L \dot{S}) / (\dot{M} - i\Omega_L \dot{S}) \quad (4.2)$$

If we have an aperture a_0 at a plane z_0 as in Eq. (2.30), the possible range of u is given by Eq. (2.32) namely

$$\left| u - (\dot{M}/\dot{S}_0) w \right| \leq a_0/\dot{S}_0 \quad (4.3)$$

Now over one range of u Eq. (2.39) must be integrated with $\dot{z}_{\min} = 0$; over another $\dot{z}_{\min}$ is given by the second term of Eq. (4.1). In order to perform the integration, it is necessary to determine the boundary curve where $\dot{z}_{\min}$ changes from one value to the other. This occurs where

$$\alpha^2 |u - \beta_1 w|^2 - \left| u + i\omega_L w \right|^2 + \dot{\Phi}_0 - \dot{\Phi}_2 |w|^2 = 0$$

which may be written

$$\left| u - C_1 w \right| = b_1 \quad (4.4)$$

where

$$\left. \begin{aligned} c_1 &= \frac{(\alpha^2 \beta_1 + i\omega_L)}{\alpha^2 - 1}, \\ b_1^2 &= \frac{\bar{\Phi}_0}{1 - \alpha^2} + |w|^2 \left[\frac{|\alpha^2 \beta_1 + i\omega_L|^2}{(1 - \alpha^2)^2} + \frac{\alpha^2 |\beta_1^2| - \omega_L^2 - \bar{\Phi}_2}{1 - \alpha^2} \right] \end{aligned} \right\} \quad (4.5)$$

It is to be noted that if $w = 0$ as in section 3, Eq. (4.4) gives the circle $|u|^2 = \bar{\Phi}_0 / (1 - \alpha^2)$ as the dividing curve. If b_1^2 , as defined by Eq. (4.5), is negative, then $\dot{z}_{\min} = 0$ for all u , if $\alpha < 1$, and $\dot{z}_{\min}$ is the second term of Eq. (4.1) for all u if $\alpha > 1$. The region over which Eq. (2.39) must be integrated is bounded by Eq. (4.3) which may be written

$$|u - c_2 w| \leq b_2, \quad c_2 = \dot{M}_0 / \dot{S}_0, \quad b_2 = a_0 / \dot{S}_0 \quad (4.6)$$

Substituting the appropriate $z_{\min}$ and boundaries, one may obtain different values of $i(x, y, z)$ depending on the relative values of b_1 , b_2 . For example if the aperture is large and the beam sufficiently near the axis so that

$$b_1^2 > 0, \quad b_2 > b_1 + |c_1 - c_2|, \quad \alpha < 1 \quad (4.7)$$

Then Eq. (2.39) gives

$$\begin{aligned} \frac{i(x, y, z)}{i_c} &= \frac{\lambda^2}{\pi} \iint_{|u - c_1 w| \leq b_1} \exp \left(-\lambda^2 \alpha^2 |u - \beta_1 w|^2 \right) du_x du_y + \\ &+ \frac{\lambda^2}{\pi} \exp \left[-\lambda^2 \left(-\bar{\Phi}_0 + \bar{\Phi}_2 |w|^2 \right) \right] \iint_{\substack{|u - c_2 w| \leq b_2 \\ |u - c_1 w| \leq b_1}} \exp \left[-\left(\lambda^2 |u + i\omega_L w|^2 \right) \right] du_x du_y \end{aligned} \quad (4.8)$$

Now the integrals of Eq. (4.8) are of the type of Eq. (C.3) with a scale change, and are to be integrated over the region of Eq. (C.10). Hence using the results of Eqs. (C.9) - (C.13),

$$\frac{i(x,y,z)}{i_c} = \frac{1}{\alpha^2} \left[1 - I(\Delta_1, \lambda \alpha b_1) \right] + \exp \left[-\lambda^2 (-\Phi_0 + |w|^2 \Phi_2) \right] \left[I(\Delta_2, \lambda b_1) - I(\Delta_3, \lambda b_2) \right] \quad (4.9)$$

where

$$\Delta_1 = |c_1 - \beta_1| \alpha \lambda |w|, \quad \Delta_2 = |c_1 + i\Omega_L| \lambda |w|, \quad \Delta_3 = |c_2 + i\Omega_L| \lambda |w| \quad (4.10)$$

And $I(\Delta, b)$ is the function defined in Eq. (C.3) and shown in Figs. 2 and 3.

If the energy is so high that

$$b_1^2 > 0, \quad b_1 > b_2 + |c_1 - c_2|, \quad \alpha < 1 \quad \text{or} \quad b_1^2 < 0, \quad \alpha > 1 \quad (4.11)$$

then it is easily seen that $\dot{z}_{\min}$ is always given by the second term of Eq. (4.1) and

$$\frac{i(x,y,z)}{i_c} = \frac{1}{\alpha^2} \left[1 - I(\Delta_3 \alpha, \lambda b_2 \alpha) \right] \quad (4.12)$$

By using Eq. (C.8) it is easy to see that on the axis, where $|w| = 0$ and therefore $\Delta_1 = \Delta_2 = \Delta_3 = 0$, the i/i_c of Eqs. (4.9) and (4.12) reduce to those of Eqs. (3.8) and (3.9). It should be noted that the current density only takes the comparatively simple forms of Eqs. (4.9) and (4.12) when Eqs. (4.7) or (4.11) are satisfied. This implies the circles $|u - c_1 w| = b_1$ and $|u - c_2 w| = b_2$ do not intersect.

In Refs 3-5 expressions have been given for the current density variation neglecting the effect of longitudinal velocities. The results obtained may be shown to be the limiting case of this section when $\bar{\Phi}_0$ becomes large, so that Eq. (4.11) is satisfied. The current density is then exactly that of Eq. (4.12). In Refs. 3-5 there was no magnetic field, so that the comparison must be made with $\omega_L = \Omega_L = 0$. In these references there was a finite cathode and no aperture, hence S_0 , a_0 , z_0 refer to the cathode plane.

If the relative magnitudes of $|w|$, $\bar{\Phi}_0$, and u_0 are such that neither Eq. (4.7) nor Eq. (4.11) is satisfied, it is still possible to evaluate the integrals concerned, but the results are rather more complicated. This situation would arise if for a particular point in the beam the curve defining the dividing line between $\dot{z}_{\min} = 0$ and $Z_{\min} = 0$, i.e. Eq. (4.4), passes outside the permissible range of u , i.e. Eq. (4.6). In that case it is no longer possible to take the second integral of Eq. (C.6) from Eq. (C.7), hence the extra complication.

5. NON-UNIFORM CATHODE CURRENT DENSITY AND OTHER EXTENSIONS OF THE METHOD

If the current density is still axially symmetric, but not uniform, it is no longer possible to take i_0 outside the integral sign in Eq. (2.39) - unless we are at a cathode image plane so that $S = 0$. If this is not the case, it is more convenient to use W , w as independent coordinates, and integrate Eq. (2.26). In this case Eq. (2.25) can be written

$$\dot{z}_{\min}^2 = \text{Max} \left[0, -|w + (i\Omega_L S - M)w|^2 + |(S + i\omega_L S)w - W|^2 - \bar{\Phi}_0 + \bar{\Phi}_{12}|w|^2 \right] \quad (5.11)$$

and if M_0 , S_0 etc. is the matrix from the cathode to the aperture a_0 at z_0 , the aperture can be expressed by

$$|M_0 W - S_0 U| < a_0$$

which can be written

$$\left| (M_0 S - S_0 M) W - S_0 w \right| < a_0 S \quad (5.2)$$

It is now possible to carry out exactly the same procedure as in the preceding section. Again the curve separating the two values of $Z_{\min}$ can be written in the form

$$\left| W - C_3 w \right| = b_3$$

while the boundary over which W may range is given by Eq. (5.2) and is therefore of the same form. Equation (2.26) may now be evaluated in exactly the same way as Eq. (2.39) of the last section. The only difference which now occurs is that instead of the simple $I(\Delta, b)$ functions of the last section one is now required to integrate

$$\frac{1}{\Lambda} \iint i_c(|W|) \exp - \alpha^2 |W - Dw|^2 dW_x dW_y$$

An example of this technique when the "aperture" was the finite size of the cathode has been given in Ref. 5. In this case $M_0 = 1$, $S_0 = 1$ and Eq. (5.2) is simply the obvious $|W| < a_0$. We will not, however, go through the algebra required for non-uniform cathode emission.

It is to be noted that the methods of this paper can equally well be applied to axially symmetric beams with curvilinear ray axes. In these cases the differential equations for the matrix elements must be slightly varied from Eq. (A.20), and the transformation law of Eq. (A.29) must be replaced by that of Eq. (A.31) where $\epsilon = Z$. For sheet beams the $\epsilon W/R$ term need only be replaced by ϵW . These changes of transformation do somewhat complicate the algebra, and no example will be given in this paper.

6. A SIMPLE EXAMPLE

As an illustration of the method, let us consider thermal effects in a pencil beam which starts as a parallel flow beam from an infinite planar cathode. After length z_0 it has reached a potential ϕ_{00} , and then passes through an aperture a . This aperture is also a magnetic shield, and immediately after the aperture the beam comes into an axial magnetic field B such that the cyclotron frequency is just equal to the plasma frequency of the beam, and in which there is no electric field. Assuming the cathode has temperature T and the beam is emitted with uniform current density at the cathode, we will investigate the longitudinal current density variation across the beam at anode plane distant z_1 from the aperture. The physical situation is sketched in Fig. 1.

Clearly the first important problem is to evaluate the matrix elements M , $\bar{M}$, S , $\bar{S}$ and M_0 , $\bar{M}_0$, S_0 , $\bar{S}_0$ of the transformations from the cathode to the anode and from the aperture to the anode. For this purpose we divide the cathode anode region into 3 parts; the first is from the cathode to the aperture, the second passing through the aperture, the third is the drift region beyond. In all three regions w must satisfy Eq. (A.20) so that

$$\frac{dw}{dz} = \phi_0^{-1/2} u, \quad \frac{du}{dz} = -(\phi_2 + \omega_L^2) \phi_0^{-1/2} w \quad (6.1)$$

However, if $\tilde{A}_i$ is the transfer matrix,

$$\tilde{A}_i = \begin{pmatrix} M_i & S_i \\ \bar{M}_i & \bar{S}_i \end{pmatrix} \quad (6.2)$$

for the i^{th} region, it is easily seen from the definitions of the elements that the transfer matrix from after the aperture to z , is $\tilde{A}_3$, while that from the cathode to z , is $\tilde{A}_3 \tilde{A}_2 \tilde{A}_1$.

In the first region, because the beam is electrostatic and obeys the Child-Langmuir Equations from a space-charge limited cathode,

$$0 \leq z \leq z_0, \quad \Omega_L = \omega_L = 0, \quad \phi_0 = \phi_{00} (z/z_0)^{4/3}, \quad \rho_0 = -\epsilon_0 (4/9) (\phi_{00}/z_0^2) (z/z_0)^{-2/3} \quad (6.3)$$

so that

$$0 \leq z \leq z_0, \quad \omega_L = 0, \quad \bar{\phi}_{00} = 2\eta\phi_{00}, \quad \bar{\phi}_0 = \bar{\phi}_{00} (z/z_0)^{4/3}, \quad \bar{\phi}_2 = 0 \quad (6.4)$$

There is a sharp discontinuity in ϕ'_0 in crossing the aperture. On one side it is $4/3(z/z_0)^{1/3} (\phi_{00}/z_0)$ on the other zero. Therefore in region 2 we may say that the change in $\bar{\phi}'_0$, $\Delta\bar{\phi}'_0$, is given by

$$\Delta\bar{\phi}'_0 = - (4/3) (\bar{\phi}_{00}/z_0) \quad (6.5)$$

In the drift region there is no electric field or change in ρ_0 so that, using Eq. (A.4),

$$z_0 \leq z \leq z_0 + z_1, \quad \bar{\phi}_0 = \bar{\phi}_{00}, \quad \bar{\phi}_2 = - (1/9) (\bar{\phi}_{00}/z_0^2) \quad (6.6)$$

Now in this region the applied magnetic field is just sufficient to counteract the space-charge spreading force. Hence, using Eq. (A.18)

$$z_0 \leq z \leq z_1 + z_0, \quad \omega_L^2 = -\bar{\phi}_2 = (1/9) (\bar{\phi}_{00}/z_0^2) \equiv \omega_{L0}^2 \quad (6.7)$$

Using the $\bar{\phi}_2$ and ω_L of Eq. (6.4) in Eq. (6.1) it is seen that

$$0 \leq z \leq z_0, \quad \frac{dw}{dz} = (u/z_0)(z_0/z)^{2/3}/(3\omega_{L0}), \quad \frac{du}{dz} = 0 \quad (6.8)$$

which may be integrated to give

$$0 \leq z \leq z_0, \quad \begin{pmatrix} w_1 \\ u_1 \end{pmatrix} = \begin{pmatrix} 1 & (z/z_0)^{1/3}/\omega_{L0} \\ 0 & 1 \end{pmatrix} \begin{pmatrix} W \\ U \end{pmatrix} \quad (6.9)$$

where W, U are the values of (w, u) at $z = 0$.

As one crosses region 2, the plane of the aperture, Eq. (6.1) can be integrated, using Eqs. (6.5), (6.7) and (A.4) to give a change in w, u of $\Delta w, \Delta u$ in crossing the aperture of

$$\Delta w = 0, \quad \Delta u = -\frac{1}{4} w \phi_{00}^{-1/2} \Delta \phi, \quad (6.10)$$

Hence if w_1, u_1 are the values of (w, u) before the aperture, and w_2, u_2 the values after then the transformation across the aperture is given by

$$\begin{pmatrix} w_2 \\ u_2 \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ \omega_{L0} & 0 \end{pmatrix} \begin{pmatrix} w_1 \\ u_1 \end{pmatrix} \quad (6.11)$$

Finally, in the third region Eqs. (6.6) and (6.7) are satisfied so that

$$z_0 \leq z \leq z_1 + z_0, \quad \frac{dw}{dz} = (u/z_0) / (3\omega_{L0}), \quad \frac{du}{dz} = 0 \quad (6.12)$$

which may be integrated to give

$$z_0 \leq z \leq z_0 + z_1 \quad \begin{pmatrix} w_3 \\ u_3 \end{pmatrix} = \begin{pmatrix} 1 & (z-z_0)/(3z_0\omega_{L0}) \\ 0 & 1 \end{pmatrix} \begin{pmatrix} w_2 \\ u_2 \end{pmatrix}$$

where w_2, u_2 are the values of w, u at the plane z_0 .

We are now in a position to find the transfer matrices from the aperture to the plane (z_0+z_1) and from the cathode to the plane (z_0+z_1) . From the definition of these matrices, Eqs. (2.31) and (A.28), and from Eqs. (6.9), (6.11) and (6.13) it is seen that

$$\begin{pmatrix} M_o & S_o \\ \cdot & \cdot \\ M_o & S_o \end{pmatrix} = \begin{pmatrix} 1 & (z_1/z_o)/(3\omega_{L0}) \\ 0 & 1 \end{pmatrix} \quad (6.14)$$

and

$$\begin{aligned} \begin{pmatrix} M & S \\ \cdot & \cdot \\ M & S \end{pmatrix} &= \begin{pmatrix} 1 & (z_1/z_o)/(3\omega_{L0}) \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ \omega_{L0} & 1 \end{pmatrix} \begin{pmatrix} 1 & 1/\omega_{L0} \\ 0 & 1 \end{pmatrix} \\ &= \begin{pmatrix} 1+(z_1/z_o)/3 & (3+2z_1/z_o)/(3\omega_{L0}) \\ \omega_{L0} & 2 \end{pmatrix} \end{aligned} \quad (6.15)$$

Only because we chose such a simple example is it possible to evaluate the matrices analytically. It is to be noted that all the component matrices which make up the right hand side of Eqs. (6.14) and (6.15) have unit determinant, i.e. satisfy Eq. (A.29).

Now that the matrix elements have been found, the current density distribution at the plane (z_0+z_1) may be found by directly applying the formulation of Section 4.

Using Eqs. (3.6) and (4.2), and remembering, from Eq. (6.3) that $\Omega_L = 0$, it is seen that

$$\alpha = 1 + (z_1/z_o)/3, \quad \beta_1 = \omega_{L0}/\alpha \quad (6.16)$$

so that from Eqs. (4.5), (4.6), (4.10), (6.7), and (6.14)

$$c_2 = 0, \quad c_1 = (\alpha + i)\omega_{LO}/(\alpha^2 - 1), \quad b_2 = a_0 \quad (6.17)$$

$$b_1^2 = -\frac{\Phi_{00}}{\alpha^2 - 1} \left[1 - \frac{r^2}{9z_0^2} \left(\frac{\alpha^2 + 1}{\alpha^2 - 1} \right) \right], \quad \Delta_3 = 0$$

In this case $\alpha > 1$, hence if we are sufficiently near the axis for b^2 to be negative which implies, from Eqs. (6.7) and (6.17)

$$9z_0^2 > r^2 \left[\alpha^2 + 1/(\alpha^3 - 1) \right] \quad (6.18)$$

then from Eq. (4.10) and (4.12) the current density at radius r , $i(r, z)/i_c$ is given by

$$\begin{aligned} i(r, z)/i_c &= \frac{1}{\alpha^2} \left[1 - I(0, \lambda a_0 \alpha) \right] \\ &= \frac{1}{\alpha^2} \left[1 - e^{-\lambda^2 a_0^2 \alpha^2} \right] \end{aligned} \quad (6.19)$$

In Eq. (6.19) α is given by Eq. (6.16) and λ by Eq. (2.9).

This example was not supposed to be intrinsically interesting, it was merely to illustrate the method. In general the matrix elements must be found by integrating an equation such as Eq. (A.20) numerically. However, once the matrix elements have been found, the application of the formulae of Section 4 to a simple case is very simple.

pd

Distribution (open):

Scientific Staff AR Division.

APPENDIX A

The Matrix Formulation for the Transformation of Transverse Coordinates

In this appendix the equations of motion for an axially symmetric solid beam will be derived to the paraxial approximation. It will be shown that transverse position and velocity at one axial plane are related to those at another by a 2 x 2 matrix with complex coefficients. By suitable choice of variables, this matrix will be shown to have unit determinant.

Inside a steady beam, Poisson's equation is.

$$\underline{\underline{E}} = - \underline{\underline{\nabla}} \phi , \quad \nabla^2 \phi = - \rho / \epsilon_0 \quad (\text{A.1})$$

where $\underline{\underline{E}}$ is the electric field, ϕ is the electrostatic potential, ρ the space-charge density and ϵ_0 the dielectric constant. To the paraxial approximation, the effect of transverse variations in ρ or ϕ may be neglected. To this approximation, for axially symmetric solid beams, Eq. (A.1) can be shown to give, for small r ,

$$\phi \approx \phi_0(z) - 1/4 r^2 \left[\phi_0''(z) + \rho_0(z)/\epsilon_0 \right] \quad (\text{A.2})$$

where ϕ_0 , ρ_0 are the potential and charge density on the axis, and prime " ' " denotes d/dz .

If ϕ is given by Eq. (A.2), the electric field (E_x , E_y , E_z) has the form, from Eq. (A.1),

$$\underline{\underline{E}} = (2x\phi_2, 2y\phi_2, -\phi_0') \quad (\text{A.3})$$

where ϕ_2 denotes the expression

$$\phi_2 = 1/4 \left[\phi''(z) + \rho_0(z)/\epsilon_0 \right] \quad (\text{A.4})$$

In the same way, if we ignore the self-magnetic field of the beam, then the magnetic equations are

$$\underline{B} = \underline{\nabla} \Psi, \quad \underline{\nabla}^2 \Psi = 0 \quad (\text{A.5})$$

where $\underline{B}$ is the magnetic field and Ψ the magnetic scalar potential. Again for small r in an axially symmetric solid beam Eq. (A.5) has the solution

$$\Psi = \Psi_0(z) - 1/4 r^2 \Psi''_0(z) \quad (\text{A.6})$$

so that the magnetic field (B_x, B_y, B_z) is given by

$$\underline{B} = \left[-1/2 x B'_0(z), -1/2 y B'_0(z), B_0(z) \right] \quad (\text{A.7})$$

where B_0 is the longitudinal magnetic field on the axis Ψ'_0 . While it is possible to add a constant azimuthal field B_θ , with extra components $(-B_\theta y/r, B_\theta x/r, 0)$, this field cannot exist without a central conductor, and will therefore be ignored.

If $\underline{E}$ and $\underline{B}$ are given by Eqs. (A.3) and (A.7), we are in a position to solve Lorentz's equation

$$\frac{d\underline{v}}{dt} = -\eta \left[\underline{E} + (\underline{v} \times \underline{B}) \right] \quad (\text{A.8})$$

where $\underline{v}$ is the velocity of the particle, and η is $|e|/m$. A first integral of Eq. (A.8) gives the energy equation

$$\frac{1}{2} v^2 - 2 \eta \phi = \text{const.} \quad (\text{A.9})$$

Substitution of the expressions

$$\bar{\Phi}_{10}(z) = 2 \eta \phi_0, \quad \bar{\Phi}_{12}(z) = 2 \eta \phi_2 \quad (\text{A.10})$$

and of Eq. (A.2) into Eq. (A.9) yields the energy balance equation in the form

$$v^2 - \bar{\Phi}_{10}(z) + \bar{\Phi}_{12}(z) r^2 = \text{const.} \quad (\text{A.11})$$

The transverse equations of motion may be written, using the expressions for $\underline{E}$, $\underline{B}$, of Eqs. (A.3) and (A.7) in Eq. (A.8),

$$\dot{x} = -\eta (2 x \phi_2 + \dot{y} B_0 + 1/2 \dot{z} B'_0 y) \quad (\text{A.12})$$

$$\dot{y} = -\eta (2 y \phi_2 - \dot{x} B_0 - 1/2 \dot{z} B'_0 x)$$

We may now define the Larmor frequency ω_L by

$$\omega_L = 1/2 \eta B_0, \quad (\text{A.13})$$

then the time derivative of ω_L , $\dot{\omega}_L$, is given by

$$\dot{\omega}_L = 1/2 \eta \dot{z} B'_0. \quad (\text{A.14})$$

To this order of approximation, since $\dot{\omega}_L$ only appears in the product $(\dot{\omega}_L y)$, $\dot{\omega}_L$ may be considered as constant for all particles. By some algebra, Eq. (A.12) can be written in the form:

$$(\dot{x} + i\dot{y}) = (-\bar{\Phi}_{12} + i\dot{\omega}_L) (x + iy) + 2i\omega_L (\dot{x} + i\dot{y}) \quad (\text{A.15})$$

Equation (A.15) has been derived previously by other authors, e.g. Herrman. Since the equation is linear in $(x + iy)$ and its derivatives, a linear

transformation could be derived relating the $(x + iy)$, $(\dot{x} + i\dot{y})$ at one time, and therefore plane, with those at another. However, the solutions of Eq. (A.15) are complex, and therefore it is first convenient to make the transformation

$$w = (x + iy) e^{-i\chi} \quad (\text{A.16})$$

where χ is the rotation through the Larmor angle

$$\chi = \int \omega_L dt \quad (\text{A.17})$$

In terms of these variables, Eq. (A.15) becomes

$$\ddot{w} + (\Phi_{12} + \omega_L^2) w = 0. \quad (\text{A.18})$$

If we prefer z as the independent variable, we may use the relation

$$\frac{d}{dt} = \dot{z} \frac{d}{dz} = \Phi_0^{1/2} \frac{d}{dz} \quad (\text{A.19})$$

to first order, to obtain from Eq. (A.18) the relation

$$\frac{dw}{dz} = \Phi_0^{-1/2} u, \quad \frac{du}{dz} = -(\Phi_{12} + \omega_L^2) \Phi_0^{-1/2} w \quad (\text{A.20})$$

where u is the transverse velocity $\dot{w}$ in the rotated coordinate system.

It is to be noted that Eq. (A.18) is linear in w - whether or not there is magnetic flux threading the cathode (i.e. $\omega_L \neq 0$ at $z = 0$). The paraxial equations which may be derived to give the beam boundary are non-linear (in fact have a singularity as $w \rightarrow 0$); the equations given here are quite different, however. They are the equations for the motion of particles inside the beam. However, the equations assume we know Φ_{12} which is related,

via Eqs. (A.4) and (A.10), to the space-charge density. If the total current in the beam is I , and the beam radius $a(z)$, in the zero-temperature approximation, then the space-charge density $\rho_0(z)$ is given by

$$\rho_0 = I \int_0^{-1/2} / (\pi a^2) \quad (\text{A.21})$$

Hence in order to set up Eqs. (A.18) and (A.20), it is first necessary to solve the paraxial equation for the beam edge (c.f. Ref. 10).

The energy balance equation, Eq. (A.11) involved the square of the velocity v . It is important to relate this quantity to $\dot{u}$. From Eqs. (A.16), (A.17), (A.19), and (A.20) we see that if the velocity is $(\dot{x}, \dot{y}, \dot{z})$ then

$$(\dot{x} + i \dot{y}) = \frac{d}{dt} (w e^{i\chi}) = (u + i \omega_L w) e^{i\chi} \quad (\text{A.22})$$

Hence we may deduce that v^2 is given by

$$v^2 = \dot{x}^2 + \dot{y}^2 + \dot{z}^2 = |u + i \omega_L w|^2 + \dot{z}^2 \quad (\text{A.23})$$

Now $|w|$ is simply the distance r from the axis; hence the energy balance equation, Eq. (A.11), may be written in the form

$$|u + i \omega_L w|^2 + \dot{z}^2 - \frac{I}{2} (z) + \frac{I}{2} |w|^2 = \text{const.} \quad (\text{A.24})$$

The solutions of Eq. (A.20) are real if the initial values of w, u are real. It is easily verified that if w_1, u_1 and w_2, u_2 are any two solutions of Eq. (A.20), then

$$\frac{d}{dz} (w_1 u_2 - w_2 u_1) = 0 \quad (\text{A.25})$$

Let us choose $w = M(z)$, $v = \dot{M}(z)$, and $w = S(z)$, $v = \dot{S}(z)$ as the solutions of Eq. (A.20) satisfying

$$M(0) = 1, \dot{M}(0) = 0, S(0) = 0, \dot{S}(0) = 1 \quad (\text{A.26})$$

Then it is seen that $M(z)$ is the magnification of the beam, being the change in distance from the axis of a particle starting at unit distance from the axis with zero transverse velocity; $S(z)$ is the stiffness of the beam, being the distance from the axis reached by a particle starting on the axis with unit transverse velocity. It is to be noted that M , S , $\dot{M}$, $\dot{S}$ do not, to this order of approximation, depend on Z , the longitudinal velocity at the cathode.

If now a particle has initial position and velocity components such that

$$w(0) = W, \quad u(0) = U \quad (\text{A.27})$$

then these coordinates transform so that at any other plane

$$\begin{pmatrix} w \\ u \end{pmatrix} = \begin{pmatrix} M & S \\ \dot{M} & \dot{S} \end{pmatrix} \begin{pmatrix} W \\ U \end{pmatrix} \quad (\text{A.28})$$

From Eqs. (A.25) and (A.26), we see that the matrix in Eq. (A.29) has unit determinant

$$M \dot{S} - \dot{M} S = 1 \quad (\text{A.29})$$

Because the ray axis of the paraxial system is straight (in this case it is the z -axis), the change in transverse position due to small change in initial longitudinal velocity ϵ would be of the order ϵW , ϵU , and so could be neglected to this order of approximation. By identical arguments

it can be shown that, for hollow beams with a curvilinear ray-axis, the transformation laws have the form

$$\begin{pmatrix} w \\ u \end{pmatrix} = \begin{pmatrix} M & S \\ \dot{M} & \dot{S} \end{pmatrix} \begin{pmatrix} W \\ U \end{pmatrix} + \frac{\epsilon W}{R} \begin{pmatrix} \Delta \\ \dot{\Delta} \end{pmatrix} \quad (\text{A.30})$$

where w , W , u , U , ϵ are as above, R is the instantaneous radius of the ray-axis, and Δ , $\dot{\Delta}$ depend only on z through the electromagnetic fields. For hollow beams with a straight ray-axis, Δ , $\dot{\Delta}$ will be zero, though M , $\dot{M}$, S , $\dot{S}$, will be related to the fields through slightly different formulae.

For sheet beams with no variation in the y direction, the $\epsilon W/R$ term becomes ϵW , but formulae similar to Eq. (A.30) arise. Again if the ray-axis is straight, Δ , $\dot{\Delta}$ will be zero.

APPENDIX B

Change of Coordinates and the Jacobian

In the body of the paper we often wish to transform variables from an orthogonal coordinate system (q_1, q_2, q_3) to one (Q_1, Q_2, Q_3) where these are related by the transformations

$$q = q_1 + iq_2, \quad Q = Q_1 + iQ_2, \quad q = CQ + D, \quad q_3^2 = Q_3^2 + E \quad (B.1)$$

where C, D are independent of Q_1, Q_2, Q_3 and E is independent of Q_3 . Now the volume element $dq_1 dq_2 dq_3$ in the q_i system is related to that in the Q_i system $dQ_1 dQ_2 dQ_3$ by the expression

$$dq_1 dq_2 dq_3 = J dQ_1 dQ_2 dQ_3 \quad (B.2)$$

where J is the Jacobian of the transformation, and is given by the determinant

$$J = \begin{vmatrix} \partial q_1 / \partial Q_1 & \partial q_1 / \partial Q_2 & \partial q_1 / \partial Q_3 \\ \partial q_2 / \partial Q_1 & \partial q_2 / \partial Q_2 & \partial q_2 / \partial Q_3 \\ \partial q_3 / \partial Q_1 & \partial q_3 / \partial Q_2 & \partial q_3 / \partial Q_3 \end{vmatrix} \quad (B.3)$$

Now from Eq. (B.1) we have the expressions

$$\partial q_1 / \partial Q_3 = \partial q_2 / \partial Q_3 = 0, \quad \partial q_3 / \partial Q_3 = Q_3 / q_3 \quad (B.4)$$

and

$$\frac{\partial q_1}{\partial Q_1} \frac{\partial q_2}{\partial Q_2} - \frac{\partial q_1}{\partial Q_2} \frac{\partial q_2}{\partial Q_1} = \left| \frac{\partial q}{\partial Q} \right|^2 = |C|^2 \quad (B.5)$$

Hence the Jacobian has the value $Q_3 |C|^2 / q_3$, and Eq. (B.2) becomes

$$dq_1 dq_2 dq_3 = Q_3 |C|^2 / q_3 dQ_1 dQ_2 dQ_3 \quad (B.6)$$

This result is required in the text. Note that the transformation is impossible if the Jacobian vanishes, i.e. $|C|$ is zero.

APPENDIX C

A Special Integral

We will consider a function p which may take complex values, such that

$$|p - C| \geq b \quad (C.1)$$

where C is complex so that

$$C = \Gamma e^{i\gamma} \quad (C.2)$$

and Γ, γ, b are real. An integral which occurs frequently in this paper is

$$I(\Delta, b) = \frac{1}{\Lambda} \iint \exp - |p - D|^2 dp_x dp_y \quad (C.3)$$

where p_x, p_y may range over all values defined by Eq. (C.1), and Δ is defined by

$$C - D = \Delta e^{i\delta} \quad (C.4)$$

Substituting

$$p = Q e^{iq} + C \quad (C.5)$$

into Eq. (C.1) and (C.3) it is seen that

$$I(\Delta, b) = \frac{1}{\Lambda} \int_b^\infty Q dQ \int_0^{2\pi} \exp - |Q + \Delta e^{i(\delta-q)}|^2 d q$$

$$\begin{aligned}
 &= \frac{1}{\lambda} \int_b^{\infty} Q \, dQ \int_0^{2\pi} \exp - \left[Q^2 + \Delta^2 + 2 Q \Delta \cos (\delta - q) \right] d q \\
 &= \int_b^{\infty} 2 Q \exp - \left[Q^2 + \Delta^2 \right] I_0 (2 Q \Delta) d Q \quad (C.6)
 \end{aligned}$$

In Eq. (C.6) I_0 is the modified Bessel Function of order zero, and we have used the relation

$$I_0 (x) = \frac{1}{2\pi} \int_0^{2\pi} \exp (x \cos \theta) d\theta \quad (C.7)$$

$I(\Delta, b)$ is plotted versus Δ, b in Figs. 2 and 3.

When Δ is zero, i.e. $C = D$, Eq. (C.6) takes the very simple form

$$I(0, b) = \int_b^{\infty} 2 Q e^{-Q^2} dQ = e^{-b^2} \quad (C.8)$$

while if $b \rightarrow 0$ it may be shown that

$$\left[1 - I(\Delta, b) \right] / b^2 = \int_0^b (2/b^2) Q e^{-(Q^2 + \Delta^2)} I_0 (2 Q \Delta) dQ \rightarrow e^{-\Delta^2} \quad (C.9)$$

Finally if $b = \infty$,

$$I(\Delta, \infty) = 0 \quad (C.10)$$

If the integral of $\exp - (p - D)^2$ is required in the region between the non-intersective circles

$$\left| p - c_1 \right| = b_1, \quad \left| p - c_2 \right| = b_2 \quad (C.11)$$

where the circle with suffix 2 completely surrounds that with suffix 1, then it is clear from Eq. (C.6) that the integral is

$$I = \frac{1}{\lambda} \iint_{\substack{|p-c_2| < b_2 \\ |p-c_1| > b_1}} \exp - (p - \Delta)^2 dp_x dp_y = I(\Delta_1, b_1) - I(\Delta_2, b_2) \quad (C.12)$$

where Δ_1, Δ_2 are given by

$$|c_1 - D| = \Delta_1, \quad |c_2 - D| = \Delta_2 \quad (C.13)$$

When the circles intersect, Eq. (C.12) is more complicated, it is still possible to eliminate one of the integrals, but we do not, for simplicity, consider this case in this paper. The conditions for non-intersection are that

$$|c_2 - c_1| < b_2 - b_1 \quad (C.14)$$

and Eq. (C.14) is only valid if this condition is satisfied.

References

- 1) P. A. Lindsay, Advances in Electronics, 13, 181 (1961).
- 2) J. R. Pierce, "Theory and Design of Electron Beams",
D. von Nostand Co., Inc., New York (1954).
- 3) C. C. Cutler and M. E. Hines, Proc. Inst. Radio Eng. 43, 307 (1955).
- 4) W. E. Danielson, J. L. Rosenfeld and J. A. Saloom, Bell Syst.
Tech. J. 35, 375 (1956).
- 5) P. T. Kirstein, Trans PGED of the Inst. Radio Eng. XXXX (1963).
- 6) E. Ash, Proceedings 4th International Conference on Microwave Tubes,
XXXX (1963).
- 7) G. Herman, J. Appl. Phys., 29, 127 (1958).
- 8) Y. V. Troitski, J. Techn. Fiz. 30, 25 (1960).
- 9) P. A. Sturrock, Static and Dynamic Electron Optics,
Cambridge Univ. Press (1955).
- 10) P. T. Kirstein, J. Electron. and Contr., 8, 207 (1960).

List of Figures

Fig. 1. Schematic of a pencil beam through a defining aperture.

Fig. 2. Plot of $[1 - I(\Delta, b)] / b^2$ versus Δ for $b \leq 1$.

Fig. 3. Plot of $1 - I(\Delta, b)$ versus Δ/b for $b \geq 1$.

FIG. 1.

FIG. 2.

FIG. 3.