EUROPEAN ORGANISATION FOR NUCLEAR RESEARCH

CERN-ISR-VA/74-31

Closed distribution

ION INDUCED GAS DESORPTION PROBLEMS IN THE ISR*

by

R.S. Calder

CM-P00064832

Geneva, 7th June 1974

* Invited paper presented at the 4th Annual Vacuum Conference, Liverpool, England, 17th - 19th April 1974.

Paper submitted for publication in 'Vacuum'.

Abstract

Not least among the many stringent conditions which must be satisfied to achieve the proper operation of the Intersecting Storage Rings at CERN are those pertaining to its 2 km of ultrahigh vacuum. Apart from the direct influence of the residual gas molecules through nuclear and Coulomb scattering on the stored beam lifetimes (of the order of days during which the stored protons should travel the astronomical distance of some light days!) there are also indirect processes which additionally involve adsorption/desorption phenomena on the vacuum chamber wall. The beam of high energy protons creates low energy secondary ions in the residual gas. These ions, generated in the space charge potential of 1 kV per 10 ampères of proton beam, are accelerated by this potential onto the stainless steel vacuum chamber wall where a variety of adsorption/desorption phenomena may be stimulated. Desorbed molecules are fed back into the residual gas resulting in the possibility of creating an unstable run-away pressure increase which can finally destroy the stored beam. This danger depends on the local parameters of the vacuum system, and most critically, on the state of the vacuum chamber surface.

The paper summarises recent observations in this field and describes the results of investigations aimed at producing cleaner surfaces in vacuum chambers. These investigations, which have included high temperature bakeouts, ion bombardment scrubbing by glow discharge, oxidation, etc., will show that under favourable conditions, net negative desorption coefficients can be obtained which turn the Intersecting Storage Rings into a large ion pump. Results, supported and compared with measurements using Auger and Sims surface analysis, are presented mainly from the empirical point of view with the emphasis on practical implications for machines where the surfaces of the vacuum system are subjected to ion bombardment.

1. INTRODUCTION

Low energy ion interactions seem a far cry from our main business at CERN, namely multi-GeV proton physics. The purpose of this paper is to explain why, in a special technological situation, there has arisen an important connection between the two subjects. It is, in fact, only in the last 2 to 3 years that we at CERN have become concerned with low energy ion surface effects, and this has been due not so much to a pure interest in the subject - although that certainly exists - but because these effects interfere with and limit critically the operation of the world's highest energy nuclear physics facility - namely the CERN Intersecting Storage Rings or ISR. Therefore our approach to the effect - and for us it is a problem of ion stimulated gas desorption in a UHV environment - is rather empirical and orientated towards problem solving rather than to a pure study of the subject. The basic question is familiar - it is that of how to clean a metal surface of adsorbed gas; but instead of dealing with, for example, a square millimetre on a single crystal face of tungsten, we are trying to do the same for 2 km of UHV stainless steel chamber involving a thousand square metres of surface.

Let me start at the beginning - what is the ISR? It is a unique high energy facility (shown schematically in Fig. 1) in which 28 GeV protons from a proton synchrotron accelerator are accumulated and constrained to travel on two counter circulating and separate orbits. The orbits are interleaved deformed circles of approximately 300 metres diameter which intersect at eight points around the ring. The almost head-on collisions of the protons in the opposed beams give a useful energy (i.e. for the production of new particles etc.) in the centre of mass coordinates of 56 GeV. This, as shown by the appropriate relativistic transformation, could only be achieved with conventional targets and accelerators if the latter were able to give almost 2'000 GeV - something still quite beyond present day accelerator possibilities. Hence the unique and enormous value of the ISR in the realm of sub-nuclear physics.

The requirements on the vacuum system of the ISR are rather stringent and are determined primarily by the following characteristics. Firstly the lifetime of the 10 to 20 A beam, which may be limited by blow-up due to scattering collision processes on the residual gas in the vacuum, should exceed 24 hours. For this an average pressure in the range 10^{-10} to 10^{-9} torr, depending on the residual gas composition, is required. The second vacuum condition comes via a consideration of background events originating from these same collisions with residual gas molecules and which interfere with the detection of true beam-beam events. This imposes an upper limit to the pressure of about 10^{-11} torr in and around the intersection regions. In fact, for reasons which will become apparent later, the whole 2 km system now operates at an average pressure of about 1×10^{-11} torr. In the photo (Fig. 2) can be seen one of the intersection regions and it gives some idea of the scale of the installation, of which the vacuum system comprises some 70 turbomolecular pumps, 300 sputter-ion pumps, 600 titanium sublimation pumps, 500 Bayard-Alpert gauges and some 10'000 all metal flanges - all bakeable to 300°C .

So far so good - but our problems start when we begin to accumulate high intensity proton beams. At one or more localised regions around the rings important and sometimes catastrophic pressure increases occur. These, which we call "pressure bumps" and which have proven to be a severe and critical limitation on the exploitation of the ISR, have their origin in the following mechanism. Positive ions, mostly H_2^+ , and electrons are produced by beam-residual gas ionising collisions, see Fig. 3. The ions are accelerated radially out of the beam by its space charge potential and onto the vacuum chamber walls. Here, the ions, with an energy given by this space charge potential of some 100 volts per amp. of proton beam, release adsorbed surface contaminants. This increases the local pressure which in turn increases the desorbing ion flux. Thus a potentially unstable pressure avalanche is initiated. Here we introduce η , the net desorption coefficient and define it as the net number of molecules entering the gas phase per incident ion. Net implies that the incident ion, which may be reflected or alternatively lost from the gas phase (i.e. ionically pumped) must be considered. Hence $\eta \geq -1$, and for negative values a pumping action and net pressure decrease will be observed. η is the central parameter in our discussion and will, in general, be a function of the ion energy, ion species, state of surface and desorbed species.

The electrons created in the ionising events are trapped within the positive beam which they would eventually neutralise. However, for various reasons concerned with beam stability, this must be prevented and therefore these electrons are extracted onto special clearing electrodes placed periodically around the machine.

It is relevant to point that desorption of adsorbed gas either by synchrotron radiation (the dominant effect in electron storage rings) or by beam loss of protons onto the chamber walls is, in both cases, negligible.

2. PRESSURE BUMPS

An elementary consideration in which we balance the gas flow into and out of a section of the vacuum chamber leads, see Fig. 4, to the differential equation

$$A \frac{dP}{dt} dx = q_0 dx + PI\sigma\eta dx + C \frac{d^2P}{dx^2} dx - \left(S'P dx \right) \quad (1)$$

in which P is pressure, A is the tube cross section and q_0 the normal outgassing rate for unit length. The second term gives the beam induced desorption proportional to beam current I , pressure P , ionisation cross section σ and net desorption coefficient η . The third term, in which C is the gas conductance per unit length, represents the gas flow in a conductance limited system and may be replaced by the fourth term in parenthesis when conductance restrictions are small. $S' \left(= \frac{S}{L} \right)$ is then the effective pumping speed per unit length in this lumped volume approximation.

Obviously, considering the lumped volume approximation, the beam induced desorption term acts in opposition to the installed pumping speed and the solution

$$P_{t \rightarrow \infty} = \frac{q_0}{(S' - I\sigma\eta)}$$

demonstrates clearly the possibility of an unstable pressure run-away when a value of $(I\eta)_{crit} \approx S'/\sigma$ is approached.

The remedy appears to be straight forward - either reduce η by producing cleaner surfaces or increase the effective pumping speed by installing bigger pumps. The latter, however, leads to conduction.

limitations and a proper solution in which the last term is dropped from the equation (1) and S is used to establish the boundary conditions at the pumping ports, gives the essentially geometric stability condition¹⁾

$$\tan \sqrt{\frac{I_0 \eta}{C}} L < \frac{S}{\sqrt{I_0 \eta C}}$$

$$\text{i.e. } I_0 \eta < \pi^2 C / 4L^2$$

which must be satisfied. Increasing the pumping speed gives little help, rather one must reduce the inter-pump distance $2L$ or increase the conductance. Since further improvement in either of these directions is difficult - the chamber conductance is limited by the aperture of the machine magnets and the inter-pump distance by the length of these magnets - we must concentrate on obtaining cleaner surfaces with reduced ion induced gas desorption yields.

Here I would like to show two examples of a pressure bump development. In the first, see Fig. 5, the pressure grows rapidly as the beam current is increased, and, after causing some loss of beam, it recovers to a stable but increased value. The above simple theory seems to account sufficiently well for the observed behaviour. The second example, see Fig. 6, is different in so far as the whole pressure increase occurred at constant beam current I . In fact the pressure increase during the first 5 hours after stacking the proton beam was barely discernible and became important only after 10 hours and critical after 12 hours. The above simple theory is not adequate to explain this very slow pressure rise at constant current and it seems one may have to allow for re-adsorption effects on the walls with modified binding energies and/or for changing gas composition during the growth of the pressure bump - both of which could lead to a progressive change or increase of η and the development of an unstable situation.

Let us look a little more closely at the material of our chamber surfaces and the pressure bump desorption products. The material is a vacuum annealed (800°C) 316 nitrogen hardened low carbon austenitic stainless steel which is baked in situ under vacuum for 24 h at 300°C after conventional degreasing by trichlor, etc. This is our standard chamber preparation. An Auger analysis of such a surface shows important carbon and oxygen peaks, but only very weakly the metal components. The surface is far

from clean²⁾. After a higher temperature bakeout to 400°C a very slight and un-spectacular improvement is seen.

Fig. 7 shows the desorption products in an ISR pressure bump. The original gas composition of $\approx 90\% \text{H}_2$ is modified by the desorption of many components, of which CO at mass 28 and H_2 dominate. The final composition in this particular case reached 40% H_2 , 40% CO with the remaining 20% spread over a variety of masses up to 44 and which are commonly found in vacuum systems. Only mass 26 seems out of proportion with common cracking patterns and causes some problem of identification. Often, for reasons not yet understood, the induced H_2 desorption is much smaller.

Fig. 8 shows values of the desorption coefficient η measured in the ISR under the empirical but realistic conditions of changing gas composition³⁾. It is shown as a function of bombarding ion energy after in situ bakeouts of 300°C and 340°C - the latter shows a considerable improvement, more perhaps than one might have reasonably expected on the basis of the Auger spectra after 300°C and 400°C bakeouts. One should note that at the lowest energies, corresponding to beam currents of a few amps, the 340°C bakeout gives a negative η and the phenomenon of beam pumping, rather than beam induced desorption, can be observed.

3. SOLUTION TO THE PROBLEM OF PRESSURE BUMPS

The evidence cited above suggests that our standard method of chamber preparation by baking at 300°C leaves us with surfaces which are not quite clean enough for trouble free operation of the ISR, but which can probably be cleaned to yield zero or even negative desorption coefficients. Certainly the possibility of solving our problem by reducing the desorption coefficient rather than by the brute force attack of more and bigger pumps is more elegant and the prospect of a negative desorption coefficient giving self pumping of the machine is particularly attractive.

When initially commissioned it was customary to prepare the vacuum system by 200°C bakeouts, but we soon learnt that a considerable improvement with respect to vacuum stability and the suppression of pressure bumps was obtained by baking to 300°C. At the same time the observed desorption

coefficients η decreased from values typically > 2 to values < 1 and often very close to zero. Unfortunately the design of the ISR vacuum chamber does not, in general, allow us to pursue this approach any further and to bake, for example, in situ at 340°C to obtain the low η values shown previously in Fig. 8. Therefore we are obliged to search for other methods. Methods, which to date appear to be the most promising include ion bombardment cleaning in a glow discharge, very high temperature (800°C - 1000°C) firing in a vacuum furnace, and simply a change to certain other materials, notably titanium. Results from gold or silver plated stainless steel have, in general, been variable and rather disappointing; attempts to 'burn-off' the contaminating carbon layer by high temperature oxidation have been inconclusive⁴⁾.

Fig. 9 shows the marked reduction in η after our glow discharge cleaning treatment³⁾ - one notes particularly the strongly negative η which, after a slight initial increase, becomes independent of voltage. This cleaning treatment was made in situ, that is, there was no exposure to the atmosphere intervening between the treatment and the subsequent vacuum conditioning bakeout and the measurements. Similar results however are obtained if, as is now our standard practice, an atmospheric exposure does intervene. The Auger spectra in Figure 10 show the effects of the glow discharge cleaning - notably a large reduction in the overlayering carbon, although a small persistent peak remains. The compositional change following atmospheric exposure and vacuum rebake after the glow discharge cleaning is primarily a strong re-oxidation of the surface without any other major recontamination.

Our glow discharge cleaning technique is simple although probably still not yet optimised. Vacuum chambers of virtually any length - and typically up to ≈ 5 m - are first given the standard 300°C vacuum bakeout and are then treated by flowing argon through them at $\approx 2.10^{-2}$ torr while maintaining a slightly abnormal D.C. glow discharge between the chamber wall (to be cleaned by ion bombardment) and a central wire

acting as anode^{*}. Upon striking the discharge a very large pressure increase can be observed which may approach in magnitude the pressure of the argon carrier gas⁶⁾. The composition of the desorbed gas - see Fig. 11 - is predominantly CO and H₂, a spectrum rather similar to that shown earlier for an ISR pressure bump. The best cleaning is obtained if the chamber is held at an elevated temperature - we use 300°C - during the discharge. Maybe this reduces re-adsorption. Doses of some $2 - 4 \cdot 10^{18}$ ions cm⁻² appear necessary to reach approximately zero desorption - complete cleaning? - although the bulk of the desorption is complete by $\approx 1 \cdot 10^{17}$ ions cm⁻². The discharge runs in the abnormal regime at some 20 A cm⁻² cathode current and ≈ 350 volts, although the bombarding ion energy will be given by the cathode fall voltage of ≈ 150 volts. From a knowledge of the gas flow and pumping parameters of the discharge cleaning equipment, one reaches the conclusion that our stainless steel chamber surfaces, even after the 300°C bakeout, are contaminated with at least a complete monolayer of desorbable CO and H₂. Other specimens, prepared in an essentially similar way, have shown much higher desorptions in which, apparently, the equivalent of some tens of monolayers are liberated, or, as is probable for CO, created from carbon and oxygen.

* The method is essentially that described by Govier and McCracken⁵⁾ apart from the pre-bake at 300°C. This is probably the factor which is important to prevent a subsequently increased hydrogen degassing rate which was observed by Govier and McCracken. These authors attributed this effect to the break-up of adsorbed water molecules followed by ion burial of the hydrogen produced. In the work reported here the adsorbed water would be removed by the 300°C bakeout before the discharge cleaning. In fact, after a further vacuum conditioning bakeout at 300°C, we cannot even observe any argon in the system and all thermal outgassing rates are normal for this type of material⁷⁾ and not significantly different from that measured before the argon glow discharge cleaning.

The dose of 3.10^{16} ions cm^{-2} would only be attained in the ISR after some 2000 years of normal operation, see Fig. 11. Hence, in principle, it seems that the machine would always operate at the maximum of the desorption efficiency curve unless we use some method such as the glow discharge to accelerate the cleaning process. This observation is, however, rendered questionable by some results which suggest that in some cases there can be a significant self-cleaning effect in the ISR.

We are using the glow discharge not only as a cleaning process but also as a rather crude analytical tool at the same time. A vacuum chamber, once cleaned by the process, may be exposed to the atmosphere for days or even months and then retested by this method. After the normal vacuum conditioning bakeout of 300°C - to remove water vapour and other superficial atmospheric contaminants - it is found to exhibit an extremely small desorption spectrum indicating that no important recontamination has taken place. The same is true after several vacuum bakeouts during which the enhanced diffusion and outgassing rate of H_2 could, conceivably, have recharged the surface⁷⁾.

Similar improvements in apparent surface cleanliness as monitored by the glow discharge method and by Auger surface analysis have been obtained by very high temperature vacuum bakeout²⁾. To date, unfortunately, we have not been able to confirm this by direct observations of the desorption coefficient η in the ISR⁴⁾.

An alternative line of approach involves the use of other, cleaner materials to replace the traditional stainless steel chamber. This, of course, would involve considerable expense and we would prefer to clean our existing chambers. Nevertheless, we are actively investigating these possibilities and to date we have obtained the best results from titanium which has been given an 800°C vacuum bakeout prior to installation in the ISR. This has given consistently negative desorption coefficients and is comparable with the best results from glow discharged stainless steel⁴⁾.

4. SUMMARY, OUTLOOK AND CONCLUSIONS

Our objective at CERN is to achieve a completely reliable vacuum of about 10^{-11} torr throughout the whole 2 km of ISR vacuum chamber which is stable against all operating conditions. Empirically this means producing a net keV ion desorption coefficient which is very close to zero, i.e. $\eta < 0.1$, or negative for the 1000 m^2 of chamber surface. Of the several methods already discussed, ion scrubbing by a glow discharge seems to be the most promising. It has yielded negative values of η in several test sections of the ISR involving several square metres of surface. The result can be a substantial beam pumping effect which, in the theoretical limit of $\eta \rightarrow -1$, can, for 10 amps of beam current, equal 7 l/sec per metre of chamber and which is approximately equal to the installed pumping speed.

Fig. 12 shows a nice example of this beam pumping effect observed in a glow discharge cleaned section. It is just the reverse of the earlier pressure bumps of Figs. 5 and 6. We would like to extend this to the whole machine. Unfortunately, since the glow discharge treatment cannot be done in-situ, it will involve a very considerable amount of work and a loss of machine operation over several months. We are loathe to embark precipitously into this project without being completely sure of ourselves. Apart from wondering whether or not an easier or better solution may exist, we are most critically concerned about the long term stability of such a treatment. Long term must be taken to mean several years - perhaps 10 - and include the possibility of 2 to 3 atmospheric ventings and rebaking cycles per year. All indications up to the present after 3 or 4 atmospheric exposures and rebaking cycles, storage in the atmosphere over several months or operation in the machine for about a year, indicate that the treatment is more or less stable. I say 'more or less' because of the difficulty in obtaining exactly reproducible conditions and results in our experimental situation. Certainly there is not a catastrophic recontamination back to anything like the initial level.

As a result of these considerations our approach will probably be one of glow discharge cleaning the ISR ring piece-meal while at the same time continuing our research for better alternatives.

Our outlook for the future is one of confidence. We expect to solve our problem of pressure bumps by improved surface cleanliness and we may, simultaneously, have the satisfaction of turning the ISR machine into a very large ion pump. In parallel we are prepared for the worst and we are developing our brute force reserve line of bigger and better pumps - namely distributed Ti-sublimation getter pumping.

I may conclude by introducing our next problem - the possibility of converting the ISR to still higher energies by using super conducting magnets. If this should be done it becomes rather attractive to operate the vacuum chamber at liquid helium temperature. The advantages would be an enormous reduction of all outgassing rates and to convert the whole chamber surface into a large cryopump. This proposition does, however, entrain new problems related to those already discussed. So far we have had difficulties when η is of the order of unity and we must aim to achieve values of less than 0.1 or, preferably, negative. However, as has been shown in some recent work⁸⁾, a cryo-surface which accumulates a substantial layer of condensed gas, e.g. H_2 , may exhibit η values in excess of 10^4 ! I will leave you to think, as we are doing, about this alarming prospect!

Acknowledgements

The work reported here is due to the combined efforts of the whole of the ISR Vacuum Group at CERN. The author is particularly indebted to Dr. A.G. Mathewson for the data on Auger analysis and to Mr. F. Le Normand for work on glow discharge cleaning.

References

- ¹E Fischer and K Zänkel, The Stability of the Residual Gas Density in the ISR in presence of High Intensity Proton Beams, CERN-ISR-VA/73-52.
- ²A G Mathewson, The Surface Cleanliness of 316 L + N Stainless Steel studied by SIMS and AES, this conference.
- ³O Gröbner and R S Calder, Beam Induced Gas Desorption in the CERN Intersecting Storage Rings, 1973 Particle Accelerator Conference, IEEE Transactions on Nuclear Science, Vol. NS-20(3), 1973, 760.
- ⁴R S Calder, E Fischer, O Gröbner and E Jones, Vacuum Conditions for Storage Rings, presented at the 9th International Conference on High Energy Accelerators, 2nd-7th May 1974, Stanford, California.
- ⁵R P Govier and G M McCracken, Gas Discharge Cleaning of Vacuum Surfaces, J Vac Sci Technol, Vol. 7, 1970, 552.
- ⁶R S Calder, A. Grillot, F. Le Normand and A G Mathewson, Manuscript in preparation.
- ⁷R S Calder and G Lewin, Reduction of Stainless Steel Outgassing in Ultrahigh Vacuum, Brit J Appl Phys, Vol. 18, 1967, 1459.
- ⁸S K Erents and G M McCracken, Sputtering of Condensed Gases by Proton Bombardment, Culham Laboratory Report CLM-P 360, (presented at the fifth International Conference on Atomic Collisions in Solids, Gatlinburg, Tennessee, 24-28th September 1973).

Figure Captions

- Fig. 1 The general layout of the CERN proton synchrotron accelerator and the Intersecting Storage Rings (ISR).
- Fig. 2 A photograph of one of the intersection regions of the CERN ISR.
- Fig. 3 A schematic representation of the mechanism causing 'pressure bumps' in the ISR.
- Fig. 4 An idealised element of the ISR linear vacuum system. q_0 is the normal thermal outgassing per unit length and $PI\sigma\eta$ the beam induced gas desorption.
- Fig. 5 Beam storage which induces a localised pressure run-away or 'pressure bump'. This is followed by some loss of beam and the recovery of the pressure to a stable but increased value.
- Fig. 6 Localised pressure run-away at constant proton beam current. The origin of the time scale corresponds to the time when the 10.5 A beam was stored.
- Fig. 7 Desorption spectrum for an ISR beam induced pressure bump. (The bombarding ion energy of 1.2 keV is, in this example, determined by a special biasing test electrode and is not, as normal, given by the ISR beam space charge potential).
- Fig. 8 Desorption coefficient η as a function of the ion energy E_i for the ISR stainless steel vacuum chamber. The curves show the relative efficiencies of 24 hour vacuum bakeouts at 300°C and 340°C (ISR proton beam current $I = 3$ A).
- Fig. 9 The dependence of the desorption coefficient η on ion energy E_i , (1) before and (2) after an argon glow discharge cleaning treatment (measured at 6.0 and 9.5 A ISR proton beam currents respectively).
- Fig. 10 The Auger electron spectra for the ISR vacuum chamber steel showing the effect on surface composition of argon glow discharge cleaning. The top trace gives the initial condition, the middle trace the condition at the end of the discharge and the bottom trace the condition after re-installation in the ISR.
- Fig. 11 The evolution of gas desorption and the desorption coefficient η during the process of argon glow discharge cleaning.
- Fig. 12 These traces show the pressure increase observed at a glow discharge cleaned section of the ISR when dumping a 10 A proton beam. This is an example of 'beam pumping' associated with negative values of the desorption coefficient η . (There is a recorder offset between traces).

Fig. 1

Fig. 2

The Process Causing Pressure Bumps In The ISR

Fig. 3

Fig. 4

Fig. 5

Fig. 6

fig.6

Fig. 7

Fig. 8

Fig. 9

Fig. 10

Fig. 11

Fig. 12.