CERN LIBRARIES, GENEVA

CM-P00064037

AR/Int. SG/62-7

11 July, 1962

EXPERIMENTAL UTILISATION OF PROTON STORAGE RINGS

by

L. W. Jones ^{x)}

B. de Raad

CERN, Genève

Paper prepared for the 1962
International Conference on Instrumentation for
High Energy Physics at CERN.

^{x)} On leave from the University of Ann Arbor, Mich.

I. Introduction

Successful operation of the CERN and Brookhaven alternating gradient synchrotrons has stimulated discussions among physicists as to the next step in high-energy accelerator construction. While most discussion has centered about proton synchrotrons of energy greater than 100 GeV, the possibility of colliding beams presents another interesting method of extending the available energy in high energy research. The Accelerator Research Division at CERN has been studying the addition of 25 GeV proton storage rings to the CERN P.S., and during the past spring a small study group was assembled to consider the utility of such storage rings from the experimental, theoretical physics, and accelerator design viewpoints. The present paper is drawn from contributions and discussions of this study group.

In this brief paper we will only present a summary of possible storage ring parameters and discuss factors in the accelerator design which are related to its utility for experiments. We also present some considerations on detectors and their possible use with colliding beams. We shall not discuss here the many particular experiments and theoretical questions which occupied a major part of the study.

II. Beam Characteristics

Colliding beam storage rings which use as their injector the CERN P.S. would be designed for 25 GeV protons. While earlier discussions centered about storage rings overlapping at just two points, it developed that the experimental demands on such a machine would probably require a maximum number of interaction regions around two overlapping concentric storage rings (CSR). The basic concepts of colliding beams, storage rings, and beam stacking are adequately covered in the literature ^{1,2,3)} and we shall not review them here.

The design of the CSR considered recently (Fig. 1) would have the following beam characteristics in the interaction regions:

Beam width	7 cm
Beam height	1 cm
Total energy spread	2.3 o/o
Intersection angle	15°
Circulating beam current	20 amperes
Interaction rate	1.8×10^5 events/sec.

The circulating beam current is based on the present PS performance (5×10^{11} protons/pulse). Mills has shown that a further increase of beam current in the storage rings by an order of magnitude is theoretically possible.

The background interaction rate caused by collisions of the circulating protons with the residual gas atoms at a pressure of 10^{-10} mm Hg, is about 4.8×10^4 events/sec per meter of beam. If 10 m of beam effectively contribute to the background in the interaction region, the number of background events is 2.6 times larger than the number of colliding beam events. These reaction rates can easily be handled by existing electronics and spark chamber techniques.

It is also possible to stack protons at lower energy, but then the adiabatic damping of the betatron and synchrotron oscillations during acceleration is less effective. The colliding beam interaction rate is proportional to $E^{5/2}$, while the background is proportional to E .

III. Layout of the interaction region

The interaction region and adjacent CSR magnets are shown in Fig. 2. We have assumed that different magnets are used for bending and focusing,

since this leads to a larger flexibility in the use of the CSR, as will be shown below. Each SR then consists of 96 bending magnets, 52 long quadrupoles and 88 short quadrupoles. The free length in between the coils of the quadrupoles adjacent to the long straight sections that contain the interaction regions is 9 m.

Fig. 2 also shows possible orbits of two colliding protons that are elastically scattered in the interaction region. Due to the relatively large background from the residual gas it will always be necessary to detect both elastically scattered protons in coincidence in order to identify the reaction. The same is true for inelastic reactions in which secondaries are produced. Extrapolation of present data obtained with 25 GeV protons on a stationary target indicates that most of the reaction products will come off at rather small angles (some tens of milliradians) to the primary beams and therefore the CSR magnets must be designed to obstruct these particles as little as possible.

The quadrupoles of the magnet periods adjacent to the interaction regions are completely open in the median plane. Their yokes are on the top and the bottom, while the return windings of the coils are on the sides. The spacing between the coils is about 40 cm. A schematic cross-section of such a quadrupole is shown in Fig. 3. The bending magnets are of the C-type with their yokes arranged such that particles scattered in diametrically opposite directions can be observed. By suitable arranging magnet return yokes and mountings, and by judicious design of the vacuum chambers a continuous range of angles, from about 6 milliradians to 90° could be covered, although not all in the same interaction region.

In many cases it is necessary to measure the momenta of the elastically or quasi elastically scattered protons with a precision better than 1 o/o. For small angle scattered particles this can only be done by using the bending magnets of the CSR at the same time as analyzing magnets for the scattered particles. To make full use of this possibility it would be

advantageous to use special bending magnets, with the same length and magnetic field but larger transversal dimensions in place of magnets 2 and 4. Special spark chambers could be built in the gap of these magnets around the SR vacuum chamber.

By using a large (say 20 cm) gap height, one can observe protons that are vertically scattered over very small angles. A large gap width would cover a wide range of scattering angles in the horizontal plane.

Schemes for superposing the orbits of different momenta in order to obtain a small radial beam dimension in the interaction region, have been studied by Terwilliger⁴⁾ and Hereward⁵⁾. This does not increase the interaction rate, but has several advantages for the experiments. It is then also possible to observe very small angle scattered particles in the horizontal plane, while the interaction region as seen from magnets 2 and 4 presents itself as a small source of particles which allows a more accurate momentum analysis of the reaction products. Such superposition schemes lead to increased beam dimensions elsewhere in the SR and therefore it seems best to build one of these schemes into the CSR but to use it only when required for a specific experiment.

The ring building for the CSR has been indicated very schematically in Fig. 1. The maximum distance between the proton orbits in the two CSR is 7.9 m which leads to a minimum width for the ring building of about 13 m. Near the interaction regions this width should be increased to at least 30 m. We have also indicated two 25 GeV experimental halls, since the SR can be used to provide dc beams of secondaries by inserting stationary targets in the long straight sections.

IV. Detectors

In order to place the colliding beams in proper perspective relative to present techniques on existing accelerators, we should emphasize that

the interaction rate (1.8×10^5 per second) is equivalent to a beam of 6×10^5 protons passing through a 30 cm liquid hydrogen target in 0.1 second. The background rates in scintillation counters and spark chambers can be estimated accordingly. We believe that this, in fact, is the appropriate current analogy to colliding beam experiments of the future. Just as experimentalists now surround such liquid hydrogen targets in pion or proton beams of 10 - 30 GeV/c with counter arrays, spark chambers, and magnetic analyzers, we would similarly surround the colliding beam areas. Even the cryogenics might be similar, as a material reduction of background would result from cooling the adjacent vacuum pipe to liquid helium temperature.

Fig. 4 shows a possible arrangement of spark chambers around the interaction region. By using a sufficient number of spark chambers with suitable shapes one can cover a 4π solid angle, although this may not always be necessary. Fig. 4 also shows the yoke of a magnet which produces a magnetic field of about 2 Wb/m^2 at the position of the interaction region for the momentum analysis of low energy secondaries produced at large angles. The effect of the magnetic field at the interaction region is cancelled by the return flux which also crosses the proton orbits.

As the above discussion indicates, we place strong emphasis on the use of triggered spark chambers as tools for colliding beam experiments. Using the space and time resolution now available with spark chambers, the origin of an event could be localized and short-lived secondaries studied effectively even though their points of production and decay lay within the vacuum tank and outside the detector volume.

Although it has been said many times, it bears repeating that new detection techniques will probably be required to make the most effective use of colliding beams. However, we regard it as almost inevitable that such new techniques will turn up. For example, in the past, each new generation of accelerator has been accompanied by quite new detectors.

Thus the early cyclotrons were used primarily with Geiger counters, but it would not have been possible to exploit the post-war generation of synchrotrons and synchrocyclotrons with only Geiger counters. However, it was at about that time that scintillation counters were developed, and they were the dominant experimental tools for these machines. Similarly, the Bevatron and Cosmotron were built without prior knowledge of the bubble chamber, which, together with electromagnetic separators, has proven to be a most useful technique in this energy range. Currently, as the alternating gradient accelerators are commencing productive research, the scintillation chamber and spark chamber have progressed from development to practical usage, and they promise to materially increase the usefulness of these accelerators. We believe it would be unrealistic to assume that this rich development of detection technology is ending. On the contrary, we are sure that colliding beams will be used with detectors as unfamiliar to us today as the experimental technology at the P.S. would have been 10 years ago.

Acknowledgement

We want to thank Drs. K. Johnsen, G. K. O'Neill, L. Resegotti, A. Schoch and C. J. Zilverschoon for many stimulating discussions.

References

1. Symon, K. R. and Sessler, A. M.
CERN Symp. 1956, 1, p. 44.
2. Hereward, H. G., Johnsen, K., Schoch, A. and Zilverschoon, C. J.
Brookhaven Conference on High Energy Accelerators 1961.
3. O'Neill, G. K.
CERN Symp. 1959, p. 125.
4. Terwilliger, K. M.
CERN Symp. 1959, p. 53.
5. Hereward, H. G.
CERN PS Int/AR/60-34.

Figure captions

1. CERN PS with concentric storage rings.
2. Magnet layout around the interaction region.
3. Cross-section of quadrupole with open median plane.
4. Interaction region with superimposed magnetic field and spark chamber arrangement.

Fig. 1

Fig. 2

Fig. 3

Fig. 4
 Disposition of spark chambers
 around the interaction region
 with magnetic momentum analysis
 (20 MG field)